

Description:

Length: 0.698", grip: 0.375", thread: 10-32, reduced head, close tolerance, short thread, philips recess, cadmium plated alloy steel

NAS8603-6 Manufacturer certs (CofC) are provided free on all orders

Order this part online

**Additional Information**

Gov. Issued Name:	Screw, Close Tolerance
NSN:	5305-01-470-6949
NIIN:	014706949
FSC:	Screws / 5305
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS8603-6 Specifications

Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Fastener Length:	0.730 Inches Minimum And 0.760 Inches Maximum
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Head Diameter:	0.266 Inches Minimum And 0.303 Inches Maximum
Head Style:	Flat Countersunk
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Nominal Thread Diameter:	0.1900 Inches
Internal Drive Style:	Cross Recess Type 1
Material Document And Classification:	Mil-s-5000 Assn Std Single Material Response Overall And Mil-s-6049 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas8603 Professional/industrial Association Standard
Surface Treatment Document And Classification:	Qq-p-416 Assn Std Single Treatment Response Overall
Surface Treatment:	Cadmium Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close-tolerance-bolts/NAS8603-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.