

Description:

Fastener Length: 1-41/64", Thread: 1/4-28, Thread Length: 13/32"

NAS8704-20 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Close Tolerance
NSN:	5305-01-049-5665
NIIN:	010495665
FSC:	Screws / 5305
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS8704-20 Specifications

Countersink Angle:	100.0 Degrees Nominal
Fastener Length:	1.624 Inches Minimum And 1.654 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Head Diameter:	0.354 Inches Minimum And 0.399 Inches Maximum
Head Style:	Flat Countersunk
Material:	Iron Alloy 660 Overall
Nominal Thread Diameter:	0.250 Inches
Internal Drive Style:	High-torque
Specification/standard Data:	81205-bacb30II Professional/industrial Association Standard
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.364 Inches Minimum And 0.414 Inches Maximum
Thread Quantity Per Inch:	28
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close-tolerance-screws/NAS8704-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.