

Description:

Titanium alloy, flat countersunk head, right hand thread direction, NAS8803 series bolt

NAS8803A3 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Close Tolerance
NSN:	5305-01-337-6004
NIIN:	013376004
FSC:	Screws / 5305
Schedule B:	8109.90.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)
Manufacturer Country:	United States

NAS8803A3 Specifications

Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Fastener Length:	0.496 Inches Minimum And 0.526 Inches Maximum
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Head Diameter:	0.285 Inches Minimum And 0.303 Inches Maximum
Head Style:	Flat Countersunk
Material:	Titanium Alloy Uns R56400 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Cross Recess Type 1
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas8803 Professional/Industrial Association Standard
Surface Treatment:	Aluminum Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Thread Quantity Per Inch:	32
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close-tolerance-bolts/NAS8803A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.