

Description:

Thread: 10-32, titanium, flat countersunk head, NAS8803 series bolt

NAS8803A4 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Screw, Close Tolerance
NSN:	5305-01-338-7310
NIIN:	013387310
FSC:	Screws / 5305
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel
Manufacturer Country:	United States

NAS8803A4 Specifications

Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Fastener Length:	0.558 Inches Minimum And 0.588 Inches Maximum
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Head Diameter:	0.296 Inches Minimum And 0.303 Inches Maximum
Head Style:	Flat Countersunk
Material:	Titanium Alloy Uns R56400 Overall
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Internal Drive Style:	Cross Recess Type 1
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas8803 Professional/Industrial Association Standard
Surface Treatment:	Aluminum Overall
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Thread Quantity Per Inch:	32
Thread Series Designator:	Unf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close-tolerance-bolts/NAS8803A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.