

N and P-Channel Enhancement Mode Power MOSFET

Description

The NCE1205 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs may be used to form a level shifted high side switch, and for a host of other applications.

General Features

● N-Channel

$$V_{DS} = 12V, I_D = 5A$$

$$R_{DS(ON)} < 32m\Omega @ V_{GS} = 4.5V$$

$$R_{DS(ON)} < 42m\Omega @ V_{GS} = 2.5V$$

$$R_{DS(ON)} < 80m\Omega @ V_{GS} = 1.8V$$

● P-Channel


$$V_{DS} = -12V, I_D = -5A$$

$$R_{DS(ON)} < 74m\Omega @ V_{GS} = -4.5V$$

$$R_{DS(ON)} < 110m\Omega @ V_{GS} = -2.5V$$


$$R_{DS(ON)} < 220m\Omega @ V_{GS} = -1.8V$$

● Load Switch for Portable Devices



N-channel

P-channel



Pin assignment

Package Marking and Ordering Information

| Device Marking | Device | Device Package | Reel Size | Tape width | Quantity |
|----------------|---------|----------------|-----------|------------|----------|
| 1205 | NCE1205 | DFN2X2-6L | - | - | - |

Absolute Maximum Ratings ($T_A = 25^\circ C$ unless otherwise noted)

| Parameter | Symbol | N-Channel | P-Channel | Unit | |
|--|----------------|--------------------|------------|------------|---|
| Drain-Source Voltage | V_{DS} | 12 | -12 | V | |
| Gate-Source Voltage | V_{GS} | ± 12 | ± 12 | V | |
| Continuous Drain Current | I_D | $T_A = 25^\circ C$ | 5 | -5 | A |
| | | $T_A = 70^\circ C$ | 4.5 | -3.8 | |
| Pulsed Drain Current ^(Note 1) | I_{DM} | 20 | -15 | A | |
| Maximum Power Dissipation | P_D | 1.9 | 1.9 | W | |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -55 To 150 | -55 To 150 | $^\circ C$ | |

Thermal Characteristic

| | | | | |
|--|-----------------|------|----|--------------|
| Thermal Resistance, Junction-to-Ambient ^(Note2) | $R_{\theta JA}$ | N-Ch | 65 | $^\circ C/W$ |
| Thermal Resistance, Junction-to-Ambient ^(Note2) | $R_{\theta JA}$ | P-Ch | 65 | $^\circ C/W$ |

N-CH Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|---|--------------|---|-----|-----|-----------|------------|
| Off Characteristics | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=250\mu A$ | 12 | 20 | - | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS}=12V, V_{GS}=0V$ | - | - | 1 | μA |
| Gate-Body Leakage Current | I_{GSS} | $V_{GS}=\pm 12V, V_{DS}=0V$ | - | - | ± 100 | nA |
| On Characteristics (Note 3) | | | | | | |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_D=250\mu A$ | 0.4 | 0.6 | 1 | V |
| Drain-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS}=4.5V, I_D=5A$ | - | 28 | 32 | m Ω |
| | | $V_{GS}=2.5V, I_D=4.6A$ | - | 36 | 42 | m Ω |
| | | $V_{GS}=1.8V, I_D=4.1A$ | - | 55 | 80 | m Ω |
| Forward Transconductance | g_{FS} | $V_{DS}=10V, I_D=5A$ | - | 20 | - | S |
| Dynamic Characteristics (Note 4) | | | | | | |
| Input Capacitance | C_{iss} | $V_{DS}=6V, V_{GS}=0V,$ $F=1.0MHz$ | - | 495 | - | PF |
| Output Capacitance | C_{oss} | | - | 155 | - | PF |
| Reverse Transfer Capacitance | C_{rss} | | - | 95 | - | PF |
| Switching Characteristics (Note 4) | | | | | | |
| Turn-on Delay Time | $t_{d(on)}$ | $V_{DD}=6V, R_L=1.2\Omega$ $V_{GS}=10V, R_{GEN}=4.5\Omega$ | - | 7.0 | - | nS |
| Turn-on Rise Time | t_r | | - | 5.0 | - | nS |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 18 | - | nS |
| Turn-Off Fall Time | t_f | | - | 6 | - | nS |
| Total Gate Charge | Q_g | $V_{DS}=6V, I_D=5A,$ $V_{GS}=4.5V$ | - | 6.6 | - | nC |
| Gate-Source Charge | Q_{gs} | | - | 1 | - | nC |
| Gate-Drain Charge | Q_{gd} | | - | 1.2 | - | nC |
| Drain-Source Diode Characteristics | | | | | | |
| Diode Forward Voltage (Note 3) | V_{SD} | $V_{GS}=0V, I_S=5A$ | - | - | 1.2 | V |

P-CH Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|---|--------------|---|------|------|-----------|------------|
| Off Characteristics | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=-250\mu A$ | -30 | -33 | - | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS}=-12V, V_{GS}=0V$ | - | - | -1 | μA |
| Gate-Body Leakage Current | I_{GSS} | $V_{GS}=\pm 12V, V_{DS}=0V$ | - | - | ± 100 | nA |
| On Characteristics (Note 3) | | | | | | |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_D=-250\mu A$ | -0.4 | -0.7 | -1 | V |
| Drain-Source On-State Resistance | $R_{DS(ON)}$ | $V_{GS}=-4.5V, I_D=-4.5A$ | - | 60 | 74 | m Ω |
| | | $V_{GS}=-2.5V, I_D=-3.2A$ | - | 84 | 110 | m Ω |
| | | $V_{GS}=-1.8V, I_D=-1A$ | - | 130 | 220 | m Ω |
| Forward Transconductance | g_{FS} | $V_{DS}=-10V, I_D=-5A$ | - | 10 | - | S |
| Dynamic Characteristics (Note 4) | | | | | | |
| Input Capacitance | C_{ISS} | $V_{DS}=-6V, V_{GS}=0V,$ $F=1.0MHz$ | - | 520 | - | PF |
| Output Capacitance | C_{OSS} | | - | 100 | - | PF |
| Reverse Transfer Capacitance | C_{RSS} | | - | 65 | - | PF |
| Switching Characteristics (Note 4) | | | | | | |
| Turn-on Delay Time | $t_{d(on)}$ | $V_{DD}=-6V, R_L=2.3\Omega$ $V_{GS}=-10V, R_{GEN}=6\Omega$ | - | 7.5 | - | nS |
| Turn-on Rise Time | t_r | | - | 5.5 | - | nS |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 19 | - | nS |
| Turn-Off Fall Time | t_f | | - | 7 | - | nS |
| Total Gate Charge | Q_g | $V_{DS}=-6V, I_D=-4.5A$ $V_{GS}=-4.5V$ | - | 9.2 | - | nC |
| Gate-Source Charge | Q_{gs} | | - | 1.6 | - | nC |
| Gate-Drain Charge | Q_{gd} | | - | 2.2 | - | nC |
| Drain-Source Diode Characteristics | | | | | | |
| Diode Forward Voltage (Note 3) | V_{SD} | $V_{GS}=0V, I_S=-5A$ | - | - | -1.2 | V |

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production

N- Channel Typical Electrical and Thermal Characteristics (Curves)




Figure 1: Switching Test Circuit




Figure 2: Switching Waveforms




Figure 3 Output Characteristics




Figure 4 Transfer Characteristics




Figure 5 Drain-Source On-Resistance







Figure 6 Drain-Source On-Resistance




Vgs Gate-Source Voltage (V)
Figure 7 Rdson vs Vgs




Tj Junction Temperature (°C)
Figure 8 Power Dissipation




Qg Gate Charge (nC)
Figure 9 Gate Charge



Vds Drain-Source Voltage (V)
Figure 10 Source- Drain Diode Forward



Vds Drain-Source Voltage (V)
Figure 11 Capacitance vs Vds



Vds Drain-Source Voltage (V)
Figure 12 Safe Operation Area




Figure 13 Normalized Maximum Transient Thermal Impedance

P- Channel Typical Electrical and Thermal Characteristics (Curves)




Figure 1 Output Characteristics




Figure 4 Rdson-Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 Rdson- Drain Current







Figure 6 Source- Drain Diode Forward




Vds Drain-Source Voltage (V)
Figure 7 Capacitance vs Vds




T_J-Junction Temperature(°C)
Figure 9 BV_{DSS} vs Junction Temperature






Vds Drain-Source Voltage (V)
Figure 8 Safe Operation Area



T_J-Junction Temperature(°C)
Figure 10 V_{GS(th)} vs Junction Temperature



Square Wave Pulse Duration(sec)
Figure 11 Normalized Maximum Transient Thermal Impedance

DFN2X2-6L Package Information

Top View

Bottom View

Side View

| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------------|----------------------|-------------|
| | Min. | Max. | Min. | Max. |
| A | 0.700/0.800 | 0.800/0.900 | 0.028/0.031 | 0.031/0.035 |
| A1 | 0.000 | 0.050 | 0.000 | 0.002 |
| A3 | 0.203REF. | | 0.008REF. | |
| D | 1.924 | 2.076 | 0.076 | 0.082 |
| E | 1.924 | 2.076 | 0.076 | 0.082 |
| D1 | 0.520 | 0.720 | 0.020 | 0.028 |
| E1 | 0.900 | 1.100 | 0.035 | 0.043 |
| k | 0.200MIN. | | 0.008MIN. | |
| b | 0.250 | 0.350 | 0.010 | 0.014 |
| e | 0.650TYP. | | 0.026TYP. | |
| L | 0.174 | 0.326 | 0.007 | 0.013 |

Attention

- Any and all NCE power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your NCE power representative nearest you before using any NCE power products described or contained herein in such applications.
- NCE power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all NCE power products described or contained herein.
- Specifications of any and all NCE power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- NCE power Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all NCE power products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of NCE power Semiconductor CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. NCE power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the NCE power product that you intend to use.
- This catalog provides information as of Sep.2010. Specifications and information herein are subject to change without notice.