

NCS37005

Product Preview

Ground Fault Interrupter (GFI)

Description

The NCS37005 is a signal processor for GFI applications. The device integrates a flexible power supply (including both shunt and LDO regulators), and differential fault detection circuits. The proprietary fault processing circuitry offers high performance with low turns ratio ferrite current transformers. The device also includes a specialized DSP controller that offers best in class immunity to nuisance loads without the need for external analog filters.

Features

- 6.0 – 18 Volt Operation (120 – 480 V AC Mains with the Appropriate Series Impedance)
- –40 to 85°C
- Very Low Power Consumption: <5 mW @ 5 V
- 16 Pin QFN Package
- Low Cost/Turns Ratio Ferrite Current Transformer (CT) Detection of Differential
- Self Syncing Internal Oscillator Adjusts to AC Mains Frequency to Guarantee Full Resolution on 50 and 60 Hz Distribution Systems
- Optimized Solenoid Deployment (coil is not energized near the AC mains zero crossings)
- Randomized Testing Sequence to Minimize Noise and Potential Interactions on the AC Mains
- >5 mA SCR Driver for Additional Immunity to Supply Noise/Interference
- Superior Immunity to Nuisance Loads/Noise (up to 10 A) without Loss of Detection Capability or CT Saturation
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications


- Load Panel GFI/RCD Breakers
- GFI Receptacles
- In-line GFI Circuits (power cords)

This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.



ON Semiconductor®

<http://onsemi.com>




MARKING DIAGRAM



XXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
G or ■ = Pb-Free Package
CCCCC = Country of Origin

PIN CONNECTIONS



ORDERING INFORMATION

| Device | Package | Shipping† |
|---------------|---------|-------------|
| NCS37005MNTWG | QFN16 | Tape & Reel |
| NCS37005MNG | QFN16 | Tube |
| NCS37005DARG | TSSOP20 | Tape & Reel |
| NCS37005DAG | TSSOP20 | Tube |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

NCS37005




Figure 1. Simplified Block Diagram

NCS37005

Table 1. PIN FUNCTION DESCRIPTION – QFN

| Pin # | Name | Pad Description |
|-------|--------|---|
| 0 | Ground | QFN center slug |
| 1 | MLD | Mains Level Detect (Zero Cross) |
| 2 | CTtest | Test port (Must be tied to CTbias in functional mode). |
| 3 | CTbias | 2 V reference that is connected to the external CT sensor |
| 4 | CTstim | Differential current measurement port for external CT |
| 5 | CTresD | Determines IV converter gain for detection threshold / matched to CT turns ratio (Differential Current) |
| 6 | IDF | Front end noise filter capacitor |
| 7 | NC | Tie to Ground or leave floating |
| 8 | NC | Tie to Ground or leave floating |
| 9 | NC | Tie to Ground or leave floating |
| 10 | NC | Tie to Ground or leave floating |
| 11 | NC | Tie to Ground or leave floating |
| 12 | NC | Tie to Ground or leave floating |
| 13 | NC | Float |
| 14 | NC | Float |
| 15 | SCRdrv | Used to trigger the solenoid at a fault detection |
| 16 | Supply | Power supply |

Table 2. PIN FUNCTION DESCRIPTION – TSSOP

| Pin # | Name | Pad Description |
|-------|--------|---|
| 1 | CTstim | Differential current measurement port for external CT |
| 2 | Ground | Main ground connection for IC. |
| 3 | CTresD | Determines IV converter gain for detection threshold / matched to CT turns ratio (Differential Current) |
| 4 | IDF | Front end noise filter capacitor |
| 5 | TE | Test enable |
| 6 | NC | Tie to Ground or leave floating |
| 7 | NC | Tie to Ground or leave floating |
| 8 | NC | Tie to Ground or leave floating |
| 9 | NC | Tie to Ground or leave floating |
| 10 | NC | Tie to Ground or leave floating |
| 11 | NC | Float |
| 12 | NC | Float |
| 13 | SCRdrv | Used to trigger the solenoid at a fault detection |
| 14 | Supply | Power supply |
| 15 | MLD | Mains Level Detect (Zero Cross) |
| 16 | CTbias | 2 V reference that is connected to the external CT sensor |

Table 3. ABSOLUTE MAXIMUM RATINGS

| Rating | Symbol | Value | Unit |
|---|---------------------|---|------|
| Supply Voltage Range | V _s | 6.0 to 19 V | V |
| Input Voltage Range (Note 1) | V _{in} | -0.3 to 6.0 | V |
| Output Voltage Range | V _{out} | -0.3 to 6.0 V or (V _{in} + 0.3), whichever is lower | V |
| Maximum Junction Temperature | T _{J(max)} | 140 | °C |
| Storage Temperature Range | TSTG | -65 to 150 | °C |
| ESD Capability, Human Body Model (Note 2) | ESDHBM | 2 | kV |
| ESD Capability, Machine Model (Note 2) | ESDMM | 200 | V |
| Lead Temperature Soldering Reflow (SMD Styles Only), Pb-Free Versions (Note 3) | T _{SLD} | 260 | °C |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

- Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.
- This device series incorporates ESD protection and is tested by the following methods:
ESD Human Body Model tested per AEC-Q100-002 (EIA/JESD22-A114)
ESD Machine Model tested per AEC-Q100-003 (EIA/JESD22-A115)
Latchup Current Maximum Rating: ≤ 150 mA per JEDEC standard: JESD78
- For information, please refer to our Soldering and Mounting Techniques Reference Manual, SOLDERRM/D

Table 4. THERMAL CHARACTERISTICS

| Rating | Symbol | Value | Unit |
|--|--------------------------------------|-------|------|
| Thermal Characteristics, QFN16, 3x3.3 mm (Note 4) Thermal Resistance, Junction-to-Air (Note 5) Thermal Reference, Junction-to-Lead2 (Note 5) | R _{θJA} R _{ψJL} | 64 | °C/W |
| Thermal Characteristics, TSOP-5 (Note 4) Thermal Resistance, Junction-to-Air (Note 5) | R _{θJA} | | °C/W |

- Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.
- Values based on copper area of 645 mm² (or 1 in²) of 1 oz copper thickness and FR4 PCB substrate.

Table 5. OPERATING RANGES (Note 6)

| Parameter | Conditions | Min | Typ | Max | Units |
|-------------------------------|--|-----|-----|-----|-------|
| Operating Temperature | | -40 | | 85 | C |
| IDD | | | 2 | | mA |
| SCR Trigger Current | | | | 8 | mA |
| SCR Trigger output voltage | With 5 V supply | 4.5 | | 5 | V |
| Fault Current Sensitivity | Ground Fault with ±1% resistor for RctresD | 4.5 | 5 | 5.5 | mA |
| Ground Fault Response Time | 5-20 mA | | | 150 | ms |
| Ground Fault Response Time | 20-100 mA | | | 75 | ms |
| Ground Fault Response Time | >100 mA | | | 25 | ms |
| CT Turns Ratio | | 100 | | 300 | |
| Internal Oscillator Frequency | | | 2 | | MHz |
| CT Driver Closed Loop BW | | | | 500 | KHz |

- Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.

APPLICATIONS INFORMATION




Figure 2. Typical Application Schematic

NCS37005

RECOMMENDED EXTERNAL COMPONENTS:

| Component Type | Instance | Value | Note |
|----------------|----------|-----------------|---|
| SCR | Q1 | - | ON-MCR08 |
| Diode | Dx | - | ON-1N4007 |
| Capacitor | Csup | 1 – 4.7 μ F | For a full bridge rectifier |
| Capacitor | Cidf | 180 – 220 nF | Differential current filtering |
| Resistor | RctD | 20 – 70 K | Matched to current transformer |
| Resistor | Rzc | 400 – 800 K | Zero cross detection resistor. Value limits current |
| Resistor | Rmains | 10 – 45 K | For a full bridge rectifier |
| TVS | T1 | - | ~250 – 400 V |

Filtering

The analog signal capture portion of the IC includes a single pole filter that can be set externally with Cidf. This provides an additional layer of protection against false tripping under steady state noise conditions. High frequency steady state noise is common with pumps, motors or other cyclic noise generators.

Cidf = 220 nF = 1 KHz low pass.

Setting Trip Sensitivity




The CTresD resistor sets the threshold for the differential current fault levels. Increasing CTresD causes the fault levels to trip at lower differential currents. CT efficiency at 60 Hz must be considered.

. CTresD= 400*#Turns – Subject to CT efficiency at 60 Hz

NCS37005



PACKAGE DIMENSIONS

QFN16 3x3, 0.5P
CASE 485G-01
ISSUE F



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 2. CONTROLLING DIMENSION: MILLIMETERS.
 3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
 4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| MILLIMETERS | | | |
|-------------|----------|------|------|
| DIM | MIN | NOM | MAX |
| A | 0.80 | 0.90 | 1.00 |
| A1 | 0.00 | 0.03 | 0.05 |
| A3 | 0.20 REF | | |
| b | 0.18 | 0.24 | 0.30 |
| D | 3.00 BSC | | |
| D2 | 1.65 | 1.75 | 1.85 |
| E | 3.00 BSC | | |
| E2 | 1.65 | 1.75 | 1.85 |
| e | 0.50 BSC | | |
| K | 0.18 TYP | | |
| L | 0.30 | 0.40 | 0.50 |
| L1 | 0.00 | 0.08 | 0.15 |



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative