

Crystal Oscillator

Model Name NH25M22WC Oven-Controlled Crystal Oscillator (OCXO) for Fixed Communication Equipment

www.DataSheet4U.com

Main Application

- Mobile communication base station
- Measuring instrument
- Synthesizer
- Exchanger
- High-end router

Features

- Compact, with a low height.
- A surface-mount (SMD) package.
- Reflow soldering is possible.
- Excellent phase noise characteristics.
- Excellent aging characteristics.



RoHS Compliant
Directive 2002/95/EC

Specifications


Item	Measurement condition	Model	NH25M22WC
Standard nominal frequency (MHz)			10
Power supply voltage			DC +5V
Power consumption			3 W max. at the start and 2 W max. when stable (+25°C)
Output level			HCMOS (V _{OL} : 0.5V max., V _{OH} : 4.5V min.)
Load			15pF
Duty Cycle (1/2V _{cc})			40 to 60%
Operating temperature range			-10 to +70°C
Frequency stability	Frequency warm-up characteristic	+25°C five minutes after power is on	±200×10 ⁻⁹ max.
	Aging	Based on frequency after 30 days operation	±2×10 ⁻⁹ /day max.
		Based on frequency after 30 days operation	±100×10 ⁻⁹ /year max.
	Frequency / temperature characteristic	-10 to +70°C	±20×10 ⁻⁹ max.
	Power supply variation characteristics	DC +5V±5%	±10×10 ⁻⁹ max.
Frequency control characteristic	0 to +5 V, positive polarity		±1.0×10 ⁻⁶ min.

Reference Value

Phase noise (@10MHz)	Offset frequency	dBc/Hz
	1 Hz	-70 max.
	10 Hz	-100 max.
	100 Hz	-120 max.
	1k Hz	-135 max.
	10k Hz	-135 max.

The value of phase noise changes when the frequency changes.

Dimensions



List of Options

Power supply voltage	DC +3.3V
Nominal frequency (MHz)	10 to 20

For details of options, please feel free to contact our sales representatives.

List of Ordering Codes

Frequency (MHz)	Ordering Code
10	NH25M22WC-10M-NSA3419A

The above frequencies are NDK's standard frequencies. Frequencies other than the above are available. Feel free to contact our sales representatives.