



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE15007 Integrated Circuit TV Stereo Multiplexing Decoder

Description:

The NTE15007 is a bipolar integrated circuit is a 42-Lead DIP type package designed for use in TV stereo multiplexing decoding, filters for stereo, and SAP (Separate Audio Program) demodulation applications.

Features:

- Low number of external parts
- Excellent channel separation characteristics for stereo applications. Min. 46dB at 1kHz.
- Selection of individual modes of MAIN/SAP/BOTH.
- Direct driving mode for LED display.

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Supply Voltage, V_{CC} 17V
 Allowed Power Dissipation, P_D 1800mW
 Individual Controlling Pins, $V_{14 \text{ to } 17}, V_{20}$ $V_{CC} + 0.3V$
 LED Driving Current, I_{LED} 25mA
 Operating Temperature Range, T_{opr} -10° to $+65^\circ\text{C}$
 Storage Temperature Range, T_{stg} -55° to $+150^\circ\text{C}$

Recommended Operating Condition:

Power Supply Voltage, V_{CC} $9.0 \pm 0.5V$

Electrical Characteristics: ($V_{CC} = 9V$, $\text{dBs} = 0.775V_{rms}$, $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
SAP Noise Level	$V_{SAP,N}$	Pin1 Input $5f_H$ (-14.4dBs) Pin25 Output 15kHz LPF is attached.	–	–40	–36	dB
SAP Carrier Leakage	CL_{SAP}	Pin1 Input $5f_H$ (-14.4dBs) Pin25 Output	–	–33	–30	dB
SAP Carrier Detecting Sensitivity	$SCARR$	Pin1 Input $5f_H$ Input level during LED of Pin18 is lighting on	–29.0	–25.0	–21.5	dB
SAP Frequency Characteristics 10kHz	A_{SAP}	Pin1 Input SAP 10kHz 100% (-14.4dBs) Pin25 Output 15kHz IPF is attached	–4.0	–1.5	2.0	dB

Electrical Characteristics (Cont'd): ($V_{CC} = 9V$, $dBs = 0.775V_{rms}$, $T_A = +25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
SAP Output Level	V_{SAP}	Pin1 Input SAP 1kHz 100% (-14.4dBs) Pin25 Output 15kHz LPF is attached	-0.8	-0.1	0.6	dB
SAP Distortion Ratio	THD_{SAP}	Pin1 Input SAP 1kHz 100% (-14.4dBs) Pin25 Output 15kHz LPF is attached	-	4.0	8.0	%
SAP BPF Frequency Characteristics $5f_H$	A BPF $5f_H$	Pin1 Input $5f_H$ (-14.4dBs) Pin6 Output	-16	-13.5	-12.5	dB
SAP BPF Frequency Characteristics $3f_H$	A BPF $3f_H$	Pin1 Input $3f_H$ (-14.4dBs) Pin6 Output	-	-32.5	-29.5	dB
SAP BPF Frequency Characteristics $6.5f_H$	A BPF $6.5f_H$	Pin1 Input $6.5f_H$ (-14.4dBs) Pin6 Output	-	-31.6	-29.5	dB
SAP Detecting Characteristics	$V_{SAP FM}$	Pin8 Input 63.37kHz (-14.4dBs) 93.67kHz (-14.4dBs) Pin25 Output	100	110	118	mV/kHz
SAP Muting Attenuation Amount	AT_{SAP}	Pin8 Input SAP 1kHz 100% (-14.4dBs) Pin25 Output	-	-68	-65	dB
MONAURAL Noise Level	$V_{ST NM}$	Non-input Pin23 Output 15kHz LPF is attached	-	-75	-70	dB
STEREO Noise Level	$V_{ST NS}$	Pin1 f_H (-24dBs) Pin40 to Pin41 -6dB ATT Pin24 Output 15kHz LPF is attached	-	-70	-66	dB
MAIN Output Level	V_{MAIN}	Pin1 Input 1kHz (-10dBs) 75 μ s de-emphasis is attached Pin23 Output 15kHz LPF is attached	-5.6	-5.0	-4.6	dB
SUB Detecting Level	V_{SUB}	Pin1 Input SUB 1kHz 100% Pin40 to Pin41 -6dB ATT Pin24 Output 15kHz LPF is attached	-12	-	-9	dB
MONAURAL Distortion Ratio	THD_{MONO}	Pin1 Input 1kHz (-10dBs) Pin23 Output 15kHz LPF is attached	-	0.25	0.50	%
STEREO Distortion	THD_{STE}	Pin1 Input SUB 1kHz 100% Pin24 Output 15kHz LPF is attached	-	0.75	1.20	%
Pilot Cancel (L + R)	PC_{L+R}	Pin1 Input f_H (-24dBs) 75 μ s de-emphasis is attached Pin23 Output f_H BPF is attached	-	-57.0	-51.5	dB
Pilot Cancel (L - R)	PC_{L-R}	Pin1 Input f_H (-24dBs) Pin40 to Pin41 -6dB ATT Pin24 Output f_H BPF is attached	-	-41	-35	dB

Electrical Characteristics (Cont'd): ($V_{CC} = 9V$, $dBs = 0.775V_{rms}$, $T_A = +25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
MAIN Balance Between Channels	CB_{MAIN}	Pin34 Input f_H (-18dBs) Input 1kHz (-4dBs) to Pin28 and find the output level difference between Pin22 and Pin23 by measuring the outputs of Pin22 and Pin23 independently	-0.3	0	0.3	dB
SUB Balance Between Channels	CB_{SUB}	Input 1kHz (-4dBs) to Pin27 and find the output level difference between Pin22 and Pin23 by measuring the outputs of Pin22 and Pin23 independently. The above applicable to Pin28 except that non-input to Pin28.	-0.3	0	0.3	dB
Separation Check 1kHz	SEP_{1k}	Pin1 input L Ch 100% DSB 1kHz Measure phase difference between the outputs of Pin24 and Pin23.	46	60	-	dB
Crosstalk (L - R) \leftrightarrow (SAP)	$CT_{L-R\ SAP}$	Pin26 and Pin41 Input 1kHz (-4dBs) Pin24 Output +1kHz BPF	-	-80	-67	dB
Crosstalk L \leftrightarrow SAP	CT_{LSAP}	Pin27 and Pin28 Output 1kHz (-4dBs) Pin23 Output + 1kHz BPF	-	-80	-74	dB
Crosstalk R \leftrightarrow SAP	CT_{RSAP}	Pin27 and Pin28 Input 1kHz (-4dBs) Pin22 Output + 1kHz BPF	-	-80	-74	dB
Stereo LPF Frequency Characteristics (6 f_H)	ALP1 6 f_H	Pin1 Input 6 f_H (-10dBs) Pin37 Output	-	-45	-36	dB
(L + R) LPF Frequency Characteristics (12kHz)	ALP2 12k	Pin34 Input 12kHz (-4dBs) Pin29 Output	-5.2	-4.3	-2.8	dB
(L + R) LPF Frequency Characteristics (2 f_H)	ALP2 2 f_H	Pin34 Input 2 f_H (-4dBs) Pin29 Output	-	-52	-43	dB
L - R LPF Frequency Characteristics (12kHz)	ALP3 12k	Pin26 Input 12kHz (-4dBs) Pin24 Output	-6.5	-5.3	-4.0	dB
L - R LPF Frequency Characteristics (2 f_H)	ALP3 2 f_H	Pin26 Input 2 f_H (-4dBs) Pin24 Output	-	-52	-43	dB
Stereo Capture Range LOW	CR_{LO}	Pin34 Input f_H vicinity (-18dBs) Measure the input frequency when the LED of Pin19 goes on and off by changing the burst signal frequency	-	-	14.95	kHz
Stereo Capture Range HIGH	CR_{HI}	Pin35 and Pin36, 1 μ F and 4.7 μ F 560 Ω	16.52	-	-	kHz

Electrical Characteristics (Cont'd): ($V_{CC} = 9V$, $\text{dBs} = 0.775V_{\text{rms}}$, $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
During Forced Monaural Crosstalk (L)	CT_L	Pin27 Input 1kHz (-4dBs) Pin23 Output +1kHz BPF	-	-80	-74	dB
During Forced Monaural Crosstalk (R)	CT_R	Pin27 Input 1kHz (-4dBs) Pin22 Output +1kHz BPF	-	-80	-74	dB
Muting SW V15 High Muting Attenuation Amount (L) (R)	AT_{STL}	Pin27 Input 1kHz (-4dBs) Pin22 and Pin23 Output +15kHz LPF	-	-80	-74	dB
DC Offset Voltage while Muting and Stereo are turned on	VO_{MUST}	During no-input	-50	5	50	mV
DC Offset Voltage while Muting and SAP are turned on	VO_{MUSAP}	During no-input	-120	-20	120	mV
DC Offset Voltage while SAP and Monaural are turned on	VO_{SAPMO}	During no-input	-50	0	50	mV
DC Offset Voltage while SAP and Stereo are turned on	VO_{SAPST}	During no-input	-120	0	120	mV
DC Offset Voltage while Stereo and Monaural are turned on	VO_{STM}	During no-input	-120	-20	120	mV
Circuit Current	I_{CC}	Value of inflowing current into Pin42	25	36	48	mA
V_{14} , V_{15} , V_{16} and V_{17} Controlling Voltage (L)	V_{XL}		GND	-	1.0	V
V_{14} , V_{15} , V_{16} , and V_{17} Controlling Voltage (H)	V_{XH}		2.5	-	V_{CC}	V
V_{13} and V_{20} Controlling Voltage (L)	V_{ZL}		GND	-	1.0	V
V_{13} and V_{20} Controlling Voltage (M)	V_{ZM}		2.5	-	5.5	V
V_{13} and V_{20} Controlling Voltage (H)	V_{ZH}		8.0	-	V_{CC}	V
Stereo Discriminating Level	$STE V_{th}$	Pin30 and Pin31 10 μ F f_H level is variable	12	26	39	mV_{rms}
Regulator Voltage	V_{REG}	Pin9 DC	6.7	-	-	V

Note 1. This device is for REPLACEMENT ONLY! No design information is available.

Pin Connection Diagram

MPX Input	1	42	V _{CC}
N.C.	2	41	(L+R) Switch Input
Stereo Filter Adjust	3	40	(L+R) Detector Output
SAP Filter Adjust	4	39	TP
Bias	5	38	N.C.
SAP BPF Output	6	37	Stereo LPF Output
N.C.	7	36	Phase Det (+)
SAP Detector Input	8	35	Phase Det (-)
Reg Out 6.7V	9	34	Stereo Input
SAP VCO Adjust	10	33	Stereo GND
Car Det	11	32	ST VCO Adjust
SAP GND	12	31	Pilot Det (+)
SAP SQU Inhibit	13	30	Pilot Det (-)
SAP Mute	14	29	L+R Output
Mute	15	28	Matrix L+R Input
MS 1	16	27	Matrix L+R/SAP Input
MS 0	17	26	SAP Switch Input
SAP Ind Drive	18	25	SAP Det Output
Stereo Ind Drive	19	24	(L+R) SAP Output
Forced Monaural	20	23	Line Output L
LED GND	21	22	Line Output R

