



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE30125 Super Bright LED Indicator Super Bright Pink, 3mm

Features:

- High Intensity
- Normal T-1 (3mm) Diameter Package
- General Purpose Leads
- Reliable and Rugged

Absolute Maximum Ratings: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Power Dissipation, P_D 80mW
Peak Forward Current (1/10th Duty Cycle, 0.1ms Pulse Width), I_{FM} 100mA
Continuous Forward Current, I_F 25mA
Derate Linearly From $+30^{\circ}\text{C}$ $0.8\text{mA}/^{\circ}\text{C}$
Reverse Voltage, V_R 5V
Operating Temperature Range, T_{opr} -20° to $+80^{\circ}\text{C}$
Storage Temperature Range, T_{stg} -30° to $+80^{\circ}\text{C}$
Lead Temperature (During Soldering, 1.6mm from Body, 5sec Max), T_L $+260^{\circ}\text{C}$

Electrical Optical Characteristics: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Luminous Intensity	I_V	$I_F = 20\text{mA}$	700	–	1000	mcd
View Angle of Half Power	$2 \theta_{1/2}$		25	30	35	deg
Chromatality Coordinate	X	$I_F = 20\text{mA}$	0.28	0.30	0.32	
Chromatality Coordinate	Y	$I_F = 20\text{mA}$	0.28	0.30	0.32	
Forward Voltage	V_F	$I_F = 20\text{mA}$	3.0	3.3	3.6	V
Reverse Current	I_R	$V_R = 5\text{V}$	–	–	10	μA

