



## NTE7084 Integrated Circuit Color TV Sync Deflection Circuit

### **Description:**

The NTE7084 is an IC containing not only the main functions required to achieve synchronization and deflection in color television receivers but also a generator of horizontal, vertical blanking pulses, and a generator of burst gate pulses (sandcastle type) in an 18-Lead DIP type package. This is a multi-functional device ideally suited for use in color television receivers aiming at high-quality picture reproduction.

### **Functions:**

- Synchronizing Separation
- Vertical Drive
- X-Ray Protection
- Sandcastle Pulse (Burst Gate Pulse + Horizontal Blanking Pulse)
- Composite Blanking Pulse (Vertical + Horizontal Blanking Pulse)
- Vertical Oscillation
- Horizontal AFC
- Horizontal Oscillation

### **Features:**

- Horizontal and Vertical Oscillations are Stable Against Variations in Ambient Temperature and Supply Voltage due to Small Warm-Up Drift.
- Small Variation in Horizontal Oscillation Frequency
- Good Linearity and Interlace because DC Bias at Vertical Output Stage is Subjected to Sampling Control Within Retrace Time.
- Vertical Blanking Pulse Width can be set freely by Peripheral Parts.
- Minimized Picture Distortion because AFC Circuit is Defeated During Vertical Trigger Pulse Input Period.
- Multifunctional and Compact

### **Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Maximum Supply Voltage, $V_{CC14}$ .....	14V
Maximum Current Dissipation, $I_{CC18}$ .....	16mA
Maximum Applied Voltage, $V_{11}$ .....	-6V
Allowable Power Dissipation ( $T_A \leq +65^\circ\text{C}$ ), $P_D\text{max}$ .....	570mW
Operating Temperature Range, $T_{opr}$ .....	-20° to +85°C
Storage Temperature Range, $T_{stg}$ .....	-55° to +125°C

### **Recommended Operating Conditions:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Recommended Supply Voltage, $V_{CC14}$ .....	12V
--	-----

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ ,  $V_{CC14} = 12\text{V}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
$V_{CC14}$ Current Dissipation	$I_{CC14}$		13.5	—	29.0	mA
$V_{CC18}$ Supply Voltage	$V_{CC18}$		11.8	—	13.2	V
Zener Bias Minimum Current			—	—	13	mA
Sync Separator Input DC Level			9.0	—	9.6	V
Sync Signal Peak Value			9.5	—	11.5	V
Burst Gate Pulse Peak Value (SCP)			9.5	—	11.5	V
Burst Gate Pulse Delay Time 1 (SCP)	$T_{BR}$		—	—	0.5	$\mu\text{s}$
Burst Gate Pulse Delay Time 2 (SCP)	$T_{BF}$		3.6	—	4.2	$\mu\text{s}$
Horizontal Blanking Pulse Peak Value (SCP)			2.7	—	3.3	V
Horizontal Blanking Pulse Peak Value (CBP)		$I = 1\text{mA}$	12.7	—	13.5	V
Vertical Blanking Pulse Peak Value (CBP)		Load Resistance $R = 33\text{k}\Omega$	7.2	—	8.2	V
Vertical Frequency Pull-In Range		Vertical Sync 60Hz	9.0	—	11.0	Hz
Vertical Free-Running Frequency	$f_v$	$V_{R1} = f_v$ center 55Hz	50	—	60	Hz
Supply Voltage Dependence of Vertical Frequency		$V_{14} = 12\text{V} \pm 1\text{V}$ , 55Hz at 12V	-0.5	—	0.5	Hz
Middle Point Control Threshold Level			3.8	—	4.4	V
Vertical Blanking Threshold Level			5.0	—	5.7	V
Vertical Oscillation Start Voltage			—	—	4	V
Temperature Characteristic of Vertical Frequency		$T_A = -10^\circ$ to $+60^\circ\text{C}$	-0.028	—	0.028	$\text{Hz}/^\circ\text{C}$
Vertical Driver Amplification Factor			12	—	17	dB
Horizontal AFCD.C Loop Gain		+sign at $V_1 = 5\text{V}$ , -sign at $V_1 = 1\text{V}$	$\pm 0.6$	—	$\pm 1.5$	mA
Horizontal Free-Running Frequency	$f_H$	$f_H$ center 15.73kHz	-750	—	750	Hz
Horizontal Oscillation Start Voltage			—	—	4	V
Supply Voltage Dependence of Horizontal Frequency		$V_Z - V_Z \times 90\%$	-50	—	50	Hz

**Pin Connection Diagram**



