



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE74LS625 Integrated Circuit TTL – Dual Voltage Controlled Oscillator

Description:

The NTE74LS625 is a dual voltage controlled oscillator in a 16-Lead plastic DIP type package that is an improved version of the original NTE74LS325 VCO. This new device features improved voltage-to-frequency linearity, range, and compensation as well as two independent VCO's and has complementary Z outputs. The output frequency is established by a single external capacitor in combination with voltage-sensitive inputs used for frequency control and frequency range. This device has a voltage-sensitive input for frequency control.

A single 5V supply can be used; however, one set of supply voltage and ground pins (V_{CC} and GND) is provided for the enable, synchronization-gating, and output sections, and a separate set (OSC V_{CC} and OSC GND) is provided for the oscillator and associated frequency-control circuits so that effective isolation can be accomplished in the system. For operation of frequencies greater than 10Mhz, it is recommended that two independent supplies be used. Disabling either VCO can be achieved by removing the appropriate OSC V_{CC} . Caution! Crosstalk may occur when both VCO's are operated simultaneously.

The pulse-synchronization-gating section ensures that the first output pulse is neither clipped nor extended. The duty cycle of the square-wave output is fixed at approximately 50 percent.

Features:

- Separate Supply Voltage Pins for Isolation of Frequency Control Inputs and Oscillator from Output Circuitry
- Highly Stable Operation over Specified Temperature and/or Supply Voltage Ranges

Absolute Maximum Ratings: (Note 1)

Supply Voltage (Note 2), V_{CC}	7V
Input Voltage	7V
Operating Temperature Range, T_A	0°C to +70°C
Storage Temperature Range, T_{stg}	-65°C to +150°C

Note 1. Unless otherwise specified, all voltages are referenced to GND.

Note 2. Throughout the datasheet, the symbol V_{CC} is used for the voltage applied to both the V_{CC} and OSC V_{CC} terminals, unless otherwise noted.

Recommended Operating Conditions:

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	4.75	5.0	5.25	V
High-Level Output Current	I_{OH}	-	-	-1.2	mA
Low-Level Output Current	I_{OL}	-	-	24	mA
Output Frequency	f_o	1	-	-	Hz
		-	-	20	MHz
Operating Temperature Range	T_A	0	-	+70	°C

Electrical Characteristics: (Note 3, Note 4)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
High-Level Input Voltage	V_{IH}		2	-	-	V	
Low-Level Input Voltage	V_{IL}		-	-	0.8	V	
Input Clamp Voltage	V_{IK}	$V_{CC} = \text{MIN}, I_I = -18\text{mA}$	-	-	-1.5	V	
High-Level Output Voltage	V_{OH}	$V_{CC} = \text{MIN}, V_{IL} = \text{MAX}, I_{OH} = -1.2\text{mA}$, Note 5	2.7	3.4		V	
Low Level Output Voltage	V_{OL}	$V_{CC} = \text{MIN}, V_{IL} = \text{MAX}$, Note 5	$I_{OL} = 12\text{mA}$	-	0.25	0.4	V
			$I_{OL} = 24\text{mA}$	-	0.35	0.5	V
Input Current Freq Control	I_I	$V_{CC} = \text{MAX}$	$V_I = 5\text{V}$	-	50	250	μA
			$V_I = 1\text{V}$	-	10	50	μA
			$V_I = 7\text{V}$	-	-	0.2	mA
Input Current							
High Level Input Current	I_{IH}	$V_{CC} = \text{MAX}, V_I = 2.7\text{V}$	-	-	40	μA	
Low Level Input Current	I_{IL}	$V_{CC} = \text{MAX}, V_I = 0.4\text{V}$	-	-	-0.8	mA	
Short-Circuit Output Current	I_{OS}	$V_{CC} = \text{MAX}$, Note 6	-40	-	-225	mA	
Supply Current, Total into V_{CC} and OSC V_{CC} Pins	I_{CC}	$V_{CC} = \text{MAX}$, Note 7	-	35	55	mA	

Note 3. For conditions shown as MIN or MAX, use the appropriate value specified under "Recommended Operation Conditions".

Note 4. All typical values are at $V_{CC} = 5\text{V}$, $T_A = +25^\circ\text{C}$.

Note 5. V_{OH} for Y outputs and V_{OL} for Z outputs are measured while enable inputs are connected to ground, with individual $1\text{k}\Omega$ resistors connected from CX1 to V_{CC} and from CX2 to ground. The resistor connections are reversed for testing V_{OH} for Z outputs and V_{OL} for Y inputs.

Note 6. Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

Note 7. I_{CC} is measured with the outputs disabled and open.

Switching Characteristics: ($V_{CC} = 5\text{V}$, $R_L = 667\Omega$, $C_L = 45\text{pF}$, $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Output Frequency	f_o	$C_{ext} = 50\text{pF}$	$V_{I(\text{freq})} = 5\text{V}$	7.0	9.5	12	MHz
			$V_{I(\text{freq})} = 0\text{V}$	0.9	1.2	1.5	MHz

Pin Connection Diagram

