



NEC's InGaAsP MQW-DFB LASER DIODE IN CAN PACKAGE FOR 2.5 Gb/s, CWDM APPLICATIONS

**NX6508
Series**

FEATURES

- **OPTICAL OUTPUT POWER**
 $P_o = 5.0 \text{ mW}$
- **PEAK EMISSION WAVELENGTH**
 $\lambda_p = 1\,470 \text{ to } 1\,610 \text{ nm}$
(Based on ITU-T recommendations)
- **LOW THRESHOLD CURRENT**
 $I_{th} = 10 \text{ mA}$
- **HIGH SPEED**
 $t_r = 100 \text{ ps MAX}$
- **SIDE MODE SUPPRESSION RATIO**
 $\text{SMSR} = 40 \text{ dB}$
- **OPERATING CASE TEMPERATURE RANGE**
 $T_c = -20 \text{ to } +85^\circ\text{C}$
- **InGaAs MONITOR PIN-PD**
- **CAN PACKAGE**
 $\phi 5.6 \text{ mm}$
- **BASED ON TELCORDIA RELIABILITY**



DESCRIPTION

NEC's NX6508 Series are 1 470 to 1 610 nm Multiple Quantum Well (MQW) structured Distributed Feed-Back (DFB) laser diode with InGaAs monitor PIN-PD. These devices are ideal for 2.5 Gb/s CWDM application.

ELECTRO-OPTICAL CHARACTERISTICS ($T_c = -20 \text{ to } +85^\circ\text{C}$, unless otherwise specified)

	PART NUMBER		NX6508 SERIES			
SYMBOLS	PARAMETER AND CONDITIONS		UNIT	MIN.	TYP.	MAX.
P _o	Optical Output Power from Fiber, CW		mW		5.0	
V _{op}	Operating Voltage, P _o = 5.0 mW		V		1.1	1.6
I _{th}	Threshold Current, T _C = 25°C		mA		10	20
						50
η _d	Differential Efficiency	P _o = 5.0 mW, T _C = 25°C	W/A	0.18	0.25	
		P _o = 5.0 mW		0.10		
Δη _d	Temperature Dependence of Differential Efficiency Δη_d = 10 log $\frac{\eta_d (@ T_C^{\circ}C)}{\eta_d (@ 25^{\circ}C)}$		dB	−3.0	−1.6	
λ _p	Peak Emission Wavelength, P _o = 5.0 mW		nm	λ _p −2	λ _p *1	λ _p +2
Δλ/ΔT	Temperature Dependence of Peak Emission Wavelength, CW		nm/°C	0.08	0.1	0.12
SMSR	Side Mode Suppression Ratio, P _o = 5.0 mW		dB	30	40	
t _r	Rise Time, 20-80%, P _o = 5.0 mW		ps			100

Continued on next page

ELECTRO-OPTICAL CHARACTERISTICS (T_C = -20 to +85°C, unless otherwise specified)

SYMBOLS	PART NUMBER		NX6508 SERIES		
	PARAMETER AND CONDITIONS	UNIT	MIN.	TYP.	MAX.
t _f	Fall Time, 80-20%, P _o = 5.0 mW	ps			150
I _m	Monitor Current, V _R = 1.5 V, P _o = 5.0 mW	μA	200	1 000	2 000
I _d	Monitor Dark Current	V _R = 1.5 V, T _C = 25°C		0.1	10
		V _R = 1.5 V		10	100

*1 Available Available for CWDM Wavelengths based on ITU-T recommendations

λ_p = 1 470, 1 490, 1 510, 1 530, 1 550, 1 570, 1 590, 1 610 nm

Please refer to **Table A**.

Table A: CWDM wavelength code (@ T_C = 25°C)

WAVELENGTH CODE	MIN. (nm)	TYP. (nm)	MAX. (nm)
47	1 468	1 470	1 472
49	1 488	1 490	1 492
51	1 508	1 510	1 512
53	1 528	1 530	1 532
55	1 548	1 550	1 552
57	1 568	1 570	1 572
59	1 588	1 590	1 592
61	1 608	1 610	1 612

ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	UNIT	RATINGS
P _o	Optical Output Power from Fiber	mW	10
I _F	Forward Current of LD	mA	150
V _R	Reverse Voltage of LD	V	2.0
I _F	Forward Current of PD	mA	2.0
V _R	Reverse Voltage of PD	V	15
T _C	Operating Case Temperature	°C	-20 to +85
T _{stg}	Storage Temperature	°C	-40 to +85
T _{sld}	Lead Soldering Temperature	°C	350 (3 sec.)
RH	Relative Humidity	%	85

Subject: Compliance with EU Directives

CEL certifies, to its knowledge, that semiconductor and laser products detailed below are compliant with the requirements of European Union (EU) Directive 2002/95/EC Restriction on Use of Hazardous Substances in electrical and electronic equipment (RoHS) and the requirements of EU Directive 2003/11/EC Restriction on Penta and Octa BDE.

CEL Pb-free products have the same base part number with a suffix added. The suffix –A indicates that the device is Pb-free. The –AZ suffix is used to designate devices containing Pb which are exempted from the requirement of RoHS directive (*). In all cases the devices have Pb-free terminals. All devices with these suffixes meet the requirements of the RoHS directive.

This status is based on CEL's understanding of the EU Directives and knowledge of the materials that go into its products as of the date of disclosure of this information.

Restricted Substance per RoHS	Concentration Limit per RoHS (values are not yet fixed)	Concentration contained in CEL devices	
		-A	-AZ
Lead (Pb)	< 1000 PPM	Not Detected	(*)
Mercury	< 1000 PPM	Not Detected	
Cadmium	< 100 PPM	Not Detected	
Hexavalent Chromium	< 1000 PPM	Not Detected	
PBB	< 1000 PPM	Not Detected	
PBDE	< 1000 PPM	Not Detected	

If you should have any additional questions regarding our devices and compliance to environmental standards, please do not hesitate to contact your local representative.

Important Information and Disclaimer: Information provided by CEL on its website or in other communications concerning the substance content of its products represents knowledge and belief as of the date that it is provided. CEL bases its knowledge and belief on information provided by third parties and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. CEL has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. CEL and CEL suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall CEL's liability arising out of such information exceed the total purchase price of the CEL part(s) at issue sold by CEL to customer on an annual basis.

See CEL Terms and Conditions for additional clarification of warranties and liability.