


# Infrared Light Emitting Diode in Miniature SMD Package

## OP200

- Flat Lens
- High Power
- 0805 Package Size
- 880nm Wavelength





www.DataSheet4U.com

The OP200 is a GaAlAs infrared LEDs mounted in a miniature SMT package. The device incorporates a flat molded lens which enables a wide beam angle and provides an even emission pattern. This device is packaged in a 0805 size chip carrier that is compatible with most automated mounting equipment. The OP200 is mechanically and spectrally matched to the OP520 series phototransistors.

### Applications

- Non-Contact Position Sensing
- Machine automation
- Datum detection
- Optical encoders



OP200



RoHS

Optek reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPTEK Technology Inc.— 1645 Wallace Drive, Carrollton, Texas 75006  
Phone: (800) 341-4747 FAX: (972) 323-2396 sensors@optekinc.com www.optekinc.com



A subsidiary of  
www.DataSheet4U.com

# SMD Infrared LED

## OP200



### Absolute Maximum Ratings

$T_A = 25^\circ\text{C}$  unless otherwise noted

Storage Temperature Range	-40° C to +85° C
Operating Temperature Range	-25° C to +85° C
Lead Soldering Temperature	260° C <sup>(1)</sup>
Reverse Voltage	30 V
Continuous Forward Current	50 mA
Power Dissipation	130 mW <sup>(2)</sup>



Notes:

- Solder time less than 5 seconds at temperature extreme.
- De-rate linearly at 2.17 mW/° C above 25° C.

### Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	CONDITIONS
$E_{e(\text{APT})}$	Apertured Radiant Incidence	0.2			mW/cm <sup>2</sup>	$I_F = 20\text{mA}^{(3)}$
$V_F$	Forward Voltage			1.5	V	$I_F = 20\text{mA}$
$I_R$	Reverse Current			100	μA	$V_R = 2.0\text{V}$
$\lambda_P$	Peak Emission Wavelength		890		nm	$I_F = 10\text{mA}$
$\Theta_{\text{HP}}$	Emission Angle at Half Power Points		100		Deg.	$I_F = 20\text{mA}$
$t_r, t_f$	Rise and Fall Time			500	ns	$I_{F(\text{PEAK})} = 100\text{mA}$ , PW = 10μs, 10% D.C.




- $E_{e(\text{APT})}$  is a measurement of the apertured radiant incidence upon a sensing area 0.081" (2.06mm) in diameter, perpendicular to and centered on the mechanical axis of the lens, and 0.590" (14.99mm) from the measurement surface.  $E_{e(\text{APT})}$  is not necessarily uniform within the measured area.



# SMD Infrared LED

## OP200

www.DataSheet4U.com



PIN	FUNCTION
1	Anode
2	Cathode

DIMENSIONS ARE IN INCHES AND [MILLIMETERS].