



## OPTO-3800 Series Centronics Modems Printer Interface

The OPTO-3800 series are Centronics bus extenders which operate over fiber optic cable. The OPTO-3800 X consists of a terminal and a printer unit which can operate up to 30 kB/s for distances of 2.5 km.

### Specifications

<b>Data:</b>	Centronics Terminal & Printer Units 15,000 lines/minute
<b>Data Rate:</b>	30 kB/s
<b>Wavelength:</b>	850 nm
<b>No. of Fibers:</b>	2
<b>Mounting</b>	
<b>Style:</b>	Rack mount
<b>Size:</b>	50" W x 4.8" L x 1.16" H 126 mm x 120 mm x 29 mm
<b>Operating</b>	
<b>Temperature:</b>	-20°C to + 70°C
<b>Connectors:</b>	Optical: SMA or ST Data: 36-pin Centronics Power: External DC jack for OPTO-PS-2

### Ordering Information

Part Number	Description
OPTO-3800S	One pair: Terminal & printer modems, SMA optical port, Centronics female 36-pin connector
OPTO-3800ST	One pair: Terminal & printer modems, ST optical port, Centronics female 36-pin connector
OPTO-PS-2	Power Supply, AC/DC plug-in

### Applications

- Computer networking
- Remote peripherals
- High noise environment
- Factory/office automation

Power Budget/Distance		
Fiber Size	Power Budget	Distance
50/125	4 dB	1.0 km
62.5/125	8 dB	2.5 km
100/140	13 dB	2.5 km