


P0690ATF / P0690ATFS


N-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
900V	$2.35\Omega @ V_{GS} = 10V$	6A



TO-220F
TO-220FS



ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ }^{\circ}\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	900	V
Gate-Source Voltage		V_{GS}	± 30	
Continuous Drain Current ²	$T_C = 25\text{ }^{\circ}\text{C}$	I_D	6	A
	$T_C = 100\text{ }^{\circ}\text{C}$		3.5	
Pulsed Drain Current ¹		I_{DM}	18	
Avalanche Energy ³		E_{AS}	45	mJ
Power Dissipation	$T_C = 25\text{ }^{\circ}\text{C}$	P_D	52	W
	$T_C = 100\text{ }^{\circ}\text{C}$		20	
Operating Junction & Storage Temperature Range		T_J, T_{STG}	-55 to 150	$^{\circ}\text{C}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		2.4	$^{\circ}\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		62.5	

¹Pulse width limited by maximum junction temperature.

²Ensure that the channel temperature does not exceed 150°C .

³ $V_{DD} = 50V$, $L = 10\text{mH}$, starting $T_J = 25^{\circ}\text{C}$.

P0690ATF / P0690ATFS

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	900			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	2	3.4	4	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0V, V _{GS} = ±30V			±100	nA
Gate Voltage Drain Current	I _{DSS}	V _{DS} = 480V, V _{GS} = 0V, T _C = 25 °C			1	μA
		V _{DS} = 400V, V _{GS} = 0V , T _C = 100 °C			100	
Drain-Source On-State Resistance ¹	R _{DS(ON)}	V _{GS} = 10V, I _D = 3A		2	2.35	Ω
Forward Transconductance ¹	g _{fs}	V _{DS} = 10V, I _D = 3A		6		S
DYNAMIC						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 25V, f = 1MHz		1610		pF
Output Capacitance	C _{oss}			89		
Reverse Transfer Capacitance	C _{rss}			9		
Total Gate Charge ²	Q _g	V _{DD} = 720V, V _{GS} = 10V, I _D = 6A		34		nC
Gate-Source Charge ²	Q _{gs}			10.5		
Gate-Drain Charge ²	Q _{gd}			11		
Turn-On Delay Time ²	t _{d(on)}	V _{DD} = 450V, I _D = 6A, R _G = 6Ω		80		nS
Rise Time ²	t _r			190		
Turn-Off Delay Time ²	t _{d(off)}			120		
Fall Time ²	t _f			130		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T _J = 25 °C)						
Continuous Current ³	I _S				6	A
Forward Voltage ¹	V _{SD}	I _F = 6A, V _{GS} = 0V			1.4	V
Reverse Recovery Time	t _{rr}	I _F = 6A, dI _F /dt = 100A / μS		545		nS
Reverse Recovery Charge	Q _{rr}			3.6		μC

¹Pulse test : Pulse Width ≤ 380 μsec, Duty Cycle ≤ 2%.


²Independent of operating temperature.

³ Pulse width limited by maximum junction temperature.


P0690ATF / P0690ATFS

N-Channel Enhancement Mode MOSFET


Output Characteristics




Transfer Characteristics




On-Resistance VS Temperature




Capacitance Characteristic



Gate charge Characteristics




Source-Drain Diode Forward Voltage




P0690ATF / P0690ATFS

N-Channel Enhancement Mode MOSFET


Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve




P0690ATF / P0690ATFS

N-Channel Enhancement Mode MOSFET

Package Dimension

TO-220F (3-Lead) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	4.2		4.93	e	2.05	2.55	3.05
A1	2.34		3.1	F	27.45		30.6
B	17.77		20.3	G	7.72		9.3
b	0.6		1.05	H	6.1		7.1
b1	0.9	1.23	1.62	L	12.5		14.5
b2	0.6		1.9	L1	1.97		3.8
c	0.4		1.0	P	2.98		3.4
D	14.7		16.4	Q	2.1		2.96
D1	6.4		7.5	q	3.0		3.8
E	9.7		10.4				



P0690ATF / P0690ATFS

N-Channel Enhancement Mode MOSFET

Package Dimension

TO-220FS (3-Lead) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	4.2	4.7	4.93	e	2.05	2.54	3.05
A1	2.34	2.8	3.1	F	28.04		30.3
B	17.7		20.3	G	8.2	8.87	9.57
b	0.65	0.8	1.05	L	12.37		14.3
b1	0.9	1.3	1.5	L1	1.4	2.3	2.5
c	0.4	0.7	1.0	P	2.98	3.2	3.4
D	15.37		16.3	Q	2.1	2.6	2.96
D1	5.5		7.5	q	3.0	3.5	3.8
E	9.7	10.16	10.36				

