





PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
200V	0.42Ω	9A



- 1. GATE
- 2. DRAIN
- 3. SOURCE

ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ °C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	200	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current ²	$T_C = 25\text{ °C}$	I_D	9	A
	$T_C = 100\text{ °C}$		5	
Pulsed Drain Current ¹		I_{DM}	22	
Avalanche Current		I_{AS}	9	
Avalanche Energy	$L = 2.1\text{ mH}$	E_{AS}	85	mJ
Power Dissipation	$T_C = 25\text{ °C}$	P_D	28	W
	$T_C = 100\text{ °C}$		11	
Junction & Storage Temperature Range		T_J, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		4.4	°C / W

¹Pulse width limited by maximum junction temperature.

²Limited only by maximum temperature allowed.

ELECTRICAL CHARACTERISTICS ($T_J = 25\text{ °C}$, Unless Otherwise Noted)


PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	200			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2	2.6	4	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 200V, V_{GS} = 0V$			1	μA
		$V_{DS} = 160V, V_{GS} = 0V, T_J = 125\text{ °C}$			10	
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 4.5A$		0.3	0.42	Ω
Forward Transconductance ¹	g_{fs}	$V_{DS} = 10V, I_D = 4.5A$		19		S

DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 25V, f = 1MHz$		841		pF
Output Capacitance	C_{oss}			123		
Reverse Transfer Capacitance	C_{rss}			29		
Total Gate Charge ²	Q_g	$V_{DS} = 200V, V_{GS} = 10V,$ $I_D = 9A$		29		nC
Gate-Source Charge ²	Q_{gs}			4		
Gate-Drain Charge ²	Q_{gd}			13		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{DS} = 100V, I_D \cong 9A,$ $V_{GS} = 10V, R_{GEN} = 6\Omega$		11		nS
Rise Time ²	t_r			38		
Turn-Off Delay Time ²	$t_{d(off)}$			36		
Fall Time ²	t_f			45		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ($T_J = 25^\circ C$)						
Continuous Current	I_S				9	A
Forward Voltage ¹	V_{SD}	$I_F = 9A, V_{GS} = 0V$			1.6	V
Reverse Recovery Time	t_{rr}	$I_F = 9A, di_F/dt = 100A / \mu S$		151		nS
Reverse Recovery Charge	Q_{rr}			779		nC


¹Pulse test : Pulse Width $\leq 300 \mu sec$, Duty Cycle $\leq 2\%$.

²Independent of operating temperature.


Output Characteristics




Transfer Characteristics




On-Resistance VS Temperature




Capacitance Characteristic




Gate charge Characteristics




Source-Drain Diode Forward Voltage



Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve

