


Fully Sealed Container Cermet Potentiometer Professional Grade



FEATURES

- 1 W at 70 °C
- Cermet element
- Test according to CECC 41000 or IEC 60393-1
- Full sealing
- Mechanical strength
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

| QUICK REFERENCE DATA | |
|-------------------------|---|
| Multiple module | No |
| Switch module | n/a |
| Detent module | n/a |
| Special electrical laws | A: linear, L: logarithmic, F: reverse logarithmic |
| Sealing level | IP 67 |
| Lifespan | 25K cycles |

DIMENSIONS in millimeters ± 0.5 mm

P12T

Panel cutout
Panel thickness: 4 max.

P12Q

Panel cutout

Leads Y

Terminal spacing

Leads X

Terminal spacing

| ELECTRICAL SPECIFICATIONS | |
|--|---|
| Resistive element | Cermet |
| Electrical travel | 270° ± 10° |
| Resistance range | 22 Ω to 10 MΩ |
| | linear taper |
| | logarithmic taper |
| Standard series E3 | 1 - 2.2 - 4.7 and on request 1 - 2 - 5 |
| Tolerance | ± 20 % |
| | standard |
| | on request |
| Taper | |
| Circuit diagram | |
| Power rating | <p>linear 1 W at +70 °C logarithmic 0.5 W at +70 °C</p> |
| Temperature coefficient | See Standard Resistance Element Data |
| Limiting element voltage (linear taper) | 350 V |
| Contact resistance variation (typical) | 3 % or 3 Ω |
| End resistance (typical) | 1 Ω |
| Dielectric strength (RMS) | 2000 V |
| Insulation resistance (500 V _{DC}) | 10 ⁶ MΩ |

| MECHANICAL SPECIFICATIONS | |
|----------------------------------|-------------------------------|
| Mechanical travel | 300° ± 5° |
| Mechanical travel | 2 Ncm max. |
| End stop torque | bushing O bushings T and Q |
| | 15 Ncm max. 35 Ncm max. |
| Tightening torque | 150 Ncm max. |
| Unit weight | 7.6 g to 10 g max. |



| ENVIRONMENTAL SPECIFICATIONS | |
|------------------------------|-------------------------------|
| Operating temperature range | -55 °C to +125 °C |
| Climatic category | 55/100/56 |
| Sealing | Fully sealed - Container IP67 |

| PERFORMANCE | | | | |
|-------------------------|---|---------------------------|------------------------------|---|
| TESTS | CONDITIONS | TYPICAL VALUES AND DRIFTS | | |
| | | $\Delta R_T/R_T$ (%) | $\Delta R_{1-2}/R_{1-2}$ (%) | OTHER |
| Electrical endurance | 1000 h at rated power 90°/30° - ambient temp. 70 °C | ± 1 % | - | Contact res. variation: < 3 % Rn |
| Climatic sequence | Phase A dry heat 125 °C Phase B damp heat Phase C cold -55 °C Phase D damp heat 5 cycles | ± 0.5 % | ± 1 % | - |
| Damp heat, steady state | 56 days 40 °C 93 % RH | ± 0.5 % | ± 1 % | Dielectric strength: 1000 V _{RMS} Insulation resistance: > 10 ⁴ MΩ |
| Change of temperature | 5 cycles -55 °C at +125 °C | ± 0.5 % | - | - |
| Mechanical endurance | 25 000 cycles | ± 3 % | - | Contact res. variation: < 2 % Rn |
| Shock | 50 g's at 11 ms 3 successive shocks in 3 directions | ± 0.1 % | ± 0.2 % | - |
| Vibration | 10 Hz to 55 Hz 0.75 mm or 10 g's during 6 h | ± 0.1 % | - | $\Delta V_{1-2}/V_{1-3} \leq \pm 0.2 \%$ |

Note

- Nothing stated herein shall be construed as a guarantee of quality or durability

| STANDARD RESISTANCE ELEMENT DATA | | | | | | | |
|----------------------------------|---------------------|----------------------|--------------------|---------------------|----------------------|--------------------|----------------------------------|
| STANDARD RESISTANCE VALUES | LINEAR TAPER | | | LOGS TAPER | | | TYPICAL TCR -55 °C +125 °C |
| | MAX. POWER AT 70 °C | MAX. WORKING VOLTAGE | MAX. WIPER CURRENT | MAX. POWER AT 70 °C | MAX. WORKING VOLTAGE | MAX. WIPER CURRENT | |
| Ω | W | V | mA | W | V | mA | ppm/°C |
| 22 | 1 | 4.69 | 213.2 | | | | ± 150 |
| 47 | 1 | 6.85 | 145.8 | | | | |
| 100 | 1 | 10 | 100 | | | | |
| 220 | 1 | 14.8 | 67.4 | | | | |
| 470 | 1 | 21.6 | 46.1 | | | | |
| 1K | 1 | 31.6 | 31.6 | 0.5 | 22.4 | 22.4 | |
| 2.2K | 1 | 46.9 | 21.3 | 0.5 | 33.2 | 15.1 | |
| 4.7K | 1 | 63.5 | 14.5 | 0.5 | 48.5 | 10.3 | |
| 10K | 1 | 100 | 10 | 0.5 | 79.7 | 7.07 | |
| 22K | 1 | 148.3 | 6.7 | 0.5 | 105 | 4.77 | |
| 47K | 1 | 216.7 | 4.6 | 0.5 | 153 | 3.26 | |
| 100K | 1 | 316.2 | 3.16 | 0.5 | 224 | 2.24 | |
| 220K | 0.56 | 350 | 1.59 | 0.5 | 332 | 1.51 | |
| 470K | 0.26 | 350 | 0.75 | 0.26 | 350 | 0.74 | |
| 1M | 0.12 | 350 | 0.35 | 0.12 | 350 | 0.35 | |
| 2.2M | 0.05 | 350 | 0.16 | 0.05 | 350 | 0.16 | |
| 4.7M | 0.02 | 350 | 0.07 | | | | |
| 10M | 0.01 | 350 | 0.01 | | | | |

MARKING



- Vishay trademark
- Part number (including ohmic value and tolerance code)
- Manufacturing date
- Marking of terminals: 1 or a

PACKAGING

- For shafts AJ, EJ: In box of 15 pieces (code B1)
- For other shafts: In box of 25 pieces (code B2)

OPTIONS

SPECIAL FEATURES

| | |
|----------------------------------|--|
| Shafts | <p>Lengths are measured from the mounting surface to the free end of shaft. Shaft slot is aligned with the wiper within $\pm 10^\circ$. Special shafts are available, in accordance with drawings supplied by customers. We recommend customers not to machine shafts, in order to avoid damage. Bending or torsion of terminals should be avoided.</p> |
| Shaft and panel sealing hardware | <p>The type P12T with AB (old code M) or AJ (old code R) shaft can be provided with an optional “DE” sealing hardware which ensures sealing of both the shaft and the mounting panel. DE sealing hardware can be supplied in a separate bag.</p> <p>DE shaft and panel sealing hardware</p>  |
| Shaft locking | <p>The shaft locking bushing is available only with P12O potentiometers. Torque applied to locking nuts should not exceed 15 Ncm.</p> <p>P12OL with spindle locking nut</p>  <p>Tolerance unless otherwise specified ± 0.5</p> |



| ORDERING INFORMATION (part number) | | | | | | | | | | | | | | | | | |
|------------------------------------|---------|---|-----------|-------|----|--------------|-----------|-------------------|--|-------------------------------------|--|--|--|---|---|--|--|
| P | 1 | 2 | O | A | B | S | 4 | 7 | 2 | M | A | B | 2 | D | E | | |
| MODEL | BUSHING | | | SHAFT | | | LEADS | OHMIC VALUE | | TOLERANCE | TAPER | PACKAGING | SPECIAL | | | | |
| P12 | ∅ | L | Old codes | | ∅ | L | Old codes | S = STD X Y | Linear from 22 Ω to 10 MΩ | M = 20 % On request: K = 10 % | A = linear L = clockwise logarithmic F = inverse clockwise logarithmic | Shafts AJ and EJ: B1 = box of 15 pieces Other shafts: box of 25 pieces | DE = shaft and panel sealed hardware or special code given by Vishay | | | | |
| | T | 6 | 8 | T | AA | 3 | 9.5 | K | Logarithmic from 100 Ω to 2.2 MΩ | | | | | | | | |
| | Q | 7 | 8 | Q | AB | 3 | 12.5 | L, M | 472 = 4.7 kΩ | | | | | | | | |
| | O | 6 | 11 | H | AJ | 3 | 22 | R | | | | | | | | | |
| | | | | | EA | 4 | 9.5 | E | | | | | | | | | |
| | | | | | EB | 4 | 12.5 | F | | | | | | | | | |
| | | | | | EJ | 4 | 22 | G | | | | | | | | | |
| | | | | | AP | Custom shaft | | | | | | | | | | | |

| PART NUMBER DESCRIPTION (for information only) | | | | | | | | | | | | | | |
|--|---------|-------|---------|-------|-------|-----------|-------|---------|-----------|---------|-------|---------|-------------|----|
| P12 | H | | | L | 4K7 | 20 % | A | | BO | DE | | | | e3 |
| MODEL | BUSHING | LEADS | SPECIAL | SHAFT | VALUE | TOLERANCE | TAPER | SPECIAL | PACKAGING | SPECIAL | AP N° | SPECIAL | LEAD FINISH | |

| ACCESSORIES | |
|--|--|
| Additional Accessories (to order separately) | www.vishay.com/doc?51051 |

| RELATED DOCUMENTS | |
|---|--|
| APPLICATION NOTES | |
| Potentiometers and Trimmers | www.vishay.com/doc?51001 |
| Guidelines for Vishay Sfernice Resistive and Inductive Components | www.vishay.com/doc?52029 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.