


# P1604ED


## P-Channel Enhancement Mode MOSFET

### PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	$I_D$
-40V	16m $\Omega$ @ $V_{GS} = -10V$	-43A



TO-252



### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		$V_{DS}$	-40	V
Gate-Source Voltage		$V_{GS}$	$\pm 20$	
Continuous Drain Current	$T_C = 25\text{ }^\circ\text{C}$	$I_D$	-43	A
	$T_C = 100\text{ }^\circ\text{C}$		-34	
Pulsed Drain Current <sup>1</sup>		$I_{DM}$	-130	
Avalanche Current		$I_{AS}$	-40.8	
Avalanche Energy	$L = 0.1\text{mH}$	$E_{AS}$	83	mJ
Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	$P_D$	50	W
	$T_C = 100\text{ }^\circ\text{C}$		32	
Operating Junction & Storage Temperature Range		$T_J, T_{STG}$	-55 to 150	$^\circ\text{C}$

### THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		2.5	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		75	$^\circ\text{C} / \text{W}$

<sup>1</sup>Pulse width limited by maximum junction temperature.

# P1604ED

## P-Channel Enhancement Mode MOSFET

### ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
<b>STATIC</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA	-40			V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250μA	-1.5	-2.2	-3.0	
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±20V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = -32V, V <sub>GS</sub> = 0V			1	μA
		V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0V, T <sub>J</sub> = 125 °C			10	
On-State Drain Current <sup>1</sup>	I <sub>D(ON)</sub>	V <sub>DS</sub> = -5V, V <sub>GS</sub> = -10V	-130			A
Drain-Source On-State Resistance <sup>1</sup>	R <sub>DS(ON)</sub>	V <sub>GS</sub> = -7V, I <sub>D</sub> = -15A		16	20	mΩ
		V <sub>GS</sub> = -10V, I <sub>D</sub> = -25A		13	16	
Forward Transconductance <sup>1</sup>	g <sub>fs</sub>	V <sub>DS</sub> = -5V, I <sub>D</sub> = -25A		24		S
<b>DYNAMIC</b>						
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = -15V, f = 1MHz		2350		pF
Output Capacitance	C <sub>oss</sub>			480		
Reverse Transfer Capacitance	C <sub>rss</sub>			310		
Gate Resistance	R <sub>g</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 0V, f = 1MHz		4.3		Ω
Total Gate Charge <sup>2</sup>	Q <sub>g</sub>	V <sub>DS</sub> = 0.5V <sub>(BR)DSS</sub> , V <sub>GS</sub> = -10V, I <sub>D</sub> = -25A		42		nC
Gate-Source Charge <sup>2</sup>	Q <sub>gs</sub>			9		
Gate-Drain Charge <sup>2</sup>	Q <sub>gd</sub>			10		
Turn-On Delay Time <sup>2</sup>	t <sub>d(on)</sub>	V <sub>DS</sub> = -20V, I <sub>D</sub> ≅ -1A, V <sub>GS</sub> = -10V, R <sub>GS</sub> = 6Ω		15		nS
Rise Time <sup>2</sup>	t <sub>r</sub>			43		
Turn-Off Delay Time <sup>2</sup>	t <sub>d(off)</sub>			62		
Fall Time <sup>2</sup>	t <sub>f</sub>			50		
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T<sub>J</sub> = 25 °C)</b>						
Continuous Current	I <sub>S</sub>				-43	A
Forward Voltage <sup>1</sup>	V <sub>SD</sub>	I <sub>F</sub> = -25A, V <sub>GS</sub> = 0V			-1.3	V
Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = -20A, dI <sub>F</sub> /dt = 100A / μS		43		nS
Reverse Recovery Charge	Q <sub>rr</sub>			31		nC







<sup>1</sup>Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

<sup>2</sup>Independent of operating temperature.

# P1604ED


## P-Channel Enhancement Mode MOSFET

### TYPICAL PERFORMANCE CHARACTERISTICS



# P1604ED

## P-Channel Enhancement Mode MOSFET



# P1604ED

## P-Channel Enhancement Mode MOSFET

### Package Dimension

### TO-252 (DPAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	8.9	10	10.41	J	4.8		5.64
B	2.1	2.2	2.5	K	0.15		1.49
C	0.4	0.5	0.61	L	0.4	0.76	0.91
D	0.82	1.2	1.5	M	4.2	4.58	5
E	0.35	0.5	0.65	S	4.57	5.1	5.52
F	0		0.2	T	3.81	4.75	5.24
G	5.3	6.1	6.3	U	1.4		1.78
H	0.5		1.7	V	0.55	1.25	1.7
I	6.3	6.5	6.8				

