



PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
25	12m Ω	55A



1. GATE
2. DRAIN
3. SOURCE

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T _C = 25 °C	I_D	55	A
	T _C = 100 °C		38	
Pulsed Drain Current ¹		I_{DM}	150	
Avalanche Current		I_{AR}	36	
Avalanche Energy	L = 0.1mH	E_{AS}	250	mJ
Repetitive Avalanche Energy ²	L = 0.05mH	E_{AR}	8.6	
Power Dissipation	T _C = 25 °C	P_D	85	W
	T _C = 100 °C		46	
Operating Junction & Storage Temperature Range		T _j , T _{stg}	-55 to 150	°C
Lead Temperature (¹ / ₁₆ " from case for 10 sec.)		T _L	275	

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	R _{θJC}		2.3	°C / W
Junction-to-Ambient	R _{θJA}		62.5	
Case-to-Heatsink	R _{θCS}	0.6		

¹Pulse width limited by maximum junction temperature.

²Duty cycle ≤ 1%

ELECTRICAL CHARACTERISTICS (T_C = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	25			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	0.8	1.2	2.5	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			±250	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 20V, V_{GS} = 0V$			25	μA
		$V_{DS} = 20V, V_{GS} = 0V, T_C = 125\text{ °C}$			250	

On-State Drain Current ¹	$I_{D(ON)}$	$V_{DS} = 10V, V_{GS} = 10V$	55			A
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 7V, I_D = 20A$		13	16	mΩ
		$V_{GS} = 10V, I_D = 30A$		12	15	
Forward Transconductance ¹	g_{fs}	$V_{DS} = 15V, I_D = 40A$		16		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 15V, f = 1MHz$		1400		pF
Output Capacitance	C_{oss}			380		
Reverse Transfer Capacitance	C_{rss}			200		
Total Gate Charge ²	Q_g	$V_{DS} = 0.5V_{(BR)DSS}, V_{GS} = 10V, I_D = 30A$		40		nC
Gate-Source Charge ²	Q_{gs}			12		
Gate-Drain Charge ²	Q_{gd}			25		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{DS} = 15V, R_L = 1\Omega$ $I_D \cong 35A, V_{GS} = 10V, R_{GS} = 2.5\Omega$		9		nS
Rise Time ²	t_r			150		
Turn-Off Delay Time ²	$t_{d(off)}$			20		
Fall Time ²	t_f			30		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_c = 25 °C)						
Continuous Current	I_S				55	A
Pulsed Current ³	I_{SM}				170	
Forward Voltage ¹	V_{SD}	$I_F = I_S, V_{GS} = 0V$			1.3	V
Reverse Recovery Time	t_{rr}	$I_F = I_S, di_F/dt = 100A / \mu S$		70		nS
Peak Reverse Recovery Current	$I_{RM(REC)}$			200		A
Reverse Recovery Charge	Q_{rr}			0.043		μC

¹Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.

REMARK: THE PRODUCT MARKED WITH "P50N02LS", DATE CODE or LOT #

TO-263 (D²PAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	14.5	15	15.8	H	1.0	1.5	1.8
B	4.2		4.7	I	9.8		10.3
C	1.20		1.35	J		6.5	
D		2.8		K		1.5	
E	0.3	0.4	0.5	L	0.7		1.4
F	-0.102		0.203	M	4.83	5.08	5.33
G	8.5	9	9.5	N			

