



P5102FM

P-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
-20V	45mΩ @ $V_{GS} = -4.5V$	-3.5A



ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ °C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±8	
Continuous Drain Current	$T_A = 25\text{ °C}$	I_D	-3.5	A
	$T_A = 70\text{ °C}$		-2.8	
Pulsed Drain Current ¹		I_{DM}	-21	
Power Dissipation	$T_A = 25\text{ °C}$	P_D	1.0	W
	$T_A = 70\text{ °C}$		0.6	
Operating Junction & Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient	$R_{\theta JA}$		120	°C / W
Junction-to-Case	$R_{\theta JC}$		60	

¹Limited by maximum junction temperature.

P5102FM

P-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)


PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-20			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-0.45	-0.6	-0.9	V
Gate-Body Leakage	I _{GSS}	V _{DS} = 0V, V _{GS} = ±8V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -16V, V _{GS} = 0V			-1	μA
		V _{DS} = -10V, V _{GS} = 0V, T _J = 70 °C			-10	
Drain-Source On-State Resistance ¹	R _{DS(ON)}	V _{GS} = -1.8V, I _D = -2A		60	71	mΩ
		V _{GS} = -2.5V, I _D = -3.5A		48	55	
		V _{GS} = -4.5V, I _D = -3.5A		40	45	
On-State Drain Current ¹	I _{D(ON)}	V _{DS} = -5V, V _{GS} = -4.5V	-21			A
Forward Transconductance ¹	g _{fs}	V _{DS} = -5V, I _D = -3.5A		17		S
DYNAMIC						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = -10V, f = 1MHz		1180		pF
Output Capacitance	C _{oss}			185		
Reverse Transfer Capacitance	C _{rss}			117		
Total Gate Charge ²	Q _g	V _{DS} = -10V, V _{GS} = -4.5V, I _D = -3.5A		16.7		nC
Gate-Source Charge ²	Q _{gs}			1.8		
Gate-Drain Charge ²	Q _{gd}			4.6		
Turn-On Delay Time ²	t _{d(on)}	V _{DS} = -10V I _D ≅ -3.5A, V _{GS} = -4.5V, R _{GEN} = 3.3Ω		20		nS
Rise Time ²	t _r			36		
Turn-Off Delay Time ²	t _{d(off)}			45		
Fall Time ²	t _f			62		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTIC (T_J = 25 °C)						
Continuous Current	I _S				-3.5	A
Forward Voltage ¹	V _{SD}	I _F = -3.5A, V _{GS} = 0V			-1.3	V
Reverse Recovery Time	t _{rr}	I _F = -3.5A, dI _F /dt = 100A / μS		30		nS
Reverse Recovery Charge	Q _{rr}				14	

¹Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

²Independent of operating temperature.


P5102FM

P-Channel Enhancement Mode MOSFET



P5102FM

P-Channel Enhancement Mode MOSFET



P5102FM

P-Channel Enhancement Mode MOSFET

Package Dimension

SOT-23 MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A		1.05		H	0.1		0.2
B	2.4		3	I	0.3		0.6
C	1.4		1.73				
D	2.7		3.1				
E	1		1.31				
F	0		0.15				
G	0.3		0.5				

