




N-Channel 60-V (D-S), 175°C MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ (Ω)	I_D (A)
60	0.014	70 ^a

TO-220AB




Top View

SUP70N06-14


DRAIN connected to TAB

TO-263



Top View

SUB70N06-14



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter		Symbol	Limit	Unit
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current ($T_J = 175^\circ\text{C}$)	$T_C = 25^\circ\text{C}$	I_D	70 ^a	A
	$T_C = 100^\circ\text{C}$		49	
Pulsed Drain Current		I_{DM}	160	
Avalanche Current		I_{AR}	70	
Repetitive Avalanche Energy ^b		E_{AR}	180	mJ
Power Dissipation	$T_C = 25^\circ\text{C}$ (TO-220AB and TO-263)	P_D	142 ^c	W
	$T_A = 25^\circ\text{C}$ (TO-263) ^d		3.7	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

Parameter		Symbol	Limit	Unit
Junction-to-Ambient	PCB Mount (TO-263) ^d	R_{thJA}	40	$^\circ\text{C/W}$
	Free Air (TO-220AB)		62.5	
Junction-to-Case		R_{thJC}	1.05	

Notes:







- Package limited.
- Duty cycle $\leq 1\%$.
- See SOA curve for voltage derating.
- When mounted on 1" square PCB (FR-4 material).

For SPICE model information via the Worldwide Web: <http://www.vishay.com/www/product/spice.htm>

SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 250 μA	60			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _{DS} = 1 mA	2.0	3.0	4.0	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 60 V, V _{GS} = 0 V			1	μA
		V _{DS} = 60 V, V _{GS} = 0 V, T _J = 125 °C			50	
		V _{DS} = 60 V, V _{GS} = 0 V, T _J = 175 °C			150	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	70			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 30 A			0.014	Ω
		V _{GS} = 10 V, I _D = 30 A, T _J = 125 °C			0.023	
		V _{GS} = 10 V, I _D = 30 A, T _J = 175 °C			0.028	
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 30 A	25	50		S
Dynamic ^b						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, f = 1 MHz		2400		pF
Output Capacitance	C _{oss}			490		
Reverse Transfer Capacitance	C _{rss}			130		
Total Gate Charge ^c	Q _g	V _{DS} = 30 V, V _{GS} = 10 V, I _D = 60 A		45	70	nC
Gate-Source Charge ^c	Q _{gs}			12		
Gate-Drain Charge ^c	Q _{gd}			16		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 30 V, R _L = 0.47 Ω I _D = 60 A, V _{GEN} = 10 V, R _G = 2.5 Ω		13	30	ns
Rise Time ^c	t _r			11	30	
Turn-Off Delay Time ^c	t _{d(off)}			30	60	
Fall Time ^c	t _f			11	25	
Source-Drain Diode Ratings and Characteristics (T _C = 25 °C) ^b						
Continuous Current	I _S				70	A
Pulsed Current	I _{SM}				160	
Forward Voltage ^a	V _{SD}	I _F = 70 A, V _{GS} = 0 V			1.4	V
Reverse Recovery Time	t _{rr}	I _F = 60 A, di/dt = 100 A/μs		47		ns
Peak Reverse Recovery Current	I _{RM(REC)}			3.5		A
Reverse Recovery Charge	Q _{rr}			0.08		μC



Notes:

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.
c. Independent of operating temperature.




**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)****Output Characteristics****Transfer Characteristics****Transconductance****On-Resistance vs. Drain Current****Capacitance****Gate Charge**



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



THERMAL RATINGS



This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.