

Version : 7.0

TECHNICAL SPECIFICATION

MODEL NO : PA035XSE

The content of this information is subject to be changed without notice.

Please contact PVI or its agent for further information.

☐ Customer's Confirmation

Customer _____

Date _____

By _____

☐ PVI's Confirmation

Confirmed By



Prepared By



Revision History

Rev.	Issued Date	Revised Contents
0.1	Feb.3,2004	NEW
1.0	Mar.2,2004	Update Page:24 12. Reliability test Vibration Test& ShockTest ok
1.1	Oct.6,2004	Update Page9:Note 8-5 B/L Lamp voltage kick-off time
1.2	Oc.21,2004	Modify Page 10: 8-5) Timing Characteristics Of Input Signals Page 13: Fig.8-2 Horizontal Start Pixel
1.3	Jan.20,2005	Update: Page 20: Lamp current about 5mA brightness & lamp life time.
1.4	Nov.21.2005	Modify Page 9 : 8-3) Backlight driving Starting voltage (25℃) Vs(max)=400Vrms chang Vs(max)=440Vrms Starting voltage (0℃) Vs(max)=520Vrms chang Vs(max)=530Vrms
1.5	Mar,09,2006	Modify Page 26/27 : Packing
7.0	Nov,08,2007	Modify Page 27: 14.Delete carton and change Packing

TECHNICAL SPECIFICATION***CONTENTS***

<i>NO.</i>	<i>ITEM</i>	<i>PAGE</i>
-	Cover	1
-	Revision History	2
-	Contents	3
1	Application	4
2	Features	4
3	Mechanical Specifications	4
4	Mechanical Drawing of TFT-LCD module	5
5	Input / Output Terminals	6
6	Pixel Arrangement	8
7	Absolute Maximum Ratings	9
8	Electrical Characteristics	9
9	Power On Sequence	20
10	Optical Characteristics	20
11	Handling Cautions	24
12	Reliability Test	25
13	Block Diagram	26
14	Packing	27

1. Application

This technical specification applies to 3.5" color TFT-LCD module , PA035XSE

The applications of the panel are car TV, portable DVD, GPS, multimedia applications and others AV system..


2. Features

- . Compatible with NTSC & PAL system
- . Pixel in delta configuration
- . Slim and compact
- . Image Reversion : Up/Down and Left/Right
- . Optimum Viewing Direction : 6 o'clock

3. Mechanical Specifications

Parameter	Specifications	Unit
Screen Size	3.5(diagonal)	inch
Display Format	320× (R,G,B) ×234	dot
Active Area	71.6(H) × 52.65(V)	mm
Pixel Pitch	0.2237(H) × 0.225(V)	mm
Pixel Configuration	Delta	
Black-light	CCFL,1 tube	
Outline Dimension	83.7(W) × 68.6(H) × 6.6(D)(typ.)	mm
Surface Treatment	Anti – Glare	
Weight	58±5	g
Gray scale inversion direction	6 o'clock [Note 10-1]	

4. Mechanical Drawing of TFT-LCD Module



5. Input / Output Terminals

TFT-LCD Module Connector

FPC Down Connect , 28Pins , Pitch : 0.5 mm

Pin No	Symbol	I/O	Description	Remark
1	STH1	I/O	Start pulse for source driver	Note 5 – 5
2	AV _{SS}	I	Analog GND for source driver	
3	AV _{DD}	I	Analog power input for source driver	Note 5 – 3
4	V _B	I	Video Input B	Note 5 – 1
5	V _G	I	Video Input G	
6	V _R	I	Video Input R	
7	V _{SS}	I	Digital GND	
8	V _{DD}	I	Digital power input	Note 5 – 3
9	CPH1	I	Sampling and shift clock for source driver	Note 5 – 6
10	CPH2	I	Sampling and shift clock for source driver	
11	CPH3	I	Sampling and shift clock for source driver	
12	STH2	I/O	Start pulse for source driver	Note 5 – 5
13	Q2H	I	Video input rotation control	
14	INH	I	Output enable for source driver	
15	R/L	I	Left/Right Control for source driver	Note 5 – 5
16	V _{COM}	I	Common electrode voltage	Note 5 – 1
17	V _{COM}	I	Common electrode voltage	
18	XOE	I	Output enable for gate driver	
19	CPV	I	Clock input for gate driver	
20	U/D	I	Up/Down Control for gate driver	Note 5 – 5
21	DIO2	I/O	Vertical start pulse	
22	DIO1	I/O	Vertical start pulse	
23	V _{GL}	I	Gate off voltage(alternative every 1-H)	Note 5 – 1
24	V _{EE}	I	Gate driver negative voltage	Note 5 – 2
25	V _{SS}	I	GND	
26	V _{CC}	I	Logic power for gate driver	Note 5 – 3
27	V _{GH}	I	Gate on voltage	Note 5 – 4
28	GND	-	B/L case GND	

Note 5 – 1 : $V_{COM(TYP.)} = 6.0V_{PP}$.

Phase of the video signal input and V_{COM}

The relation between these values could refer to 8-1 Operating condition.




Fig.1

Liquid crystal transmission of the video signal input, V_{COM} and timing

	V_{COM}	
	H Level	L Level
Video Signal Input Maximum	Black	White
Video Signal Input Minimum	White	Black

White : maximum transmission / Black : minimum transmission

Note 5 – 2 : $V_{EE(TYP.)} = -15V$

Note 5 – 3 : $V_{DD}, V_{CC(TYP.)} = +3.3V$, $AV_{DD(TYP.)} = +5.0V$

Note 5 – 4 : $V_{GH(TYP.)} = +17V$


Note 5 – 5 : STH1, STH2 and R/L mode

R/L	STH1	STH2	Remark
High(V_{DD})	Input	Output	Left to Right
Low(0 Volt.)	Output	Input	Right to Left


DIO1,DIO2,and U/D mode

U/D	DIO1	DIO2	Remark
High(V_{CC})	Input	Output	Down to Up
Low(0 Volt.)	Output	Input	Up to Down

U/D(PIN 20)=Low R/L(PIN 15)=High




U/D(PIN 20)=High R/L(PIN 15)=Low



Note 5 – 6: The CPH1 reference Fig.8-1 Sampling clock timing

CPH2 and CPH3 connect GND.

6. Pixel Arrangement



7. Absolute Maximum Ratings :

The followings are maximum values , which if exceeded, may cause faulty operation or damage to the unit.

$$\text{GND} = 0\text{V} , \text{Ta} = 25^{\circ}\text{C}$$

Parameter		Symbol	MIN.	MAX.	Unit	Remark
Supply Voltage For Source Driver		AV_{DD}	-0.3	+7.0	V	
		V_{DD}	-0.3	+7.0	V	
Supply Voltage For Gate Driver	H Level	V_{GH}	-0.3	+45	V	
	L Level	V_{GL}	-23	+0.3	V	
		$V_{GH}-V_{GL}$	+15	+40	V	


8. Electrical Characteristics

8-1) Operating Condition

Parameter		Symbol	MIN.	Typ.	MAX.	Unit	Remark
Supply Voltage For Source Driver	Analog	V_{DD}	+4.5	+5.0	+5.5	V	
	Logic	V_{DD}	+3.0	+3.3	+3.6	V	Depend on T/C signal voltage
			+4.5	+5.0	+5.5	V	
Supply Voltage For Gate Driver	V_{GH}		+15.0	+17.0	+19.0	V	
	V_{EE}		-15.5	-15.0	-14.5	V	
	$V_{GL\ DC}$		-12.5	-11.0	-9.5	V	DC Component of V_{GL}
	$V_{GL\ AC}$		-	+6.0	-	V_{P-P}	AC Component of V_{GL}
	Logic	V_{CC}	+3.0	+3.3	+3.6	V	Depend on T/C signal voltage
			+4.5	+5.0	+5.5	V	
Analog Signal input Level (VR , VG , VB)	V_{IAC}		-	+3.6	+4.0	V	Note 8-2
	V_{IDC}		-	+2.5	-	V	
Digital input voltage	H level	V_{IH}	+0.7 V_{DD}	-	-	V	
	L level	V_{IL}	-	-	+0.3 V_{DD}	V	
V_{COM}		$V_{COM\ AC}$	-	+6.0	-	V_{P-P}	AC Component of V_{COM}
		$V_{COM\ DC}$	-	+0.96	-	V	DC Component of V_{COM} Note 8-1

Note 8-1 : PVI strongly suggests that the $V_{COM\ DC}$ level shall be adjustable ,and the adjustable level range is $0.96V \pm 1V$, every module's $V_{COM\ DC}$ level shall be carefully adjusted to show a best image performance.

Note 8-2: Both NTSC and PAL system Video Signal input waveform is based on 8 steps gray scale.



8-2) Current Consumption (GND=0V)

Ta= 25 °C

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Current for Driver	I _{GH}	V _{GH} =+17V	-	0.055	0.083	mA	
	I _{GL}	V _{GL} =-12V	-	0.067	0.087	mA	V _{GL} center voltage
	I _{CC}	V _{CC} =+3.3V	-	0.441	0.563	mA	
	AI _{DD}	V _{DD} =+3.3V	-	1.2	3	mA	
	I _{EE}	V _{EE} =-15V	-	0.441	0.6	mA	
	I _{DD}	AV _{DD} =+5V	-	7	10	mA	

8-3) Backlight driving & Power Consumption

Pin No	Symbol	Description	Remark
1	VL1	Input terminal (Hi voltage side)	
2	VL3	Input terminal (Low voltage side)	Note 8-3

Note 8-3 : Low voltage side of backlight inverter connects with Ground of inverter circuits.

Ta= 25 °C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
Lamp voltage	V _L	-	265	-	Vrms	
Lamp current	I _L	2	3	5	mA	Note 8-4
Lamp frequency	P _L	25	35	65	KHz	Note 8-5
Starting voltage (25°C) (Reference Voltage)	V _s	-	-	440	Vrms	Note 8-6
Starting voltage (0°C) (Reference Voltage)	V _s	-	-	530	Vrms	Note 8-6

Note 8-4 : In order to satisfy the quality of B/L, no matter use what kind of inverter, the output lamp current must be between Min. and Max. to avoid the abnormal display image caused by B/L.

Note 8-5: The waveform of lamp driving voltage should be as closed to a perfect SIN wave as possible.

Note 8-6 : The "Max of starting voltage" means the minimum voltage of inverter to turn on the CCFL. And it should be applied to the lamp for more than 1 second to start up. Otherwise the lamp may not be turned on.

Power Consumption

Ta= 25 °C

Parameter	Symbol	Conditions	TYP.	Unit	Remark
LCD Panel Power Consumption			50	mW	
Backlight Lamp Power Consumption			0.65	W	Note 8-7
Total Power Consumption			0.69	W	

Note 8-7 : Backlight lamp power consumption is calculated by $I_L \times V_L$.

8-4) Input / Output Connector

6. Backlight Connector
JST BHR-03VS-1,
Pin No. : 3 ,
Pitch : 4 mm

8-5) Timing Characteristics Of Input Signals

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Remark
1Field Scanning Period	t1V	-	262.5	-	H	
1Line Scanning Period	t1H	-	63.5	-	μs	
Source Driver Operating Frequency	fhc	4	6.4	8	MHz	
Signal Sampling Pulse Width	tchw	125	156.25	250	ns	
Signal Sampling Pulse Delay	tchd	47.65	52	58.25	ns	tchd 12,23
Signal Sampling Pulse Width(H)	tchwh	71.45	78.12	87.35	ns	
Signal Sampling Pulse Delay(L)	tchwl	71.45	78.12	87.35	ns	
Source Start Signal Pulse Width	tshw	45	156.25	315	ns	*tshset=tshhld
Source Start Signal Setup Time	tshset	20	78.12	-	ns	
Source Start Signal Hold Time	tshhld	20	78.12	-	ns	
Source Output Enable Pulse Width	tohw	1.0	2.0	-	μs	
Source Start Signal Rising Time	tss	-	9.8	-	μs	
Video Input Signal Start Point	tvsv	-	10.0	-	μs	
Phase Difference Between XOE&CPV	toc	1.5	2.3	-	μs	
Gate Clock Period	tevw	10	63.5	-	μs	
Gate Clock Pulse Width(H)	tecvwh	10	31.7	48	μs	
Gate Clock Pulse Width(L)	tecvwl	10	31.7	48	μs	
Gate Start Signal Pulse Width	tsvw	5	63.5	126**	μs	**tsvset=tsvhld
Gate Start Signal Setup Time	tsvset	5	53.2	-	μs	
Gate Start Signal Hold Time	tsvhld	5	10.3	-	μs	
Phase Difference Between INH&STH	tosp	-	4	-	μs	
Phase Difference Between SYNC&INH	tohs	-	1.4	-	μs	
Gate Output Enable Pulse Width	toev	-	2.5	-	μs	
V _{COM} Delay Time	t _{DCOM}	-	-	3	μs	
RGB Delay Time	t _{DRGB}	-	-	2	μs	
Vertical Display Start	tsv	-	3	-	tH	

8 – 6) Signal Timing Waveforms





Fig. 8-1 Vertical Start Line for NTSC



** odd field : Scan lines 14n+6 14n+12 (n = 2, 3, 4..) are not displayed.
even field : Scan lines 14n+12 14n+20 (n = 2, 3, 4..) are not displayed.

Fig. 8-1 Vertical Start Line for PAL




Fig. 8-2 Horizontal Start Pixel




Fig. 8-3 Detail Horizontal Timing




Fig. 8-4 Sampling Clock Timing




Fig. 8-5 Vertical Shift Clock Timing

Vertical timing (From up to down)




Fig. 8-6(a) Vertical Timing (From Up to Down)

Vertical timing (From down to up)





Fig. 8-6(b) Vertical Timing (From Down to Up)

9. Power On Sequence

The Power on Sequence only effect by V_{CC} , V_{SS} , V_{DD} , V_{EE} and V_{GH} , the others do not care.



- 1) $10\text{ms} \leq T1 < T2$
- 2) $0\text{ms} < T3 \leq T4 \leq 10\text{ms}$


10. Optical Characteristics

10-1) Specification:

$T_a = 25^\circ\text{C}$

Parameter		Symbol	Condition	MIN.	TYP.	MAX.	Unit	Remarks
Viewing Angle	Horizontal	θ_{21}, θ_{22}	$CR \geq 10$	± 45	± 50	-	deg	Note 10-1
	Vertical	θ_{12}		10	15	-	deg	
		θ_{11}		30	35	-	deg	
Contrast Ratio		CR	At optimized Viewing angle	200	350	-		Note 10-2
Response time	Rise	Tr	$\theta = 0^{\circ}$	-	15	30	ms	Note 10-4
	Fall	Tf		-	25	50	ms	
Uniformity		U		65	70	-	%	Note 10-6
Brightness		L	3mA	200	250	-	cd/m ²	Note 10-3
			5mA	300	350	-		
White Chromaticity		x	$\theta = 0^{\circ}$	0.280	0.310	0.340		
		y	$\theta = 0^{\circ}$	0.310	0.340	0.370		
Lamp Life Time			+25 ^o C	-	30000	-	hrs	Note 10-5


Note 10-1 : The definitions of viewing angles



Note 10-2 : $CR = \frac{\text{Luminance when Testing point is White}}{\text{Luminance when Testing point is Black}}$
 (Testing configuration see 10-2)
 Contrast Ratio is measured in optimum common electrode voltage.

Note 10-3 : 1. Topcon BM-7(fast) luminance meter 1° field of view is used in the testing (after 20~30 minutes operation).
 2. Lamp Current 3mA & 5mA
 3. Inverter model : TDK-347.

Note 10-4 : The definition of response time :



Note 10-5: Lamp life time 3mA about 30000hrs ; 5mA about 20000hrs

Note 10-6: The uniformity of LCD is defined as

$$U = \frac{\text{The Minimum Brightness of the 9 testing Points}}{\text{The Maximum Brightness of the 9 testing Points}}$$


Luminance meter : BM-5A or BM-7 fast(TOPCON)

Measurement distance : 500 mm +/- 50 mm



Ambient illumination : < 1 Lux

Measuring direction : Perpendicular to the surface of module


The test pattern is white (Gray Level 63).



10-2) Testing configuration




Pattern A




Pattern B

- R, G, B Waveform of Pattern A at Testing Point



- R, G, B Waveform of Pattern B at Testing Point



11. Handling Cautions

11-1) Mounting of module

- a) Please power off the module when you connect the input/output connector.
- b) Please connect the ground pattern of the inverter circuit surely. If the connection is not perfect, some following problems may happen possibly.
 - 1.The noise from the backlight unit will increase.
 - 2.The output from inverter circuit will be unstable.
 - 3.In some cases a part of module will heat.
- 6. Polarizer which is made of soft material and susceptible to flaw must be handled carefully.
- 6. Protective film (Laminator) is applied on surface to protect it against scratches and dirt. It is recommended to peel off the laminator before use and taking care of static electricity.

11-2) Precautions in mounting

- a) When metal part of the TFT-LCD module (shielding lid and rear case) is soiled, wipe it with soft dry cloth.
- b) Wipe off water drops or finger grease immediately. Long contact with water may cause discoloration or spots.
- c) TFT-LCD module uses glass which breaks or cracks easily if dropped or bumped on hard surface. Please handle with care.
- d) Since CMOS LSI is used in the module. So take care of static electricity and earth yourself when handling.

11-3) Adjusting module

- a) Adjusting volumes on the rear face of the module have been set optimally before shipment.
- b) Therefore, do not change any adjusted values. If adjusted values are changed, the specifications described may not be satisfied.

11-4) Others

- a) Do not expose the module to direct sunlight or intensive ultraviolet rays for many hours.
- b) Store the module at a room temperature place.
- c) The voltage of beginning electric discharge may over the normal voltage because of leakage current from approach conductor by to draw lump read lead line around.
- d) If LCD panel breaks, it is possibly that the liquid crystal escapes from the panel. Avoid putting it into eyes or mouth. When liquid crystal sticks on hands, clothes or feet. Wash it out immediately with soap.
- e) Observe all other precautionary requirements in handling general electronic components.
- f) Please adjust the voltage of common electrode as material of attachment by 1 module.

12. Reliability Test


No	Test Item	Test Condition
1	High Temperature Storage Test	Ta = +70°C, 240 hrs
2	Low Temperature Storage Test	Ta = -20°C, 240 hrs
3	High Temperature Operation Test	Ta = +60°C, 240 hrs
4	Low Temperature Operation Test	Ta = 0°C, 240 hrs
5	High Temperature & High Humidity Operation Test	Ta = +60°C, 90%RH, 240 hrs
6	Thermal Cycling Test (non-operating)	-25°C → +70°C, 200 Cycles 30 min 30 min
7	Vibration Test (non-operating)	Frequency : 10 ~ 55 Hz Amplitude : 1.5 mm Sweep time: 11 mins Test Period : 6 Cycles for each direction of X, Y, Z
8	Shock Test (non-operating)	100G, 6ms Direction : ±X, ±Y, ±Z Cycle : 3 times
9	Electrostatic Discharge Test (non-operating)	200pF, 0 Ω ±200V 1 time / each terminal

Ta: ambient temperature

[Criteria]


In the standard conditions, there is not display function NG issue occurred. (Including: line defect , no image). All the cosmetic specification is judged before the reliability stress.

13. Block Diagram



14. Packing

REV	DESCRIPTION	DESIGN	DATE
01	INITIAL RELEASE	Jimm yc	'05.12.06
02	CANCEL THE CARTON(50-0100101)	Jimm yc	'07.11.05



NOTE:
1. One layer include: 1 piece of cushion sheet, 12 pcs panel & 1 piece of tray.
2. Q'TY: 108 pcs panel/carton.
3. Dimension: 455*375*190mm
4. Weight: 8.5 KG
5. tray 需180°交叉堆疊，疊堆後可從側邊檢視圓弧防呆方向是否正確

6	50-0100091	CARTON INTERNAL	1	
5	50-0500041	摺口袋450*380*700mm	1	抗靜電
4		PA035XS Panel	108	
3	50-0200035	EPE CUSHION SHEET	9	抗靜電
2	50-0300882	PS TRAY	10	抗靜電
1	50-0300491	EPE FOAM	2	

MTL.SPEC.		UNSPECIFIED TOL'S		REMARK			
		ANGLE					
		ROUGHNESS					
APPROVE	Frank Shin	SCALE	UNIT	SHEET	DWG.TITLE PA035XSE PACKING DRAW		
CHECK	Frank Shin	1:1	mm	1 OF 1			
DESIGN	Jimm yc	MTL.NO.					
					DWG.NO.	REV. 02	SIZE A4

元太科技股份有限公司
Prime View International Co.,ltd.