

PA239 L

**Screw and push wire
Terminal Block (12 poles)**



TECHNICAL DATA

	IEC Standards	American Standards
Ratings	450V - 24A	300V - 15A
Wire size	2.5 sqmm / 2x0.5 sqmm + 2x1.5 sqmm	18 ÷ 14AWG
Working Temperature	- 5 ÷ 110°C (short time 140°C)	23 ÷ 221°F
Plastic Material	Polyamide PA6.6 natural colour, UL94 V2, GWT 960°C	
Metal Parts	Cage insert made in nickel plated brass; M3 Captive screw made in zinc plated steel; Spring made in stainless steel	
Accessories	LT PA239, PA228 (2 and 3 poles)	

Approvals	File Nr.	Ratings (sqmm/AWG – V – A – T)	Standard References
	CA02.01195	2.5 / 2x0.5+1.5 sqmm - 450V – 110°C	EN 60998-1; EN 60998-2-1; EN 60998-2-2
	CA02.01195	2.5 / 2x0.5+1.5 sqmm - 450V – 110°C	EN 60998-1; EN 60998-2-1; EN 60998-2-2
	123057	2.5 / 2x0.5+1.5 sqmm - 450V - 24A / / 17.5A (1.5 sqmm) - – 110°C	DIN EN 60998-1; DIN EN 60998-2-1 (VDE 0613)
	E76048 vol. 1 sec. 9	18 ÷ 14 AWG (screw) – 18 ÷ 16 AWG (screwless) - 300V - 15A - 105°C	UL 1059; CSA C22-2 N.158-1987
	LR 40455	20 ÷ 14AWG (screw) 24 ÷ 16AWG (screwless) - 300V - 15A	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
PA 239L/12P	109432	500	40x20x40	14.5

DIMENSIONAL
DRAWING

