


**Rectifier diodes  
Schottky barrier**

**PBYR2545CTF, PBYR2545CTX**

**FEATURES**

- Low forward volt drop
- Fast switching
- Reverse surge capability
- High thermal cycling performance
- Isolated mounting tab

**SYMBOL**



**QUICK REFERENCE DATA**

|                                   |
|-----------------------------------|
| $V_R = 40\text{ V} / 45\text{ V}$ |
| $I_{O(AV)} = 20\text{ A}$         |
| $V_F \leq 0.65\text{ V}$          |

**GENERAL DESCRIPTION**


Dual, common cathode schottky rectifier diodes in a plastic envelope with electrically isolated mounting tab. Intended for use as output rectifiers in low voltage, high frequency switched mode power supplies.

The PBYR2545CTF is supplied in the SOT186 package.  
The PBYR2545CTX is supplied in the SOT186A package.


**PINNING**

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | anode 1 (a) |
| 2   | cathode (k) |
| 3   | anode 2 (a) |
| tab | isolated    |

**SOT186**



**SOT186A**



**LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134)

| SYMBOL      | PARAMETER   | CONDITIONS  | MIN. | MAX.           |                | UNIT             |
|-------------|---|---|------|----------------|----------------|------------------|
|             |   |   |      | 40CTF<br>40CTX | 45CTF<br>45CTX |                  |
| $V_{RRM}$   | Peak repetitive reverse voltage                           | PBYR25<br>PBYR25  | -    | 40             | 45             | V                |
| $V_{RWM}$   | Working peak reverse voltage                              |   | -    | 40             | 45             | V                |
| $V_R$       | Continuous reverse voltage                                | $T_{hs} \leq 86\text{ }^\circ\text{C}$  | -    | 40             | 45             | V                |
| $I_{O(AV)}$ | Average rectified output current (both diodes conducting) | square wave; $\delta = 0.5$ ;<br>$T_{hs} \leq 98\text{ }^\circ\text{C}$   | -    | 20             |                | A                |
| $I_{FRM}$   | Repetitive peak forward current per diode                 | square wave; $\delta = 0.5$ ;<br>$T_{hs} \leq 98\text{ }^\circ\text{C}$   | -    | 20             |                | A                |
| $I_{FSM}$   | Non-repetitive peak forward current per diode             | $t = 10\text{ ms}$  | -    | 135            |                | A                |
|             |   | $t = 8.3\text{ ms}$   | -    | 150            |                | A                |
| $I_{RRM}$   | Peak repetitive reverse surge current per diode           | sinusoidal; $T_j = 125\text{ }^\circ\text{C}$ prior to surge; with reapplied $V_{RRM(max)}$ pulse width and repetition rate limited by $T_{jmax}$ | -    | 1              |                | A                |
| $T_j$       | Operating junction temperature                            |   | -    | 150            |                | $^\circ\text{C}$ |
| $T_{stg}$   | Storage temperature                                       |   | - 65 | 175            |                | $^\circ\text{C}$ |

**Rectifier diodes  
Schottky barrier**
**PBYR2545CTF, PBYR2545CTX**
**ISOLATION LIMITING VALUE & CHARACTERISTIC**
 $T_{hs} = 25\text{ }^{\circ}\text{C}$  unless otherwise specified

| SYMBOL     | PARAMETER  | CONDITIONS   | MIN. | TYP. | MAX. | UNIT |
|------------|--|--|------|------|------|------|
| $V_{isol}$ | Peak isolation voltage from all terminals to external heatsink   | SOT186 package; R.H. $\leq$ 65%; clean and dustfree  | -    | -    | 1500 | V    |
| $V_{isol}$ | R.M.S. isolation voltage from all terminals to external heatsink | SOT186A package; $f = 50\text{-}60\text{ Hz}$ ; sinusoidal waveform; R.H. $\leq$ 65%; clean and dustfree | -    | -    | 2500 | V    |
| $C_{isol}$ | Capacitance from pin 2 to external heatsink                      | $f = 1\text{ MHz}$   | -    | 10   | -    | pF   |

**THERMAL RESISTANCES**







| SYMBOL                | PARAMETER                               | CONDITIONS   | MIN. | TYP. | MAX.     | UNIT       |
|-----------------------|---|--|------|------|----------|------------|
| $R_{th\ j\text{-}hs}$ | Thermal resistance junction to heatsink | per diode<br>both diodes<br>(with heatsink compound) | -    | -    | 4.8<br>4 | K/W<br>K/W |
| $R_{th\ j\text{-}a}$  | Thermal resistance junction to ambient  | in free air  | -    | 55   | -        | K/W        |

**ELECTRICAL CHARACTERISTICS**
 $T_j = 25\text{ }^{\circ}\text{C}$  unless otherwise specified

| SYMBOL | PARAMETER                      | CONDITIONS  | MIN. | TYP. | MAX. | UNIT |
|--------|--------------------------------|---|------|------|------|------|
| $V_F$  | Forward voltage per diode      | $I_F = 20\text{ A}$ ; $T_j = 125\text{ }^{\circ}\text{C}$   | -    | 0.58 | 0.65 | V    |
| $I_R$  | Reverse current per diode      | $I_F = 20\text{ A}$<br>$V_R = V_{RWM}$  | -    | 0.63 | 0.68 | V    |
|        |                                | $V_R = V_{RWM}$ ; $T_j = 100\text{ }^{\circ}\text{C}$   | -    | 0.3  | 2    | mA   |
| $C_d$  | Junction capacitance per diode | $V_R = 5\text{ V}$ ; $f = 1\text{ MHz}$ ; $T_j = 25\text{ }^{\circ}\text{C}$ to $125\text{ }^{\circ}\text{C}$ | -    | 30   | 40   | mA   |
|        |                                |   | -    | 530  | -    | pF   |

Rectifier diodes  
Schottky barrier


PBYR2545CTF, PBYR2545CTX



Rectifier diodes  
Schottky barrier

PBYR2545CTF, PBYR2545CTX

**MECHANICAL DATA**




**Notes**

1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

Rectifier diodes  
Schottky barrier

PBYR2545CTF, PBYR2545CTX

**MECHANICAL DATA**



**Notes**

1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

Rectifier diodes  
Schottky barrier

PBYR2545CTF, PBYR2545CTX

## DEFINITIONS

|  |   |
|--|---|
| <b>Data sheet status</b>   |   |
| Objective specification  | This data sheet contains target or goal specifications for product development.       |
| Preliminary specification  | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification  | This data sheet contains final product specifications.                                |
| <b>Limiting values</b>   |   |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. |   |
| <b>Application information</b>   |   |
| Where application information is given, it is advisory and does not form part of the specification.  |   |
| © Philips Electronics N.V. 1998  |   |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.  |   |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.   |   |

## LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.