


**PC3541**

PT-250-SBG14-A-ZVG/US/ /W

Pressure sensors

Alternative article: PT5301

When selecting an alternative article and accessories please note that technical data may differ!



1: FKM seal / DIN 3869-14
tightening torque 25 Nm

**Product characteristics**

Electronic pressure sensor

Quick disconnect

for industrial applications

Process connection: G 1/4 A

Analog output

Measuring range: 0...250 bar

Application

| | |
|------------------------------|--|
| Application | Type of pressure: relative pressure Liquids and gases |
| Pressure rating [bar] | 400 |
| Bursting pressure min. [bar] | 1000 |
| Medium temperature [°C] | -25...90 |

Electrical data

| | |
|-----------------------------|------------------|
| Electrical design | DC |
| Operating voltage [V] | 8.5...36 DC |
| Insulation resistance [MΩ] | > 100 (500 V DC) |
| Protection class | III |
| Reverse polarity protection | yes |

Outputs

| | |
|-----------------|-------------------------------------|
| Output | Analog output |
| Output function | 4...20 mA analog |
| Analog output | 4...20 mA |
| Max. load [Ω] | (Ub - 8.5 V) x 50; 775 at Ub = 24 V |

Measuring / setting range

| | |
|-----------------------|---------|
| Measuring range [bar] | 0...250 |
|-----------------------|---------|

Accuracy / deviations

| | |
|---|--------------------------------|
| Accuracy / deviations (in % of the span) | |
| Characteristics deviation * | < ± 1.0 |
| Linearity | < ± 0.25 (BFSL) / < ± 0.5 (LS) |

PC3541

PT-250-SBG14-A-ZVG/US/ /W

Pressure sensors

| | |
|--------------------------|---------|
| Hysteresis | < ± 0.2 |
| Repeatability **) | < ± 0.1 |
| Long-term stability ***) | < ± 0.1 |

Temperature coefficients (TEMPCO) in the temperature range -25...90° C (in % of the span per 10 K)

| | |
|-----------------------------------|---------|
| Greatest TEMPCO of the zero point | < ± 0.1 |
| Greatest TEMPCO of the span | < ± 0.1 |

Reaction times

| | | |
|------------------------------------|------|---|
| Step response time analogue output | [ms] | 3 |
|------------------------------------|------|---|

Environment

| | | |
|---------------------|------|----------------|
| Ambient temperature | [°C] | -40...90 |
| Storage temperature | [°C] | -40...100 |
| Protection | | IP 67 / IP 69K |

Tests / approvals


| | | |
|----------------------|--|--|
| EMC | EN 61000-4-2 ESD: EN 61000-4-3 HF radiated: EN 61000-4-4 Burst: EN 61000-4-5 Surge: EN 61000-4-6 HF conducted: | 4 kV CD / 8 kV AD 10 V/m 4 kV coupling clamp 1 kV signal for DC units 10 V |
| Shock resistance | DIN IEC 68-2-27: | 50 g (11 ms) |
| Vibration resistance | DIN IEC 68-2-6: | 20 g (10...2000 Hz) |
| MTTF [Years] | | 1579 |

Mechanical data

| | |
|--------------------------|---|
| Process connection | G ¼ A |
| Materials (wetted parts) | stainless steel 316L / 1.4404; sealing: FPM (Viton) |
| Housing materials | stainless steel 316L / 1.4404; TROGAMID |
| Min. pressure cycles | 50 million |
| Weight [kg] | 0.079 |

Electrical connection

| | |
|------------|---------------|
| Connection | M12 connector |
|------------|---------------|

Wiring**Remarks**

| | |
|---------|---|
| Remarks | *) incl. drift due to tightening torque, zero and span error **) with temperature fluctuations < 10 K ***) in% of the span / 6 months BFSL = Best Fit Straight Line / LS = Limit Value Setting |
|---------|---|

| | | |
|---------------|---------|---|
| Pack quantity | [piece] | 1 |
|---------------|---------|---|

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — PC3541 — 19.11.2012

Alternative article: PT5301**When selecting an alternative article and accessories please note that technical data may differ!**