



PCSB20 Power Chip Shielded Backlight Inductors



Dimensions: $\frac{\text{Inches}}{\text{(mm)}}$



Features

- Designed for use in back light applications
- Ultra miniature size for high density mounting
- Magnetically shielded
- Designed with heat resistant materials for reflow operation
- Flat top for pick and place assembly
- Non standard values are available

Electrical

Inductance Range: 100 μ h to 10000 μ h.

Tolerance: $\pm 20\%$ over the entire inductance range.

Test Frequency: Inductance measured at 100KHz, 0.1 Vrms.

Operating Temp. Range: -40° to +85°C.

Physical

Marking: Color Code using standard EIA three dot system.

Packaging: 2500 pieces per 13 inch reel.

Allied Part Number	Inductance (μ h)	Tolerance (%)	SRF Reference (MHz)	DCR Max. (Ω)	*Rated Current Irms (mA)
PCSB20-101M-RC	100	20	12	.95	220
PCSB20-151M-RC	150	20	10	1.4	200
PCSB20-221M-RC	220	20	8	1.7	180
PCSB20-331M-RC	330	20	6	2.2	160
PCSB20-471M-RC	470	20	5	3.8	140
PCSB20-681M-RC	680	20	4	4.9	120
PCSB20-102M-RC	1000	20	2	9	100
PCSB20-152M-RC	1500	20	1	11	80
PCSB20-222M-RC	2200	20	1	19	50
PCSB20-332M-RC	3300	20	1	24	40
PCSB20-472M-RC	4700	20	1	30	30
PCSB20-682M-RC	6800	20	0.9	56	20
PCSB20-103M-RC	10000	20	0.8	74	10

*Temperature rise shall not be more than 30°C at Irms.
All specifications subject to change without notice.