





SMT sockets



SMT headers



Specify Contact/Shell  
976P 10μ" Gold/PHSBRNZ



Specify Contact/Shell  
622C 30μ" Gold/Tin  
623C Tin/Tin



Features

- Available in either DIP or PGA configurations
- Contacts float on the Z-axis to insure perfect coplanarity
- Socket profile = .166 above PCB
- Header profile = .232 above PCB with bottom of mated connector at .140 above PCB.
- Pick and Place Tabs for Automatic Assembly Equipment.
- Hi-Temp PPS insulators compatible with all SMT processes.
- Specially designed contact insures a high strength, high reliability solder joint every time
- Recommended PCB pad size: .050" round

How to Order


PGA 132H 622C1 - 1414 F  
 Pin Grid Array    See F section for further information    Contact 623C 976P    See F section for pattern options    FR4 Material

DSM 320 - 622C F  
 DIP Surface Mount    See page B4 for options    Contact 623C 976P    FR4 Material

9011644 0000126 T2T

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

www.DataSheet4U.com




Achieve near flush socket profile with our patented Plastic Pin Carrier (PPC™)  
Disposable Carrier System — Patent No. 4,420,877

### Features

- Rigid Pin Carrier for ease in assembly
- Contact is fully masked and protected during solder and washing.
- No expensive RTV compounds
- No contact intrusion – Eliminates damage or oversizing of contacts
- Full inspectability of solder joints
- Easy flux removal


B

#### .016" (0,41) ABOVE PC BOARD




| Specify | Contact/Shell                 |
|---------|-------------------------------|
| 710C    | 30μ" Gold/200μ" Tin           |
| 711C    | 30μ" Gold/10μ" Gold           |
| 714C    | 200μ" Tin-Lead/200μ" Tin-Lead |
| PTH =   | .042 ± .003                   |

#### .016" (0,41) ABOVE PC BOARD



| Specify | Contact/Shell       |
|---------|---------------------|
| 720C    | 30μ" Gold/200μ" Tin |
| 721C    | 30μ" Gold/10μ" Gold |
| PTH =   | .042 ± .003         |

#### .031" (0,79) ABOVE BOARD



| Specify | Contact/Shell       |
|---------|---------------------|
| 725C    | 30μ" Gold/200μ" Tin |
| 726C    | 200μ" Tin/200μ" Tin |
| PTH =   | .038 ± .003         |

## How To Order

PPC - DIP - 320 - 710C

Plastic Pin Carrier™  
HPC for Hi-Temp  
Material

Product Code

# of Contacts

Contact Style

Row-to-Row Spacing

#### Contact/Shell:

Outer Shell — 1/2 Hard Brass  
Inner Contact — Beryllium Copper

#### Plating:

Outer Shell — Gold over Nickel or Tin over Nickel  
or 93/7 Tin/Lead over Nickel  
Inner Contact — Gold over Nickel or Tin over Nickel

| NO. OF CONTACTS  | 6 | 8 | 14 | 16 | 18             | 20 | 22 | 24 | 28 | 20              | 22 | 24 | 24 | 28              | 32 | 36 | 40 | 48              | 50 | 64 |  |
|------------------|---|---|----|----|----------------|----|----|----|----|-----------------|----|----|----|-----------------|----|----|----|-----------------|----|----|--|
| CENTER TO CENTER |   |   |    |    | .300<br>(7,62) |    |    |    |    | .400<br>(10,16) |    |    |    | .600<br>(15,24) |    |    |    | .900<br>(22,86) |    |    |  |

9011644 0000021 567

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

B4

See page F5 and F6 for the industry's most effective PGA Extraction Tools.

### 3 x 3 ARRAYS

DIMENSIONS:

**SOCKETS**  
.350" square  
(8,89)mm square

**PPC™ CARRIERS**  
.300" square  
(7,62)mm square



09M 0301



08S 0310



08M 0302



06M 0303



06M 0304



04M 0305

### 4 x 4 ARRAYS

DIMENSIONS:

**SOCKETS**  
.450" square  
(11,43)mm square

**PPC™ CARRIERS**  
.400" square  
(10,16)mm square



16M 0401



12M 0408



12M 0402



12M 0403



08M 0404



08M 0405



08M 0406



04M 0407

### 5 x 5 ARRAYS

DIMENSIONS:

**SOCKETS**  
.550" square  
(13,97)mm square

**PPC™ CARRIERS**  
.500" square  
(12,70)mm square



25M 0501



24M 0502



23M 0515



22M 0503



21M 0516



21M 0512



21M 0509



20M 0514



20M 0513



20M 0506



20M 0507



16M 0508



16M 0505



15M 0511



12M 0504



10M 0510

MOLDED SOCKETS



9011644 0000066 725


Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**


Pin Count | Center Configuration | Pattern Number

See page F2 for ordering information


DIMENSIONS: **SOCKETS** .650" square (16,51)mm square **PPC™ CARRIERS** .600" square (15,24)mm square **6 x 6 ARRAYS**



DIMENSIONS: **SOCKETS** .750" square (19,05)mm square **PPC™ CARRIERS** .700" square (17,78)mm square **7 x 7 ARRAYS**



DIMENSIONS: **SOCKETS** .850" square (21,59)mm square **PPC™ CARRIERS** .800" square (20,32)mm square **8 x 8 ARRAYS**



9011644 0000067 661

F

Sockets from the industry's source!








































Widest variety of contact styles - over 140 contact options listed in Section A.

## 9 x 9 ARRAYS

DIMENSIONS:

**SOCKETS**  
.950" square  
(24,13)mm square

**PPC™ CARRIERS**  
.900" square  
(22,86)mm square



9011644 0000068 5T8

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

























**PGA-68H 003B1-1132**

Pin Count  
Center Configuration

Pattern Number

See page F2 for ordering information

DIMENSIONS: **SOCKETS** 1.050" square (26,67)mm square **PPC™ CARRIERS** 1.000" square (25,40)mm square **10 x 10 ARRAYS**



All McKenzie  
Molded Sockets  
**RU**  
Recognized

9011644 0000069 434

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F15




































Select PPC™ (disposable carrier system) Sockets for low profile PGA applications.

## 11 x 11 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.150" square  
(29,21)mm square

**PPC™ CARRIERS**  
1.100" square  
(27,94)mm square



9011644 000070 156

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-6 8 H 0 0 3 B 1 - 1 1 3 2**

Pin Count

Center Configuration

Pattern Number



































See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
1.150" square  
(29,21)mm square

**PPC™ CARRIERS**  
1.100" square  
(27,94)mm square

**11 x 11 ARRAYS**



9011644 000071 092

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F17



























Decoupling Capacitor Sockets manufactured to your specifications.  
 Fax us your requirements today.

## 11 x 11 ARRAYS

DIMENSIONS:

**SOCKETS**  
 1.150" square  
 (29,21)mm square

**PPC™ CARRIERS**  
 1.100" square  
 (27,94)mm square



All McKenzie  
 Molded Sockets  
  
 Recognized

9011644 000072 T29

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**

Pin Count

Center Configuration

Pattern Number




































See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
1.250" square  
(31,75)mm square

**PPC™ CARRIERS**  
1.200" square  
(30,48)mm square

**12 x 12 ARRAYS**



9011644 0000073 965

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F19

F








See page F5 and F6 for the industry's most effective PGA Extraction Tools.

## 12 x 12 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.250" square  
(31,75)mm square

**PPC™ CARRIERS**  
1.200" square  
(30,48)mm square























## 13 x 13 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.350" square  
(34,29)mm square

**PPC™ CARRIERS**  
1.300" square  
(33,02)mm square



9011644 000074 8T1

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-6 8 H 0 0 3 B 1 - 1 1 3 2**

Pin Count | Center Configuration | Pattern Number


See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
1.350" square  
(34,29)mm square

**PPC™ CARRIERS**  
1.300" square  
(33,02)mm square

**13 x 13 ARRAYS**



**F**

9011644 0000075 738

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

**F21**

Sockets from the industry's source!

























Widest variety of contact styles - over 140 contact options listed in Section A.

**13 x 13 ARRAYS**

DIMENSIONS:

**SOCKETS**  
1.350" square  
(34,29)mm square

**PPC™ CARRIERS**  
1.300" square  
(33,02)mm square



9011644 0000076 674

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

PGA-68H 003B1-1132

Pin Count | Center Configuration | Pattern Number


























See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
1.350" square  
(34,29)mm square

**PPC™ CARRIERS**  
1.300" square  
(33,02)mm square

**13 x 13 ARRAYS**



9011644 0000077 500

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F23

F

## PGA Sockets







Select PPC™ (disposable carrier system) Sockets for low profile PGA applications.

### 13 x 13 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.350" square  
(34,29)mm square

**PPC™ CARRIERS**  
1.300" square  
(33,02)mm square


















### 14 x 14 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.450" square  
(36,83)mm square

**PPC™ CARRIERS**  
1.400" square  
(35,56)mm square



9011644 0000078 447

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**































Pin Count

Center Configuration

Pattern Number

See page F2 for ordering information

**SOCKETS** 1.450" square (36,83)mm square      **PPC™ CARRIERS** 1.400" square (35,56)mm square      **14 x 14 ARRAYS**



9011644 0000079 383

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F25






















Decoupling Capacitor Sockets manufactured to your specifications.  
Fax us your requirements today.

## 14 x 14 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.450" square  
(36,83)mm square

**PPC™ CARRIERS**  
1.400" square  
(35,56)mm square



All McKenzie  
Molded Sockets

Recognized

9011644 000080 0T5

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**

Pin Count  
Center Configuration

Pattern Number































See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
1.550" square  
(39,37)mm square

**PPC™ CARRIERS**  
1.500" square  
(38,10)mm square

**15 x 15 ARRAYS**



9011644 0000081 T31

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F27

F































See page F5 and F6 for the industry's most effective PGA Extraction Tools.

## 15 x 15 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.550" square  
(39,37)mm square

**PPC™ CARRIERS**  
1.500" square  
(38,10)mm square



9011644 000082 978

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**

Pin Count  
Center Configuration

Pattern Number

See page F2 for ordering information

| DIMENSIONS: | SOCKETS<br>1.550" square<br>(39,37)mm square | PPC™ CARRIERS<br>1.500" square<br>(38,10)mm square | 15 x 15 ARRAYS |  |  |
|-------------|--|--|----------------|--|--|
|             |  |  |                |  |  |
|             |  |  |                |  |  |
|             |  |  |                |  |  |
|             |  |  |                |  |  |
|             |  |  |                |  |  |



9011644 000083 804

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

Sockets from the industry's source!




Widest variety of contact styles - over 140 contact options listed in Section A.

## 15 x 15 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.550" square  
(39,37)mm square

**PPC™ CARRIERS**  
1.500" square  
(38,10)mm square

















## 16 x 16 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.650" square  
(41,91)mm square

**PPC™ CARRIERS**  
1.600" square  
(40,64)mm square



MOLDED SOCKETS



9011644 000084 740

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

PGA-68H 003B1-1132  
 Pin Count | Center Configuration | Pattern Number



















See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
 1.650" square  
 (41,91)mm square

**PPC™ CARRIERS**  
 1.600" square  
 (40,64)mm square

**16 x 16 ARRAYS**



MOLDED INSULATORS



9011644 0000085 687

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F31

RISC Sockets immediately available

## 17 x 17 ARRAYS


























### SOCKETS

1.750" square  
(44,45)mm square

### PPC™ CARRIERS

1.700" square  
(43,18)mm square

DIMENSIONS:



9011644 0000086 513














Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**





Pin Count | Center Configuration | Pattern Number

See page F2 for ordering information







DIMENSIONS: SOCKETS 1.750" square (44,45)mm square    PPC™ CARRIERS 1.700" square (43,18)mm square    17 x 17 ARRAYS



- 1. EMPTY SIDE, NO CONTACT
- 2. POLARITY PLUG



INTEL  
i486™



9011644 0000087 45T




Select PPC™ (disposable carrier system) Sockets for low profile PGA applications.

## 17 x 17 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.750" square  
(44,45)mm square

**PPC™ CARRIERS**  
1.700" square  
(43,18)mm square




## 18 x 18 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.850" square  
(46,99)mm square

**PPC™ CARRIERS**  
1.800" square  
(45,72)mm square



9011644 0000088 396

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

PGA-68H 003B1-1132

Pin Count | Center Configuration | Pattern Number


























See page F2 for ordering information

DIMENSIONS:

**SOCKETS**  
1.850" square  
(46,99)mm square

**PPC™ CARRIERS**  
1.800" square  
(45,72)mm square

**18 x 18 ARRAYS**



9011644 000089 222

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F35






Select PPC™ (disposable carrier system) Sockets for low profile PGA applications.

## 18 x 18 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.850" square  
(46,99)mm square

**PPC™ CARRIERS**  
1.800" square  
(45,72)mm square


















## 19 x 19 ARRAYS

DIMENSIONS:

**SOCKETS**  
1.950" square  
(49,53)mm square

**PPC™ CARRIERS**  
1.900" square  
(48,26)mm square



9011644 000090 T44


Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**

Pin Count | Center Configuration | Pattern Number

See page F2 for ordering information

**SOCKETS** 1.950" square (49,53)mm square      **PPC™ CARRIERS** 1.900" square (48,26)mm square      **19 x 19 ARRAYS**



9011644 000091 980

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020


RISC Sockets immediately available.

## 20 x 20 ARRAYS

DIMENSIONS:

**SOCKETS**  
2.050" square  
(52.07)mm square

**PPC™ CARRIERS**  
2.000" square  
(50.80)mm square



9011644 000092 817


PGA-68H 003B1-1132

Pin Count | Center Configuration | Pattern Number

Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

See page F2 for ordering information

DIMENSIONS: SOCKETS 2.150" square (54,61)mm square      PPC™ CARRIERS 2.100" square (53,34)mm square      21 x 21 ARRAYS



MOLDED SOCKETS



9011644 000093 753

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020











Sockets from the industry's source!

Widest variety of contact styles — over 140 contact options listed in Section A

## 22 x 22 ARRAYS

**SOCKETS**  
DIMENSIONS: 2.250" square  
(57,15)mm square











**PPC™ CARRIERS**  
2.200" square  
(55,88)mm square



## 23 x 23 ARRAYS

**SOCKETS**  
DIMENSIONS: 2.350" square  
(59,69)mm square

**PPC™ CARRIERS**  
2.300" square  
(58,42)mm square



Polarity mark (contact #1) is located in upper left corner. Top view of sockets are shown from highest to lowest pin count. Arrays are available in molded Thermoplastic (UL 94V-0 approved) or vapor phase and infrared compatible PPS. Optional FR4 on request.

**PGA-68H 003B1-1132**










Pin Count | Center Configuration | Pattern Number

See page F2 for ordering information

DIMENSIONS:      SOCKETS      PPC™ CARRIERS      **24 x 24 ARRAYS**

2.450" square      2.400" square      2.400" square

(62,23)mm square      (60,96)mm square



Press Fit PGA Sockets — A Solderless Alternative

9011644 000095 526

910 Page Avenue • Fremont, California 94538 USA • Telephone (510) 651-2700 • FAX (510) 651-1020

F










Select PPC™ (disposable carrier system) Sockets for low profile PGA applications.

## 25 x 25 ARRAYS

DIMENSIONS:

**SOCKETS**  
2.550" square  
(64,77)mm square

**PPC™ CARRIERS**  
2.500" square  
(63,50)mm square






## 26 x 26 ARRAYS

DIMENSIONS:

**SOCKETS**  
2.650" square  
(67,31)mm square

**PPC™ CARRIERS**  
2.600" square  
(66,04)mm square






## 27 x 27 ARRAYS

DIMENSIONS:

**SOCKETS**  
2.750" square  
(69,85)mm square

**PPC™ CARRIERS**  
2.700" square  
(68,58)mm square



9011644 000096 462