

Version: 3.0

## TECHNICAL SPECIFICATION

Model NO. : PM061WX1

The content of this information is subject to be changed without notice.  
Please contact E Ink or its agent for further information.

☐ Customer's Confirmation


Customer \_\_\_\_\_

Date \_\_\_\_\_

By \_\_\_\_\_

☐ E Ink's Confirmation

Confirmed By



Prepared By



## Revision History

Rev.	Issued Date	Revised Contents
0.1	Jan. 11, 2009	Preliminary
1.0	Mar. 13, 2009	New
2.0	August.23.2011	Update to E Ink logo
3.0	Oct.21.2011	Modify page 21 Optical Characteristics Θ 11 ==> MIN : 50 , TYP : 60

# TECHNICAL SPECIFICATION

## **CONTENTS**

<b>NO.</b>	<b>ITEM</b>	<b>PAGE</b>
-	Cover	1
-	Revision History	2
-	Contents	3
1	Application	4
2	Features	4
3	Mechanical Specifications	4
4	Mechanical Drawing of TFT-LCD module	5
5	Input / Output Terminals	7
6	Absolute Maximum Ratings	11
7	Electrical Characteristics	11
8	Pixel Arrangement	13
9	Display Color and Gray Scale Reference	14
10	Block Diagram	15
11	Interface Timing	16
12	Power On Sequence	21
13	Optical Characteristics	21
14	Handling Cautions	25
15	Reliability Test	26
16	Packing Diagram	27

**1. Application :**

This data sheet applies to a color TFT LCD module, PM061WX1.

PM061WX1 module applies to OA product, portable DVD, car TV (must use Analog to Digital driving board), which requires high quality flat panel display. If you must use in severe reliability environment, please don't extend over PVI's reliability test conditions.

If you use PM061WX1, Prime View advises to use PVI's timing controller IC (PVI-2003A) on your system which will generate proper timing signals to control PM061WX1.


**2. Features :**


- . Wide VGA (800\*480 pixels) resolution
- . Amorphous silicon TFT LCD panel with LED Back-light
- . Pixel in stripe configuration
- . Thin and light weight
- . Display Colors : 262,144 colors
- . TTL transmission interface
- . Wide view angle

**3. Mechanical Specifications :**

Parameter	Specifications	Unit
Screen Size	6.1 (diagonal)	inch
Display Format	800 × (R, G, B) × 480	dot
Display Colors	262,144	
Active Area	136.2 (H) × 72.0 (V)	mm
Pixel Pitch	0.17025 (H) × 0.150 (V)	mm
Pixel Configuration	Stripe	
Outline Dimension	149.0 (w) × 82.9 (H) × 5.9 (typ.) (D) 149.0 (w) × 82.9 (H) × 6.2 (FPC side) (D)	mm
Weight	120±10	g
Back-light	30-LED	
Surface treatment	Anti-glare	
Display mode	Normally White	
Gray scale inversion direction	6 o'clock [ref to Note 13-1 ]	

#### 4. Mechanical Drawing of TFT-LCD Module :





## 5. Input / Output Terminals :

### 5-1) TFT-LCD Panel Driving :

Connector type : IRISO 9637S-30Y905 30pin Pitch : 0.5mm

CN 1

Pin No.	Symbol	I/O	Function	Remark
1	DIO1	I/O	Horizontal Start Pulse Signal Input or Output	Note 5-6
2	VSS1	I	Ground	
3	VDD1	I	Power Supply	
4	CLK	I	Horizontal Shift Clock	Note 5-4
5	VSS1	I	Ground	
6	R/L	I	Right / Left selection	Note 5-6
7	R0	I	Red Data (LSB)	
8	R1	I	Red Data	
9	R2	I	Red Data	
10	R3	I	Red Data	
11	R4	I	Red Data	
12	R5	I	Red Data (MSB)	
13	VSS1	I	Ground	
14	G0	I	Green Data (LSB)	
15	G1	I	Green Data	
16	G2	I	Green Data	
17	G3	I	Green Data	
18	G4	I	Green Data	
19	G5	I	Green Data (MSB)	
20	VSS1	I	Ground	
21	B0	I	Blue Data (LSB)	
22	B1	I	Blue Data	
23	B2	I	Blue Data	
24	B3	I	Blue Data	
25	B4	I	Blue Data	
26	B5	I	Blue Data (MSB)	
27	LD	I	Load output signal	Note 5-7
28	REV	I	Data invert control	Note 5-8
29	POL	I	Polarity selection	Note 5-9
30	DIO2	I/O	Horizontal Start Pulse Signal Input or Output	Note 5-6

## CN 2

Pin No.	Symbol	I/O	Function	Remark
1	VSS2	I	Ground	
2	V1	I	Gamma Voltage 1	Note 5-11
3	V2	I	Gamma Voltage 2	
4	V3	I	Gamma Voltage 3	
5	V4	I	Gamma Voltage 4	
6	V5	I	Gamma Voltage 5	
7	V6	I	Gamma Voltage 6	
8	V7	I	Gamma Voltage 7	
9	VSS2	I	Ground	
10	V8	I	Gamma Voltage 8	Note 5-11
11	V9	I	Gamma Voltage 9	
12	V10	I	Gamma Voltage 10	
13	V11	I	Gamma Voltage 11	
14	V12	I	Gamma Voltage 12	
15	V13	I	Gamma Voltage 13	
16	V14	I	Gamma Voltage 14	
17	VSS2	I	Ground	
18	VDD2	I	Voltage for analog circuit	
19	VCOM	I	Common Voltage	
20	XON	I	NC	Note 5-10
21	OE	I	Output Enable	Note 5-5
22	U/D	I	Up / Down Selection	Note 5-3
23	CKV	I	Vertical Shift Clock	Note 5-7
24	STVU	I/O	Vertical Shift Pulse Signal Input or Output	Note 5-3
25	STVD	I/O	Vertical Shift Pulse Signal Input or Output	Note 5-3
26	VGG	I	Gate On Voltage	Note 5-2
27	GND	I	Ground	
28	VCC	I	Voltage for logic circuit	
29	GND	I	Ground	
30	VEE	I	Gate Off Voltage	Note 5-1



Note 5-1 : Gate off voltage,  $V_{EE(TYP.)} = -8V$

Note 5-2 : Gate on voltage,  $V_{GG(TYP.)} = +17V$

Note 5-3 : Select up or down shift

U/D	STVU	STVD	Shift
1	Hi-Z	Input	Down to Up
0	Input	Hi-Z	Up to Down

Note 5-4 : Gate driver shift clock

Note 5-5 : When OE is connected to high “1”, the driver outputs are disabled (Gate output =  $V_{EE}$ ).  
Under this condition, the operation of registers will not be affected.

Note 5-6 : Select left or right shift


R/L	DIO1	DIO2	Shift
1	Input	Hi-Z	Left to right
0	Hi-Z	Input	Right to left

Note 5-7 : Latch the polarity of outputs and switch the new data to outputs. At the rising edge (LD), latch the “POL” signal to control the polarity of the outputs.

Note 5-8 : Control whether the Data R0~G5 are inverted or not. (PVI suggests connecting to GND)  
When “REV=1”, these data will be inverted.  
EX: “00”→”3F”, “07”→”38”, “15”→”2A”

Note 5-9 : Polarity selector for dot-inversion control. Available at the rising edge of LD.  
When POL=1: Even outputs range from V1~V7, and Odd outputs range from V8~V14;  
When POL=0: Even outputs range from V8~V14, and Odd outputs range from V1~V7.

Note 5-10 : This pin is NC or must connect VCC.

Note 5-11 : Typical Application Circuit (When  $V_{DD2}$  (Typ.) = +9.5V)


**5-2) Backlight driving :**

Connector type : JST BHSR-02VS-1

Pin No	Symbol	Description	Remark
1	+	Input terminal (Anode)	Wire color : Red
2	-	Input terminal (Cathode)	Wire Color : Black

**6. Absolute Maximum Ratings :**

VSS1=VSS2=GND=0V, Ta=25℃

Parameters	Symbol	MIN.	MAX.	Unit	Remark
Supply Voltage	V <sub>DD1</sub>	-0.3	5.0	V	
	V <sub>CC</sub>			V	
	V <sub>DD2</sub>	-0.5	12.0	V	
	V <sub>GG</sub>	-0.3	40.0	V	
	V <sub>GG</sub> -V <sub>EE</sub>	-	40.0	V	
	V <sub>EE</sub>	-20	0.3	V	
Operating Temperature	Top	-30	85	℃	
Storage Temperature	Tst	-40	95	℃	

**7. Electrical Characteristics :****7-1) Recommended Operating Conditions :**

VSS1=VSS2=GND=0V, Ta=25℃

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Supply Voltage for Source Driver	V <sub>DD1</sub>	3.0	3.3	3.6	V	
	V <sub>DD2</sub>	-	9.5	-	V	
Supply Voltage for Gate Driver	V <sub>GG</sub>	-	17.0	-	V	
	V <sub>EE</sub>	-	-8.0	-	V	
	V <sub>CC</sub>	3.0	3.3	3.6	V	
Digital Input Voltage	V <sub>IH</sub>	0.8V <sub>DD1</sub>	-	V <sub>DD1</sub>	V	
	V <sub>IL</sub>	0	-	0.2V <sub>DD1</sub>	V	
V <sub>com</sub> Voltage	V <sub>com</sub>	-	3.3	-	V	

## 7-2) Recommended driving condition for LED back light :

Ta = 25℃


Parameter	Symbol	Min	TYP	MAX	Unit	Remark
Supply voltage of LED backlight	$V_{LED}$	-	-	10.4	V	Note 7-1
Supply current of LED backlight	$I_{LED}$	-	12	-	mA	Note 7-2
Backlight Power Consumption	$P_{LED}$	-	-	1248	mW	Note 7-3

Note 7-1 : The  $I_{LED}$  = 120 mA, Constant current.

Note 7-2 : The LED driving condition is defined for each LED module. (3 LED Serial)

Input current = 12mA \* 10 = 120mA

Note 7-3 :  $P_{LED} = V_{LED-1} * I_{LED-1} + V_{LED-2} * I_{LED-2} \dots\dots + V_{LED-9} * I_{LED-9} + V_{LED-10} * I_{LED-10}$




## 7-3) Power Consumption :

Parameter	Symbol	Condition	Typ.	Max.	Unit	Remark
Supply Current for Gate Driver (Hi level)	$I_{GG}$	$V_{GG} = +17V$	0.13	0.39	mA	
Supply Current for Gate Driver (Low level)	$I_{EE}$	$V_{EE} = -8V$	0.14	0.42	mA	
Supply Current for Source Driver (Digital)	$I_{DD1}$	$V_{DD1} = +3.3$	3.49	6.98	mA	
Supply Current for Source Driver (Analog)	$I_{DD2}$	$V_{DD2} = +9.5$	15.34	30.68	mA	
Supply Current for Gate Driver (Digital)	$I_{CC}$	$V_{CC} = +3.3$	0.10	0.30	mA	
LCD Panel Power Consumption			160.55	325.30	mW	Note 7-4
Total Power Consumption			-	1.573	W	

Note 7-4 : The power consumption for back light is not included.

## 8. Pixel Arrangement :

The LCD module pixel arrangement is the stripe.




## 9. Display Color and Gray Scale Reference :

Color		Input Color Data																	
		Red						Green						Blue					
		R5	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Red	Red (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red (02)	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker																		
	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
	Brighter																		
	Red (61)	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Green	Green (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	Green (02)	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
	Darker																		
	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
	Brighter																		
	Green (61)	0	0	0	0	0	0	1	1	1	1	0	1	0	0	0	0	0	0
	Green (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	Green (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Blue	Blue (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue (02)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0
	Darker																		
	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
	Brighter																		
	Blue (61)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	1
	Blue (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	Blue (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

## 10. Block Diagram :

### TFT-module Block Diagram :



If you use PM061WX1, you can apply PVI-2003 A (Timing controller) which will generate timing signals to support PM061WX1.

## 11. Interface Timing

### 11.1) Timing Parameters

AC Electrical Characteristics ( $V_{CC}=V_{DD1}=3.3V$ ,  $V_{DD2}=9.5V$ ,  $GND=V_{SS1}=V_{SS2}=0V$ ,  $T_a=25^{\circ}C$ )

Parameter	Symbol	Min.	Typ.	Max.	Unit
CLK Frequency	Fclk	-	32	40	MHz
CLK Pulse Width	Tcw	25	-	-	ns
Data Set-up Time	Tsu	4	-	-	ns
Data Hold Time	Thd	2	-	-	ns
Propagation Delay of DIO2/1	Tphl	6	10	15	ns
Time That The Last Data to LD	Tld	1	-	-	Tcw
Pulse width of LD	Twld	2	-	-	Tcw
Time That LD to DIO1/2	Tlds	5	-	-	Tcw
POL Set-up Time	Tpsu	6	-	-	ns
POL Hold Time	Tphd	6	-	-	ns
OE Pulse Width	T <sub>OE</sub>	1	-	-	μs
CKV Pulse Width	T <sub>CKV</sub>	500	-	-	ns
STV Set-up Time	T <sub>SUV</sub>	400	-	-	ns
STV Hold Time	T <sub>HDV</sub>	400	-	-	ns
Horizontal Display Period	T <sub>HDP</sub>	-	800	-	Tcw
Horizontal Period Timing Range	T <sub>HP</sub>	-	1056	-	Tcw
Horizontal Lines Per Field	T <sub>V</sub>	484	508	620	T <sub>HP</sub>
Vertical Display Timing Range	T <sub>DV</sub>	-	480	-	T <sub>HP</sub>



## 11.2) Timing Diagram :




Fig. 11-1 Horizontal timing (1)




Fig. 11-2 Horizontal timing(2)




Fig. 11-3 Vertical shift clock timing





Fig. 11-4 Vertical timing

## 12. Power On Sequence :



$$1. 10ms \leq T_1 < T_2$$

$$2. 0ms < T_3 \leq T_4 \leq 10ms$$


## 13. Optical Characteristics :

### 13-1) Specification :

 $T_a = 25^\circ\text{C}$ 


Parameter		Symbol	Condition	MIN.	TYP.	MAX.	Unit	Remarks
Viewing Angle	Horizontal	$\theta_{21}, \theta_{22}$	$CR \geq 10$	70	75		deg	Note 13-1
	Vertical	$\theta_{12}$		45	50	-	deg	
		$\theta_{11}$		50	60	-	deg	
Contrast Ratio		CR	At optimized Viewing angle	250	400	-	-	Note 13-2
Response time	Rise	Tr	$\theta = 0^\circ$	-	10	15	ms	Note 13-3
	Fall	Tf		-	15	20	ms	
Brightness			$\theta = 0^\circ / \phi = 0$	400	500		cd/m <sup>2</sup>	Note 13-4
Luminance Uniformity		U	$\theta = 0^\circ$	75	80	-	%	Note 13-5
LED Life Time				50000	-	-	hr	Note 13-8
White Chromaticity		x	$\theta = 0^\circ$	0.27	0.31	0.35	-	
		y	$\theta = 0^\circ$	0.30	0.34	0.38	-	
Cross Talk			$\theta = 0^\circ$	-	-	3.5	%	Note 13-6

Note 13-1 : The definitions of viewing angles are as follow




Note 13-2 : The definition of contrast ratio  $CR = \frac{\text{Luminance at White Pattern}}{\text{Luminance at Black Pattern}}$

Note 13-3 : Definition of Response Time  $T_r$  and  $T_f$  :



Note 13-4 : The optical characteristics shall be measured in dark room (ambient illumination on panel surface less than 1 Lux). The measuring configuration shows as following figure.



Optical characteristics measuring configuration

Note 13-5 : The uniformity of LCD is defined as :

$$U = \frac{\text{The Minimum Brightness of the 9 testing Points}}{\text{The Maximum Brightness of the 9 testing Points}}$$


Luminance meter : BM-5A or BM-7 fast (TOPCON)

Measurement distance : 500 mm +/- 50 mm

Ambient illumination < 1 Lux

Measuring direction : Perpendicular to the surface of module

The test pattern is white.



Note 13-6: Cross Talk (CTK) =  $\frac{|YA-YB|}{YA} \times 100\%$

YA: Brightness of Pattern A

YB: Brightness of Pattern B


Luminance meter : BM 5A or BM-7 fast (TOPCON)

Measurement distance : 500 mm +/- 50 mm


Ambient illumination < 1 Lux

Measuring direction : Perpendicular to the surface of module

Pattern A  
(Gray Level 31)



Pattern B  
(Gray Level 31, central  
black box exclusive)



✕: Measuring Point (A and B are at the same point.)

(Gray Level 0)

Note 13-7 : Topcon BM-7(fast)luminance meter 1° field of view is used in the testing.

Note 13-8 : The “LED Life time” is defined as the module brightness decrease to 50% original Brightness that the ambient temperature is 25°C and  $I_{LED}=120mA$ .



## 14. Handling Cautions :

### 14-1) Mounting of module :

- Please power off the module when you connect the input/output connector.
- Polarizer which is made of soft material and susceptible to flaw must be handled carefully.
- Protective film (Laminator) is applied on surface to protect it against scratches and dirt.
- Please following the tear off direction as figure14-1 to remove the protective film as slowly as possible, so that electrostatic charge can be minimized.

### 14-2) Precautions in mounting :

- When metal part of the TFT-LCD module (shielding lid and rear case) is soiled, wipe it with soft dry cloth.
- Wipe off water drops or finger grease immediately. Long contact with water may cause discoloration or spots.
- TFT-LCD module uses glass which breaks or cracks easily if dropped or bumped on hard surface. Please handle with care.
- Since CMOS LSI is used in the module. So take care of static electricity and earth yourself when handling.

### 14-3) Adjusting module :

- Adjusting volumes on the rear face of the module have been set optimally before shipment.
- Therefore, do not change any adjusted values. If adjusted values are changed, the specifications described may not be satisfied.

### 14-4) Others :

- Do not expose the module to direct sunlight or intensive ultraviolet rays for many hours.
- Store the module at a room temperature place.
- The voltage of beginning electric discharge may over the normal voltage because of leakage current from approach conductor by to draw lump read lead line around.
- If LCD panel breaks, it is possibly that the liquid crystal escapes from the panel. Avoid putting it into eyes or mouth. When liquid crystal sticks on hands, clothes or feet. Wash it out immediately with soap.
- Observe all other precautionary requirements in handling general electronic components.
- Please adjust the voltage of common electrode as material of attachment by 1 module.

### 14-5) Polarizer mark :

The polarizer mark is to describe the direction of wide view angle film how to mach up with the rubbing direction.




Figure 14-1 the way to peel off protective film

## 15. Reliability Test :

No	Test Item	Test Condition	Remark
1	High Temperature Storage Test	Ta = +95℃, 240 hrs	
2	Low Temperature Storage Test	Ta = -40℃, 240 hrs	
3	High Temperature Operation Test	Ta = +85℃, 240 hrs	
4	Low Temperature Operation Test	Ta = -30℃, 240 hrs	
5	High Temperature & High Humidity Operation Test	Ta = +60℃, 90%RH, 240 hrs (No Condensation)	
6	Thermal Cycling Test (non-operating)	-30℃ → +80℃, 200 Cycles 30min 30min	
7	Vibration Test (non-operating)	Frequency : 10 ~ 55 Hz, Amplitude : 1 mm Sweep time : 11 min Test Period : 6 Cycles for each direction of X, Y, Z	
8	Shock Test (non-operating)	100G, 6ms Direction: ±X, ±Y, ±Z Cycle: 3 times	
9	Electrostatic Discharge Test (non-operating)	200pF, 0Ω ±200V 1 time / each terminal	

Ta : ambient temperature

Note : The protective film must be removed before temperature test.

### [Criteria]

There can be no display failures after exposure to reliability tests (including : line defect, no image).  
 All the cosmetic specification is judged before the reliability stress.

## 16. Packing :

NOTE:

- 1.Q'TY: 40 pcs moudule /carton.
- 2.Dimension: 530\*295\*230mm
- 3.Weight: 7.5 Kg

4	CARTON	1	
3	靜電袋	40	抗靜電
2	PM061WX1	40	
1	瓦楞隔板緩衝材	1	上蓋+ 底座
ITEM	DESCRIPTION	QTY	REMARK

MTL.SPEC.	UNSPECIFIED TOL'S	REMARK
	ANGLE	
	ROUGHNESS	

**Eink** | 元太科技工業股份有限公司  
E ink Holdings Inc.

APPROVE	Frank shin	09.03.24	SCALE	UNIT	SHEET
CHECK	Frank shin	09.03.24			1 OF 1
DRAWN	Josephh	09.03.24	MTL.NO.		

DWG.TITLE	DWG. FILE:	REV.	SIZE
PM061WX1 Module Packing Draw		01	A4