

PQ7DV10

Variable Output, (1.5 to 7V) 10A Output Low Power-loss Voltage Regulator


■ Feature

- 10A output type
- Low power-loss (Dropout voltage : MAX.0.5V at $I_o=10A$)
- Variable output type (1.5 to 7V)
- Low operating voltage (Minimum input voltage : 3.0V)
- High-precision reference voltage type
(Reference voltage precision : $\pm 2.0\%$)
- TO-3P package
- Built-in ON/OFF control function
- Built-in overcurrent protection, overheat protection function

■ Applications

- Power supplies for various electronic equipment such as personal computers

■ Outline Dimensions



■ Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Rating	Unit
*1 Input voltage	V _{IN}	10	V
*1 ON/OFF control terminal voltage	V _C	10	V
*1 Output adjustment terminal voltage	V _{ADJ}	5	V
Output current	I _O	10	A
Power dissipation (No heat sink)	P _{D1}	2.2	W
Power dissipation (With infinite heat sink)	P _{D2}	60	W
*2 Junction temperature	T _j	150	°C
Operating temperature	T _{opr}	-20 to +80	°C
Storage temperature	T _{stg}	-40 to +150	°C
Soldering temperature	T _{sol}	260 (For 10s)	°C

*1 All are open except GND and applicable terminals.

*2 Overheat protection may operate at 125=<T_j<=150°C.




Please refer to the chapter "Handling Precautions".

SHARP

"In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest version of the device specification sheets before using any SHARP's device."

■ Electrical Characteristics(Unless otherwise specified, conditions shall be $V_{IN}=5V$, $I_o=5A$, $V_o=3V$ ($R_i=2k\Omega$) $T_a=25^\circ C$)

Parameter	Symbol	Conditions	NIN.	TYP.	MAX.	Unit
Input voltage	V_{IN}	-	3	-	10	V
Reference voltage	V_o	-	1.5	-	7	V
Reference voltage	V_{ref}	-	1.225	1.25	1.275	V
Load regulation	R_{regL}	$I_o=5mA$ to $10A$	-	0.5	2	%
Line regulation	R_{regI}	$V_{IN}=4$ to $10V$	-	0.5	2.5	%
Temperature coefficient of output voltage	$T_c V_o$	$T_j=0$ to $125^\circ C$	-	± 0.01	-	%/ $^\circ C$
Ripple rejection	RR	-	45	55	-	dB
Dropout voltage	V_{i-o}	$V_{IN}=3V$, $I_o=10A$	-	-	0.5	V
* ³ ON-state voltage for control	$V_{C(ON)}$	-	2	-	-	V
ON-state current for control	$I_{C(ON)}$	$V_C=2.7V$	-	-	20	μA
OFF-state voltage for control	$V_{C(OFF)}$	-	-	-	0.8	V
OFF-state current for control	$I_{C(OFF)}$	$V_C=0.4V$	-	-	-40	mA
Quiescent current	I_q	$I_o=0A$	-	-	17	mA

³ In case of opening control terminal ④, output voltage turns on.**Fig.1 Test Circuit****Fig.2 Test Circuit for Ripple Rejection****Fig.3 Power Dissipation vs. Ambient Temperature**

Note) Oblique line portion: Overheat protection may operate in this area.


Fig.4 Overcurrent Protection Characteristics(Typical Value)

Fig.5 Output Voltage Adjustment Characteristics




Fig.7 Output Voltage vs. Input Voltage




Fig.9 Dropout Voltage vs. Junction Temperature




Fig.6 Output Voltage Deviation vs. Junction Temperature




Fig.8 Circuit Operating Current vs. Input Voltage




Fig.10 Ripple Rejection vs. Junction Temperature




Fig.11 Quiescent Current vs. Junction Temperature





Fig.12 Ripple Rejection vs. Input Ripple Frequency



■ Typical Application

