


PV6A6BA


N-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
40V	9m Ω @ $V_{GS} = 10V$	10.9A



SOP-8



ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ }^{\circ}\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	40	V
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current	$T_A = 25\text{ }^{\circ}\text{C}$	I_D	10.9	A
	$T_A = 70\text{ }^{\circ}\text{C}$		8.7	
Pulsed Drain Current ¹		I_{DM}	44	
Avalanche Current		I_{AS}	31	
Avalanche Energy	$L = 0.1\text{mH}$	E_{AS}	48	mJ
Power Dissipation	$T_A = 25\text{ }^{\circ}\text{C}$	P_D	2.2	W
	$T_A = 70\text{ }^{\circ}\text{C}$		1.4	
Junction & Storage Temperature Range		T_j, T_{stg}	-55 to 150	$^{\circ}\text{C}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient	$R_{\theta JA}$		55	$^{\circ}\text{C} / \text{W}$
Junction-to-Case	$R_{\theta JC}$		25	

¹Pulse width limited by maximum junction temperature.

²The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^{\circ}\text{C}$.

PV6A6BA

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	40			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1.3	1.7	2.3	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 32V, V_{GS} = 0V$			1	μA
		$V_{DS} = 30V, V_{GS} = 0V, T_J = 55\text{ }^{\circ}C$			10	
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 4.5V, I_D = 10A$		6.8	14	m Ω
		$V_{GS} = 10V, I_D = 10A$		6	9	
Forward Transconductance ¹	g_{fs}	$V_{DS} = 5V, I_D = 10A$		71		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 20V, f = 1MHz$		1685		pF
Output Capacitance	C_{oss}			227		
Reverse Transfer Capacitance	C_{rss}			129		
Gate Resistance	R_g	$V_{GS} = 0V, V_{DS} = 0V, f = 1MHz$		1.3		Ω
Total Gate Charge ²	$Q_g(V_{GS}=10V)$	$V_{DS} = 20V, I_D = 10A$		33		nC
	$Q_g(V_{GS}=4.5V)$			17		
Gate-Source Charge ²	Q_{gs}			4.4		
Gate-Drain Charge ²	Q_{gd}			8		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{DS} = 20V,$ $I_D \cong 10A, V_{GS} = 10V, R_{GEN} = 6\Omega$		18		nS
Rise Time ²	t_r			12		
Turn-Off Delay Time ²	$t_{d(off)}$			55		
Fall Time ²	t_f			11		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ($T_J = 25\text{ }^{\circ}C$)						
Continuous Current	I_S				1.6	A
Forward Voltage ¹	V_{SD}	$I_F = 10A, V_{GS} = 0V$			1.3	V
Diode Reverse Recovery Time	t_{rr}	$I_F = 10A, di/dt = 100A/\mu S$		13		nS
Diode Reverse Recovery Charge	Q_{rr}			2.5		nC


¹Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

²Independent of operating temperature.


PV6A6BA

N-Channel Enhancement Mode MOSFET


Output Characteristics




Transfer Characteristics




Gate charge Characteristics




Capacitance Characteristic



On-Resistance VS Gate-To-Source




On-Resistance VS Drain Current




PV6A6BA

N-Channel Enhancement Mode MOSFET


On-Resistance VS Temperature




Source-Drain Diode Forward Voltage




Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve




PV6A6BA

N-Channel Enhancement Mode MOSFET

Package Dimension

SOP-8 MECHANICAL DATA


Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	4.8	4.9	5.0	H	0.4	0.6	0.93
B	3.8	3.9	4.0	I	0.19	0.21	0.25
C	5.79	6.0	6.2	J	0.25	0.375	0.5
D	0.33	0.4	0.51	K	0°	3°	18°
E	1.25	1.27	1.29				
F	1.1	1.3	1.65				
G	0.05	0.15	0.25				




PV6A6BA

N-Channel Enhancement Mode MOSFET

A. Marking Information



B. Tape&Reel Information:2500pcs/Reel




PV6A6BA


N-Channel Enhancement Mode MOSFET

C. Lot No.&Date Code rule

1.Lot No.



2.Date Code



PV6A6BA

N-Channel Enhancement Mode MOSFET

D.Label rule

标签内容(Label content)



1	Label Size	30 * 90 mm
2	Font style	Times New Roman or Arial (或可区分英文"0"和数字"0", "G"和"Q"的字型即可)
3	U-NIKC	Height: 4 mm
4	Package	Height: 2 mm
5	Date	Height: 2 mm Shipping date: YYYY/MM/DD, ex. 2008/09/12
6	Device	Height: 3 mm (Max: 16 Digit)
7	Lot	Height: 3 mm (Max: 9 Digit) Sub lot
8	D/C	Height: 3 mm (Max: 7 Digit)
9	QTY	Height: 3 mm (Max: 6 Digit) Thousand mark is no needed
10	RoHS label	 long axis: 12 mm minor axis: 6 mm bottom color: White Font color: Black Font style: Arial
11	Halogen Free label	 Diameter: 10 mm bottom color: Green Font color: Black Font style: Arial
12	Scan information	Device / Lot / D/C / QTY , Insert " / " between every parts. for example: P3055LDG/G12345601/GGG2301/2000 DPI (Dots per inch): Over 300 dpi Code : Code 128 Height: 6 mm at least