

Power Accessories

Power Cords

	PWC-C13US-3B-183	PWC-C-13EU-3B-183 (CEE 7/7 to IEC C13)	PWC-C13UK-3B-183	PWC-C13JP-3B-183	PWC-C13AU-3B-183	PWC-C13CN-3B-183
Accessories Image						
Region	US	EU	UK	JP	AU	CN
Voltage	125 V	250 V	250 V	125 V	250 V	250 V
Thickness	6.3 ±0.2 mm	6.7 ±0.2 mm	6.7 ±0.2 mm	7.0 ±0.2 mm	6.7 ±0.2 mm	6.7 ±0.2 mm
Max. Current	10 A	10 A	10 A	7 A	10 A	10 A
Length	1830 ±30 mm	1830 ±30 mm	1830 ±30 mm	1830 ±30 mm	1830 ±30 mm	1830 ±30 mm
Related Products	CN2500 Series, NPort® 6600 Series, NPort® 5600 Series, PWR-12200-DT-S1					

Power Adaptors

	PWR-12050-WPEU-S1	PWR-12050-WPUK-S1	PWR-12050-WPAU-S1	PWR-12050-WPUSJP-S1	PWR-12150-CN-S2
Accessories Image					
Input Rating					
I/P	100-240 VAC 50-60Hz	100-240 VAC 50-60Hz	100-240 VAC 50-60Hz	100-240 VAC 50-60Hz	100-240 VAC 50-60Hz
Input Plug					
Plug type	EU	UK	AU	US/JP	CN
Output Rating					
O/P	0.5A @ 12VDC	0.5A @ 12VDC	0.5A @ 12VDC	0.5A @ 12VDC	1.5A @ 12VDC
Output Plug					
Connector type	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5
Outer Diameter	5.5 ±0.1mm	5.5 ±0.1mm	5.5 ±0.1mm	5.5 ±0.1mm	5.5 ±0.1mm
Inner Diameter	2.1 ±0.1mm	2.1 ±0.1mm	2.1 ±0.1mm	2.1 ±0.1mm	2.1 ±0.1mm
Physical Characteristics					
Dimensions	64 x 40.5 x 30mm	64 x 40.5 x 30mm	64 x 40.5 x 30mm	64 x 40.5 x 30mm	70 x 45 x 54mm
Weight	70g	70g	70g	70g	200g
Cord Length	1530 ±100 mm	1530 ±100 mm	1530 ±100 mm	1530 ±100 mm	1800 ±200 mm
Environmental Limits					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Regulatory Approvals					
Safety	CE/FCC/UL/GS/PSE/RCM	CE/FCC/UL/GS/PSE/RCM	CE/FCC/UL/GS/PSE/RCM	CE/FCC/UL/GS/PSE/RCM	CCC
Related Products					
Related Products	NPort® 5110A, NPort® 5130A, NPort® 5150A, NPort® 5210A, NPort® 5230A, NPort® 5250A, NPort® Z2150, NPort® Z3150				