


PZ0703ED


P-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
-30V	7.5mΩ @ $V_{GS} = -10V$	-70A



TO-252



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS	SYMBOL	LIMITS	UNITS
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^{2,3}	I_D	-70	A
		-44	
Pulsed Drain Current ¹	I_{DM}	-160	A
Avalanche Current	I_{AS}	-67	
Avalanche Energy	E_{AS}	227	mJ
Power Dissipation	P_D	78	W
		31	
Junction & Storage Temperature Range	T_j, T_{stg}	-55 to 150	°C
ESD Class	HBM	4	kV

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		1.6	°C / W

¹Pulse width limited by maximum junction temperature.

²Limited only by maximum temperature allowed.

³Package limitation current is -60A.

PZ0703ED P-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, Unless Otherwise Noted)







PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = -250\mu\text{A}$	-30			V
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = -250\mu\text{A}$	-1	-1.6	-3	
Gate-Body Leakage	I_{GSS}	$V_{\text{DS}} = 0\text{V}, V_{\text{GS}} = \pm 16\text{V}$			± 30	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = -24\text{V}, V_{\text{GS}} = 0\text{V}$			1	μA
		$V_{\text{DS}} = -20\text{V}, V_{\text{GS}} = 0\text{V}, T_J = 125^\circ\text{C}$			10	
On-State Drain Current ¹	$I_{\text{D}(\text{ON})}$	$V_{\text{DS}} = -5\text{V}, V_{\text{GS}} = -10\text{V}$	-160			A
Drain-Source On-State Resistance ¹	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}} = -4.5\text{V}, I_D = -20\text{A}$		7.4	12	$\text{m}\Omega$
		$V_{\text{GS}} = -10\text{V}, I_D = -20\text{A}$		5	7.5	
Forward Transconductance ¹	g_{fs}	$V_{\text{DS}} = -5\text{V}, I_D = -20\text{A}$		53		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = -15\text{V}, f = 1\text{MHz}$		5290		pF
Output Capacitance	C_{oss}			995		
Reverse Transfer Capacitance	C_{rss}			824		
Gate Resistance	R_g	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 0\text{V}, f = 1\text{MHz}$		2		Ω
Total Gate Charge ²	Q_g	$V_{\text{DS}} = -15\text{V}, V_{\text{GS}} = -0\text{V}, I_D = -20\text{A}$		123		nC
Gate-Source Charge ²	Q_{gs}			16		
Gate-Drain Charge ²	Q_{gd}			29		
Turn-On Delay Time ²	$t_{\text{d}(\text{on})}$	$V_{\text{DS}} = -15\text{V}, I_D \approx -20\text{A}, V_{\text{GS}} = -10\text{V}, R_{\text{GS}} = 6\Omega$		32		nS
Rise Time ²	t_r			24		
Turn-Off Delay Time ²	$t_{\text{d}(\text{off})}$			90		
Fall Time ²	t_f			44		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS ($T_J = 25^\circ\text{C}$)						
Continuous Current	I_S				-70	A
Forward Voltage ¹	V_{SD}	$I_F = -10\text{A}, V_{\text{GS}} = 0\text{V}$			-1.3	V
Reverse Recovery Time	t_{rr}	$I_F = -20\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$		31		nS
Reverse Recovery Charge	Q_{rr}			16		nC

¹Pulse test : Pulse Width $\leq 300\ \mu\text{sec}$, Duty Cycle $\leq 2\%$.






²Independent of operating temperature.

³Package limitation current is -60A.

PZ0703ED P-Channel Enhancement Mode MOSFET



PZ0703ED P-Channel Enhancement Mode MOSFET




PZ0703ED

P-Channel Enhancement Mode MOSFET

Package Dimension

TO-252 (DPAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	8.9	10	10.41	J	4.8		5.64
B	2.1	2.2	2.4	K	0.15		1.1
C	0.4	0.5	0.61	L	0.4	0.76	0.89
D	0.82	1.2	1.5	M	4.2	4.58	5
E	0.4	0.5	0.61	S	4.9	5.1	5.3
F	0		0.2	T	4.6	4.75	5.44
G	5.3	6.1	6.3	U	1.4		1.78
H	0.9		1.7	V	0.55	1.25	1.7
I	6.3	6.5	6.8				



*因为各家封装模具不同而外观略有差异，不影响电性及Layout。