


## Features

- Low voltage and low current
- Complementary to PZT3904
- General purpose amplifier and switch application



**SOT-223**

1. BASE
2. COLLECTOR
3. EMITTER

## Absolute Maximum Ratings (T<sub>A</sub> = 25 °C unless otherwise noted)





Parameter	Symbol	Value	Unit
Collector-Base Voltage	V <sub>CB0</sub>	-40	V
Collector-Emitter Voltage	V <sub>CEO</sub>	-40	V
Emitter-Base Voltage	V <sub>EBO</sub>	-5	V
Collector Current	I <sub>C</sub>	-200	mA
Collector Power Dissipation	P <sub>C</sub>	1	W
Thermal Resistance from Junction to Ambient	R <sub>θJA</sub>	125	°C/W
Junction Temperature	T <sub>J</sub>	-55 to +150	°C
Storage Temperature	T <sub>STG</sub>	-55 to +150	°C

## Electrical Characteristics (T<sub>A</sub> = 25 °C unless otherwise noted)





Parameter	Symbol	Test Conditions	Min	Max	Unit
Collector-Base Breakdown Voltage	V <sub>(BR)CBO</sub> *	I <sub>C</sub> =-0.01mA, I <sub>E</sub> =0	-40	-	V
Collector-Emitter Breakdown Voltage	V <sub>(BR)CEO</sub> *	I <sub>C</sub> =-1mA, I <sub>B</sub> =0	-40	-	V
Emitter-Base Breakdown Voltage	V <sub>(BR)EBO</sub> *	I <sub>E</sub> =0.01mA, I <sub>C</sub> =0	-5	-	V
Collector Cut-Off Current	I <sub>CB0</sub>	V <sub>CB</sub> =-30V, I <sub>E</sub> =0	-	-50	nA
Collector Cut-Off Current	I <sub>CEO</sub>	V <sub>CE</sub> =-30V, I <sub>C</sub> =0	-	-500	nA
Collector Cut-Off Current	I <sub>CEx</sub>	V <sub>CE</sub> =-30V, V <sub>BE(off)</sub> =-3V	-	-50	nA
DC Current Gain	h <sub>FE(1)</sub> *	V <sub>CE</sub> =-1V, I <sub>C</sub> =-0.1mA	60	-	-
	h <sub>FE(2)</sub>	V <sub>CE</sub> =-1V, I <sub>C</sub> =-1mA	80	-	-
	h <sub>FE(3)</sub>	V <sub>CE</sub> =-1V, I <sub>C</sub> =-10mA	100	300	-
	h <sub>FE(4)</sub>	V <sub>CE</sub> =-1V, I <sub>C</sub> =-50mA	60	-	-
Collector-Emitter Saturation Voltage	V <sub>CE(sat)</sub> *	I <sub>C</sub> =-10mA, I <sub>B</sub> =-1mA	-	-0.25	V
		I <sub>C</sub> =-50mA, I <sub>B</sub> =-5mA	-	-0.4	V
Base-Emitter Saturation Voltage	V <sub>BE(sat)</sub> *	I <sub>C</sub> =-10mA, I <sub>B</sub> =-1mA	-0.65	-0.85	V
		I <sub>C</sub> =-50mA, I <sub>B</sub> =-5mA	-	-0.95	V
Transition Frequency	f <sub>T</sub>	V <sub>CE</sub> =-20V, I <sub>C</sub> =-10mA, f=100MHz	250	-	MHz
Collector Output Capacitance	C <sub>ob</sub>	V <sub>CB</sub> =-5V, I <sub>E</sub> =0, f=1MHz	-	4.5	pF
Emitter Input Capacitance	C <sub>ib</sub>	V <sub>BE</sub> =-0.5V, I <sub>C</sub> =0, f=1MHz	-	10	pF
Delay Time	t <sub>d</sub>	V <sub>CC</sub> =-3V, V <sub>BE(off)</sub> =-0.5V, I <sub>C</sub> =-10mA, I <sub>B1</sub> =-I <sub>B2</sub> =-1mA	-	35	nS
Rise Time	t <sub>r</sub>		-	35	
Storage Time	t <sub>s</sub>	V <sub>CC</sub> =-3V, I <sub>C</sub> =-10mA, I <sub>B1</sub> =-I <sub>B2</sub> =-1mA	-	225	nS
Fall Time	t <sub>f</sub>		-	75	

\*Pulse test: pulse width ≤300μS, duty cycles ≤ 2.0%.


**Typical Characteristic Curves**



**Typical Characteristic Curves**




**Package Outline Dimensions** SOT-223



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	—	1.800	—	0.071
A1	0.020	0.100	0.001	0.004
A2	1.500	1.700	0.059	0.067
b	0.660	0.840	0.026	0.033
b1	2.900	3.100	0.114	0.122
c	0.230	0.350	0.009	0.014
D	6.300	6.700	0.248	0.264
E	6.700	7.300	0.264	0.287
E1	3.300	3.700	0.130	0.146
e	2.300(BSC)		0.091(BSC)	
L	0.750	—	0.030	—
theta	0°	10°	0°	10°

**Suggested Pad Layout**



**Note:**

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.050$ mm.
3. The pad layout is for reference purposes only.

**Ordering Information**

Device	Package	Marking	Quantity	HSF Status
PZT3906	SOT-223	ZT3906	1000pcs / Reel	RoHS Compliant