

**For Astro-Physics and Other Ultra-Violet Radiation Detection  
13mm (1/2 Inch) Diameter, Head-on, 10-Stage, Cs-Te Photocathode**

## GENERAL

Parameter		Description/Value	Unit
Spectral Response		115 to 320	nm
Wavelength of Maximum Response		240	nm
Wavelength of Maximum Quantum Efficiency		200	nm
Photocathode	Material	Cs-Te	—
	Minimum Useful Size	6	mm dia.
Window Material		Mg-F <sub>2</sub>	—
Dynode	Structure	Linear focused	—
	Number of Stages	10	—
Direct Interelectrode Capacitances	Anode to Last Dynode	1.0	pF
	Anode to All Other Electrodes	2.0	pF
Base (temporary)		12-pin base (JEDEC No. B12-43)	—
Socket		E678-12A (supplied)	—

## MAXIMUM RATINGS (Absolute Maximum Values)

Parameter		Value	Unit
Supply Voltage	Between Anode and Cathode	1250	Vdc
	Between Anode and Last Dynode	250	Vdc
Average Anode Current		0.01	mA
Ambient Temperature		-80 to +50	°C

## CHARACTERISTICS (at 25°C)

Parameter	Min.	Typ.	Max.	Unit
Cathode Radiant Sensitivity at 254nm	—	28	—	mA/W
Anode Radiant Sensitivity at 254nm	—	$1.4 \times 10^4$	—	A/W
Quantum Efficiency at 200nm	—	17	—	%
Gain	—	$5.0 \times 10^5$	—	—
Anode Dark Current (after 30min. storage in darkness)	—	0.3	1	nA

## VOLTAGE DISTRIBUTION RATIO AND SUPPLY VOLTAGE

Electrodes	K	Dy1	Dy2	Dy3	Dy4	Dy5	Dy6	Dy7	Dy8	Dy9	Dy10	P
Ratio	1	1	1	1	1	1	1	1	1	1	1	1

Supply Voltage: 1000Vdc, K: Cathode, Dy: Dynode, P: Anode

# PHOTOMULTIPLIER TUBE R1080

Figure 1: Typical Spectral Response




Figure 2: Typical Gain Characteristics





Figure 3: Dimensional Outline and Basing Diagram (Unit: mm)



# HAMAMATSU

HAMAMATSU PHOTONICS K.K., Electron Tube Center

314-5, Shimokanzo, Toyooka-village, Iwata-gun, Shizuoka-ken, 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P. O. Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: Lough Point, 2 Gladbeck Way, Windmill Hill, Enfield, Middlesex EN2 7JA, United Kingdom, Telephone: (44)181-367-3560, Fax: (44)181-367-6384

North Europe: Hamamatsu Photonics Norden AB: Färögatan 7, S-164-40 Kista Sweden, Telephone: (46)8-703-29-50, Fax: (46)8-750-58-95

Italy: Hamamatsu Photonics Italia: S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39)02-935 81 733, Fax: (39)02-935 81 741

TPMH1212E01  
AUG. 1998