


Features

- High voltage
- High current capability
- Low leakage current
- High surge capability
- Low cost

Mechanical Data

- Case : DO-41 Molded plastic
- Epoxy : UL94V-O rate flame retardant
- Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- Polarity : Color band denotes cathode end
- Mounting position : Any
- Weight : 0.339 gram



DO-41		
Dim	Min	Max
A	25.40	—
B	4.06	5.21
C	0.71	0.864
D	2.00	2.72
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	R1500	R2000	R3000	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	1500	2000	3000	V
RMS Reverse Voltage	$V_{R(RMS)}$	1050	1400	2100	V
Average Rectified Output Current (Note 1) @ $T_L = 55^\circ\text{C}$	I_O	500		200	mA
Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30		25	A
Forward Voltage @ $I_F = 500\text{mA}$ @ $I_F = 200\text{mA}$	V_{FM}	2.0 —		— 3.0	V
Peak Reverse Leakage Current at Rated DC Blocking Voltage	I_{RM}	5.0			μA
Typical Junction Capacitance (Note 2)	C_j	8.0		7.0	pF
Typical Thermal Resistance Junction to Ambient	$R_{\theta JA}$	70		117	K/W
Operating and Storage Temperature Range	T_j, T_{STG}	-65 to +125			$^\circ\text{C}$

Notes: 1. Valid provided that leads are kept at ambient temperature at a distance of 9.5mm from the case.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

