

**R3000GP
 THRU
 R6000GP**

**200 Milliamp
 High Voltage
 Silicon Rectifier
 3000 to 6000 Volts**

Features

- Halogen free available upon request by adding suffix "-HF"
- High Voltage
- Low Leakage
- Low Forward Voltage Drop
- Glass passivated chip
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C


Microsemi Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
R3000GP	R3000GP	3000V	2100V	3000V
R4000GP	R4000GP	4000V	2800V	4000V
R5000GP	R5000GP	5000V	3500V	5000V
R6000GP	R6000GP	6000V	4200V	6000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	200mA	$T_A = 60^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	15A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V_F	2.3V	$I_{FM} = 0.5A;$ $T_A = 50^\circ\text{C}$
R3000GP		3.5V	
R4000GP R5000GP~R6000GP		5.0V	
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	5.0µA	$T_A = 25^\circ\text{C}$
Maximum reverse recovery time	T_{rr}	>1200	$I_F=0.5A, I_R=1.0A,$ $I_{RR}=0.25A(\text{RG1 circuit})$

Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

DO-15



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.230	.300	5.80	7.60	
B	.104	.140	2.60	3.60	
C	.026	.034	.70	.90	
D	1.000	---	25.40	---	

Ratings and Characteristics Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 - Typical Forward Characteristics





Fig.4 - Typical High Temperature Reverse Leakage





Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 4Kpcs/Reel
Part Number-AP	Ammo Packing: 3Kpcs/Ammo Box
Part Number-BP	Bulk: 25Kpcs/Carton

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . Micro Commercial Components Corp . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp . and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.