


RTD FOR AUTOCLAVE

For continuous use, Teflon Jacketed Cable

RAC251



RTD

RTD with Mounting Bush



Pt100, 3-wire
Simplex, Duplex



Range
0 to 150°C
(32 to 302°F)




Accuracy
Class AA (1/3 DIN)



Leakproof Assembly



Sheath Material
SS316L (1.14404)



Cable Length
5/10 Meters

RTD FOR AUTOCLAVE

For continuous use, Teflon Jacketed Cable

RAC251

ABOUT RAC251

RAC251 is specifically designed to withstand the high pressure & temperature of the continuous sterilization process in autoclaves. It is capable of measuring temperatures upto 150°C (302°F).

RAC251 has a completely sealed construction. As a result, the entire sensor assembly, including the probe and the cable extending from the RTD, can be completely submerged in water without affecting accuracy or long-term stability.

SPECIFICATIONS

| | |
|--------------------|----------------------------|
| Type | Pt100, 3-wire to IEC 60751 |
| Accuracy | Class AA (1/3 DIN) |
| No. of elements | Simplex/Duplex |
| Range | 0 to 150°C (32 to 302°F) |
| Sheath material | SS316L (1.4404) |
| Sheath diameter | 6 mm |
| Sheath length (SL) | 50 mm (see Fig1, Fig2) |
| Cable type | Teflon insulated cable |
| Cable length (CL) | 5/10 meters |
| Mounting bush | Included |

DIMENSIONS mm

Fig 1 : Simplex







Fig 2 : Duplex



CIRCUIT DIAGRAM




3-WIRE, SIMPLEX




3-WIRE, DUPLEX


CABLE TERMINATION TYPES



BARE LEADS



PIN TYPE LUGS



FORK TYPE LUGS

RTD FOR AUTOCLAVE

For continuous use, Teflon Jacketed Cable

RAC251

KEY FEATURES

- Specifically designed to withstand high pressure & temperature of the continuous sterilization process in autoclaves
- Measuring range : 0 to 150°C (32 to 302°F)
- Completely sealed construction
- SS316L (1.4404) body and wetted parts
- Accuracy : Class AA (1/3 DIN)

ORDERING INFORMATION

| CODE | SPECIFICATIONS | 1 | 2 | 3 | 4 | 5 |
|--------|---------------------------|---|----|----|----|----|
| RAC251 | | | | | | |
| 1 | No. of Elements | | | | | |
| | Simplex | S | | | | |
| | Duplex | D | | | | |
| 2 | Cable Length (CL) | | | | | |
| | 5 m | | 05 | | | |
| | 10 m | | 10 | | | |
| 3 | Cable Termination | | | | | |
| | Bare leads | | | BR | | |
| | Fork type lugs | | | FR | | |
| | Pin type lugs | | | PN | | |
| 4 | Future Parameter A | | | | | |
| | For future use | | | | FA | |
| 5 | Future Parameter B | | | | | FB |
| | For future use | | | | | |

CODE - 1 - 2 - 3 - 4 - 5

Order Code Format : XXXX-X-X-XX-FA-FB

Example

RAC251, Pt100, 3-wire, Duplex, Class A accuracy , 6 x 50 mm, SS316L, 5 m cable length, Pin type lugs
RAC251-D-5-PN-FA-FB

**RTD FOR
AUTOCLAVE**

ENQUIRIES

Email : sensors@radix.co.in
Call : + 91 93214 15829
Website : www.radix.co.in

CAT#836(R)1/A