



# RB500V-40

## SURFACE MOUNT SCHOTTKY DIODES

**VOLTAGE** 45 Volts    **CURRENT** 100 mA



**SOD-323**    Unit: inch (mm)

### FEATURES

- Extremely Fast Switching Speed
- Very Low  $V_F$  : 0.37V (Typ) at  $I_F = 10\text{mA}$
- Surface mount package ideally suited for automatic insertion
- In compliance with EU RoHS 2002/95/EC directives

### MECHANICAL DATA

- Case: SOD-323, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Appox Weight : 0.0041 gram
- Marking : 500
- Polarity : Color band cathode



### ABSOLUTE RATINGS

Parameter	Symbol	Value	Units
Maximum Peak Reverse Voltage	$V_{RRM}$	45	V
Reverse DC Voltage	$V_R$	30	V
Maximum Forward Current	$I_{F(AV)}$	0.1	A
Maximum Forward Peak Current (60Hz-1cycle)	$I_{FSM}$	1.0	A
Power Dissipation <sup>(1)</sup>	$P_{TOT}$	0.2	W
Peak Forward Surge Current at t=8.3ms	$I_{FSM}$	500	mA
Junction Temperature	$T_J$	-55 to + 125	°C
Storage Temperature	$T_{STG}$	-55 to + 125	°C

### THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Units
Thermal Resistance, Junction to Ambient <sup>(1)</sup>	$R_{\theta JA}$	300	°C/W

1. FR-4 Board = 70 x 60 x 1 mm. Minmum Pad Layout






# RB500V-40

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted )

Parameter	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Leakage Current	$I_R$	$V_R=10\text{V}$	-	-	0.5	$\mu\text{A}$
Forward Voltage	$V_F$	$I_F=10\text{mA}$	-	-	0.45	V
Total Capacitance	$C_T$	$V_R=10\text{V}, F=1\text{MHz}$	-	6	-	pF


## ELECTRICAL CHARACTERISTICS CURVE





# RB500V-40

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information
  - T/R - 12K per 13" plastic Reel
  - T/R - 5K per 7" plastic Reel

## LEGAL STATEMENT

### Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.