


RB521C30
Schottky Barrier Diode
<http://www.willsemi.com>
Features

- 100mA Average rectified forward current
- Low forward voltage
- Low leakage current
- Small package SOD-923


SOD-923

Circuit
Applications

- Low Current rectification


Marking
Absolute maximum ratings

Parameter	Symbol	Value	Unit
Reverse voltage (repetitive peak)	V_{RM}	30	V
Reverse voltage (DC)	V_R	30	V
Average rectified forward current	I_O	100	mA
Peak forward surge current (8.3ms single sine pluse)	I_{FSM}	0.5	A
Junction temperature	T_J	150	°C
Operating temperature	T_{opr}	-40 ~ 125	°C
Storage temperature	T_{stg}	-40 ~ 150	°C






Electronics characteristics ($T_A=25^\circ\text{C}$)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse Voltage	V_R	$I_R=100\mu\text{A}$	30			
Forward Voltage	V_F	$I_F=10\text{mA}$			0.35	V
		$I_F=100\text{mA}$			0.47	V
Reverse current	I_R	$V_R=10\text{V}$			6	μA
		$V_R=30\text{V}$			15	μA
Junction capacitance	C_J	$V_R=5\text{V}, F=1\text{MHz}$		21		pF
Thermal Resistance	$R_{\theta(JA)}$	Junction to Ambient		650		K/W

Order Informations


Device	Package	Marking	Shipping
RB521C30-2/TR	SOD-923	1* ⁽¹⁾	10000/Reel&Tape

Note 1: * = Month code(A~Z); 1 = Device code;

Typical characteristics (Ta=25°C, unless otherwise noted)

Forward voltage vs. Forward current

Reverse current vs. Reverse voltage

Forward current derating curve

Junction capacitance vs. Reverse voltage

IFSM-T Characteristics

Package outline dimensions
SOD-923


Symbol	Dimensions in millimeter		
	Min.	Typ.	Max.
A	0.36	0.40	0.45
b	0.15	0.20	0.30
C	0.05	0.12	0.20
D	0.70	0.80	0.90
E	0.55	0.60	0.65
H_E	0.90	1.00	1.10
L	0.05	0.10	0.15


Land Pattern Recommendation