



RB521G-30

SCHOTTKY BARRIER DIODE

FEATURES

- Rectifying small power
- Ultra small mold type
- Low V_F
- High reliability
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

Case: SOD-723, Plastic

Terminals: Solderable per MIL-STD-750, Method 2026


Polarity: See Diagram Below

Approx. Weight : 0.00077 gram

Marking : BN

SOD-723

Unit: inch (mm)



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

PARAMETER	SYMBOL	LIMITS	UNITS
Reverse Voltage (DC)	V_R	30	V
Average Rectified Forward Current	I_O	100	mA
Forward Current Surge Peak (60Hz . 1cyc)	I_{FSM}	500	mA
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-40 to 125	$^\circ\text{C}$







ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Forward Voltage	V_F	$I_F = 10\text{mA}$	-	-	0.35	V
Reverse Current	I_R	$V_R = 10\text{V}$	-	-	10	μA



RB521G-30

●Electrical characteristic curves (Ta=25°C)






RB521G-30

MOUNTING PAD LAYOUT

SOD-723

Unit: inch (mm)



ORDER INFORMATION

- Packing information

T/R - 8K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2007

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.