

RB751S-40

SILICON EPITAXIAL PLANAR SCHOTTKY BARRIER DIODE


for high speed switching and detection applications

Features

- Small surface mounting type
- Low reverse current and low forward voltage
- High reliability

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




Absolute Maximum Ratings ($T_a = 25\text{ }^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RM}	40	V
Reverse Voltage	V_R	30	V
Mean Rectifying Current	I_O	30	mA
Peak Forward Surge Current (60 Hz, 1 Cycle)	I_{FSM}	200	mA
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature Range	T_s	- 40 to + 125	$^\circ\text{C}$

Characteristics at $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Typ.	Max.	Unit
Forward Voltage at $I_F = 1\text{ mA}$	V_F	-	0.37	V
Reverse Current at $V_R = 30\text{ V}$	I_R	-	0.5	μA
Capacitance Between Terminals at $V_R = 1\text{ V}$, $f = 1\text{ MHz}$	C_T	2	-	pF

Note: ESD sensitive product handling required.




SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)




Dated : 23/11/2006


RB751S-40




FORWARD VOLTAGE: VF(mV)
VF-IF CHARACTERISTICS
VF分布




REVERSE VOLTAGE: VR(V)
VR-IR CHARACTERISTICS




REVERSE VOLTAGE: VR(V)
VR-Ct CHARACTERISTICS




VF DISPERSION MAP




IR DISPERSION MAP




Ct DISPERSION MAP




IFSM DISPERSION MAP




NUMBER OF CYCLES
IFSM-CYCLE CHARACTERISTICS




TIME: t(ms)
IFSM-t CHARACTERISTICS




TIME: t(s)
Rth-t CHARACTERISTICS




AVERAGE RECTIFIED FORWARD CURRENT: Io(A)
Io-Pf CHARACTERISTICS




REVERSE VOLTAGE: VR(V)
VR-Pk CHARACTERISTICS



AMBIENT TEMPERATURE: Ta(°C)
Derating Curve (Io-Ta)



CASE TEMPERATURE: Tc(°C)
Derating Curve (Io-Tc)



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949:2002 Certificate No. 05103
ISO 14001:2004 Certificate No. 7116
ISO 9001:2000 Certificate No. 0506098


Dated : 23/11/2006

RB751S-40


PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-523



UNIT	A	b _p	C	D	E	H _E	V	∠
mm	0.70 0.60	0.4 0.3	0.135 0.127	1.25 1.15	0.85 0.75	1.7 1.5	0.1	5°



SEMTECH ELECTRONICS LTD.
 (Subsidiary of Sino-Tech International Holdings Limited, a company
 listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002 Certificate No. 05103
 ISO 14001:2004 Certificate No. 7116
 ISO 9001:2000 Certificate No. 0506098

Dated : 23/11/2006