


RC2000C-T Series

Common Mode Reactor

Inquiry

Single phase 2 lines/Width type



Application

Noise suppression for Switching power supply/Inverter

Specifications

RC2000C-TA Series								
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	Dimension [mm]			
					D	W	L	A
RC2003C-TA	250	3	1	70	25	20	15	10
RC2005C-TA		5	1	50	25	20	15	10
RC2010C-TA		10	1	30	37	25	15	22
RC2015C-TA		15	1	20	37	25	15	22
RC2020C-TA		20	1	10	53	35	15	26
RC2030C-TA		30	1	7	60	37	15	40
RC2000C-TB Series								
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	Dimension [mm]			
					D	W	L	A
RC2003C-TB	250	3	2	80	25	20	15	10
RC2005C-TB		5	2	70	37	25	15	22
RC2010C-TB		10	2	40	37	25	15	22
RC2015C-TB		15	2	12	53	35	15	26
RC2020C-TB		20	2	10	62	35	15	40
TC2000C-TC Series								
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	Dimension [mm]			
					D	W	L	A
TC2003C-TC	250	3	3	90	25	20	15	10
TC2005C-TC		5	3	70	37	25	15	22
TC2010C-TC		10	3	30	53	35	15	26
TC2015C-TC		15	3	15	53	35	15	26
RD2000C-TD								

Series					Dimension [mm]			
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	D	W	L	A
					RD2005C-TD	250	5	5
RD2010C-TD	10	5	20	50	30		15	26

Fig

