

RDHA701CD10A2NX

PD-97578C

Radiation Hardened Dual Solid State Relay 100V, 1.0A, R5 Technology

Features

- Total dose capability to 100kRads(Si)
- Optically coupled
- 1000VDC input-to-output, channel-to-channel, and pin-to-case isolation
- Hermetically sealed
- Ceramic package

Typical applications

- Solar array management, heater controls, bus switching, ground power isolation, generic load switching

Product validation

Screened to MIL-PRF-38534, and meets Qualification Conformance Inspection per MIL-PRF-38534 for Class K product

Description

The RDHA701CD10A2NX is a radiation hardened dual Solid State Relay in a hermetic package. It is configured as dual single pole single throw (SPST) normally open relay. This device is characterized for 100KRad (Si) total ionizing dose. The output MOSFET utilizes IR HiRel R5 technology.

Ordering Information

Table 1 **Ordering options**

Part number	Package	Screening Level	TID Level
RDHA701CD10A2NX	8 Pin Ceramic	Class K	100krad(Si)

Product Summary

- **Part number:** RDHA701CD10A2NX
- **Radiation level:** 100 kRads (Si)
- **Configuration:** Dual DC
- **Voltage:** 100V
- **I_D:** 1.0A



Table of contents

Table of contents

Features	1
Typical applications	1
Product validation	1
Description	1
Ordering Information	1
Table of contents	2
1 Absolute Maximum Ratings	3
2 Device Characteristics	4
2.1 Electrical Characteristics (Per Channel)	4
3 Test Circuits	5
4 Package Outline	6
5 Part Numbering Nomenclature	7
Revision history	8

Absolute Maximum Ratings

1 Absolute Maximum Ratings

Table 2 Absolute Maximum Ratings @ $T_j = 25^\circ\text{C}$ (unless otherwise specified)

Parameter	Symbol	Value	Unit
Output Withstand Voltage	$V_{O(OFF)}$	100	V
Output Current ¹	I_O	1.0	A
Input Forward Current	I_F	40	mA
Peak Input Forward Current ($t \leq 1.0\text{ms}$)	I_{Fpk}	100	
Peak Input Reverse Voltage ($t \leq 1.0\text{ms}$)	V_R	5.0	V
Power Dissipation	P_{DISS}	1.0	W
Operating Temperature Range	T_J	-55 to +125	°C
Storage Temperature Range	T_S	-65 to +150	
Lead Temperature (soldering $\leq 10\text{sec}$)	T_L	300	
Weight		0.8 (Typical)	g

¹ While the SSR design meets the design, requirements specified in MIL-PRF-38534, the end user is responsible for product derating as applicable for the application.

Device Characteristics

2 Device Characteristics

2.1 Electrical Characteristics (Per Channel)

Table 3 Electrical Characteristics per Channel @ $-55^{\circ}\text{C} \leq T_c \leq +125^{\circ}\text{C}$ (Unless Otherwise Specified) ¹

Parameter	Group A Subgroups	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Output On-Resistance	1	$I_F = 10\text{mA}$, $I_O = 1.0\text{A}$	$R_{DS(ON)}$	—	0.25	0.40	Ω
	2			—	0.39	0.80	
Output Leakage Current	1	$I_F = 0$, $V_{OUT} = 100\text{V}$	I_O	—	—	10	μA
	2			—	—	25	
Input Forward Voltage	1, 2, 3	$I_F = 10\text{mA}$	V_F	1.0	—	1.85	V
Input-to-Output Leakage Current	1	$V_{I-O} = 1000\text{Vdc}$, $d_{well} = 5\text{s}$	I_{I-O}	—	—	1.0	μA
Channel-to-Channel Leakage Current			I_{CH-CH}				
Pin-to-Case Leakage Current			I_{CASE}				
Turn-On Time ^{3 4 5 6}	9, 10, 11	$I_F = 0$ to 10mA , $V_{BUS} = 28\text{V}$, $I_O = 1.0\text{A}$, Duty Cycle $\leq 1.0\%$	t_{on}	—	—	4.0	ms
Turn-Off Time ^{2 3 4 5}	9, 10, 11	$I_F = 10\text{mA}$ to 0 , $V_{BUS} = 28\text{V}$, $I_O = 1.0\text{A}$, Duty Cycle $\leq 1.0\%$	t_{off}	—	—	2.0	
Output Capacitance ⁷		$I_F = 0$, $V = +25\text{V}$, $f = 1\text{MHz}$, $T_C = 25^{\circ}\text{C}$	C_{OSS}	—	110	—	μF
Thermal Resistance ⁶		Per Channel	R_{THJC}	—	—	15	$^{\circ}\text{C/W}$
MTBF		MIL-HDBK-217F, SF@ $T_C = 25^{\circ}\text{C}$		22.7	—	—	MHrs

¹ IR HiRel does not currently have a DLA Certified Radiation Hardness Assurance Program.

² Turn-On Time (t_{on}) includes the turn-on delay and rise time; Turn-Off Time (t_{off}) includes the turn-off delay and fall time.

³ Reference Fig. 2 for Switching Test Circuits and Fig. 3 for Switching Test Wave Form.




⁴ Optically coupled Solid State Relays (SSRs) have relatively slow turn on and turn off times. Care must be taken to ensure that transient currents do not cause a violation of SOA. If transient conditions are present, IR HiRel recommends a complete simulation to be performed by the end user to ensure compliance with SOA requirements as specified in the IRHQ57110 datasheet.

⁵ Rise and fall time are controlled internally.

⁶ Specification is guaranteed by design.

Test Circuits

3 Test Circuits




RDHA701CD10A2NX

Radiation Hardened Dual Solid State Relay

Package Outline

4 Package Outline

Note: For the most updated package outline, please see the website: [Package \(8 Pin Ceramic\)](#)




RDHA701CD10A2NX

Radiation Hardened Dual Solid State Relay

Part Numbering Nomenclature

5 Part Numbering Nomenclature



Revision history

Document version	Date of release	Description of changes
	10/19/2010	Final datasheet
Rev A	10/26/2010	Updated Package Picture with IR logo –page1
Rev C	05/25/2012	Updated per ECN-1120-00458
Rev C	09/02/2021	Updated per ECN-1120-8644

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2021-09-02

Published by

**International Rectifier HiRel Products,
Inc.**

**An Infineon Technologies company
El Segundo, California 90245 USA**

**© 2023 Infineon Technologies AG.
All Rights Reserved.**

**Do you have a question about this
document?**

Email: erratum@infineon.com

Document reference

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

WARNINGS

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest International Rectifier HiRel Products, Inc., or Infineon Technologies company, office.

International Rectifier HiRel Components may only be used in life-support devices or systems with the expressed written approval of International Rectifier HiRel Products, Inc., an Infineon Technologies company, if failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety and effectiveness of that device or system.

Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.