



For a variation of the RF3 series please contact our Sales / Marketing Department for further information.

Specifications		RF3A	RF3D	RF3C
Model Number		RF3A	RF3D	RF3C
Test Voltage (kV Peak) 60 Hz		10	10	10
Rated Operating Voltage (kV Peak)				
dc or 60 Hz		8	8	8
2.5 MHz		7	7	7
16 MHz		6	6	6
32 MHz		5	5	5
Continuous Current, Carry (A, RMS)				
dc or 60 Hz		30	30	30
2.5 MHz		25	25	25
16 MHz		15	15	15
32 MHz		10	10	10
Contact Capacitance (pF)				
Between Open Contacts		4.0	4.0	4.0
Open Contacts to Ground		2.5	2.5	2.5
Contact Resistance (mΩ)		15	15	15
Operate Time (ms, Max.)		18	18	18
Release Time (ms, Max.)		18	N/A	N/A
Pull-in Voltage @ 25° C, 26.5 Vdc Coil		95	1E	1E
Dropout Voltage @ -55 to 125° C, 26.5 Vdc Coil		1-10	N/A	N/A
Coil Resistance (L± 10%) 26.5 Vdc Coil		156	12	12
Shock, 1/2 Size 11 ms. (Peak g's)		80	50	50
Vibration, Peak g's				
55-500 Hz		10	10	10
500-1000 Hz		10	-	-
1000-2000 Hz		10	-	-
Expected Mechanical Life Cycles (X10 ⁶)		1	1	1
Weight, Coils (Grams) Max.		1 (28)	2 (57)	2 (57)