



**SPECIFICATIONS**

Model Number	RF69
Test Voltage (kV Peak) 60 Hz	24
Rated Operating Voltage (kV Peak)	
DC or 60 Hz	12
2.5 MHz	*
16 MHz	*
32 MHz	*
Continuous Current, Carry (Amps, RMS)	
DC or 60 Hz	15
2.5 MHz	*
16 MHz	*
32 MHz	*
Contact Capacitance (pF)	
Between Open Contacts	2.5
Open Contacts to Ground	2.5
Contact Resistance (mΩ)	40
Operate Time (ms. Max.)	15
Release Time (ms. Max.)	15
Pull-in Voltage @ 25° C	
26.5 VDC Coil	18
Dropout Voltage @ -55 to 125° C	
26.5 VDC Coil	1-10
Coil Resistance (Ohms ± 10%)	
26.5 VDC Coil	290
Shock, 1/2 Sine 11 ms. (Peak g's)	30
Vibration, Peak g's 55-500 Hz	.06
Expected Mechanical Life Cycles (X10 <sup>6</sup> )	2
Weight, Ounces (Grams) Max.	3 (85)

\* Please contact our Sales / Marketing Dept.



- **RF69-26S**  
N/C, 12 kV, 15 Amp continuous current, ground isolated. Fly lead, high voltage connections.

