

GLASS PASSIVATED SILICON RECTIFIER

VOLTAGE RANGE 50 to 800 Volts CURRENT 16 Amperes

FEATURES


- * Low power loss, high efficiency
- * Low forward voltage drop
- * Low thermal resistance
- * High current capability
- * High surge capability
- * High reliability

MECHANICAL DATA

- * Case: TO-220 molded plastic
- * Epoxy: Device has UL flammability classification 94V-0
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 2.24 grams
- * Polarity: As marked

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	RL1601C	RL1602C	RL1603C	RL1604C	RL1605C	RL1606C	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	Volts
Maximum RMS Voltage	VRMS	35	70	140	280	420	560	Volts
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	Volts
Maximum Average Forward Rectified Current Tc = 100°C (Note 1)	Io	16.0						Amps
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	IFSM	150						Amps
Typical Current Square Time	I ² T	93.4						A ² S
Typical Thermal Resistance	RθJC	3.0						°C/W
Typical Junction Capacitance (Note 2)	CJ	40						pF
Operating and Storage Temperature Range	TJ, TSTG	-55 to + 150						°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	RL1601C	RL1602C	RL1603C	RL1604C	RL1605C	RL1606C	UNITS
Maximum Instantaneous Forward Voltage at 8.0A DC	VF	1.0						Volts
Maximum DC Reverse Current	IR	2						uAmps
at Rated DC Blocking Voltage								
		50						

- NOTES : 1. Case Temperature Measured at Metal Tab.
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
3. Suffix " A " = Common Anode.

RATING AND CHARACTERISTIC CURVES (RL1601C THRU RL1606C)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL REVERSE CHARACTERISTICS




FIG. 3 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4 - TYPICAL JUNCTION CAPACITANCE





FIG. 5 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



PACKAGING OF DIODE AND BRIDGE RECTIFIERS

BULK PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	GROSS WEIGHT(Kg)
R-1	-B	1,000	194*84*21	465*220*260	50,000	11.74
A-405	-B	1,000	194*84*21	465*220*260	50,000	15.64
DO-41	-B	1,000	194*84*21	465*220*260	50,000	19.64
DO-15	-B	500	194*84*21	465*220*260	25,000	12.84
R-3	-B	500	194*84*21	465*220*260	25,000	17.36
DO-201AD	-B	500	300*73*40	347*320*271	12,000	16.63
R-6	-B	200	300*73*40	347*320*271	4,800	12.87
RS-1	-B	600	236*236*34	502*255*176	4,800	8.50
RB-15	-B	1,000	165*252*59	347*320*271	10,000	12.05
WOM	-B	600	165*252*59	347*320*271	6,000	11.00
RC-2	-B	600	165*252*59	347*320*271	6,000	10.30
RS-2L	-B	400	210*160*52	465*220*260	4,000	14.20
RS-4L	-B	300	225*157*50	502*251*126	1,800	11.30
RS-6/-8	-B	200	236*236*34	502*255*176	1,600	14.50
BR-3	-B	200	206*208*55	465*220*260	1,600	5.94
BR-6	-B	200	206*208*55	465*220*260	1,600	7.32
BR-8/-10	-B	200	236*236*50	497*251*288	2,000	12.24
BR-15/-25/-35(W)	-B	50	206*208*57	465*220*260	400	14.40
MB-15/-25/-35(W)	-B	50	206*208*57	465*220*260	400	16.26
MP-15/-25/-35(W)	-B	50	206*208*57	465*220*260	400	8.13
WB	-B	1,000	236*236*50	497*251*288	10,000	---

TUBE PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	WEIGHT(Kg)
TO-220(A)	-C	2,000	550*140*92	572*308*126	4,000	12.24
D2PAK	-C	2,000	550*140*92	572*308*126	4,000	10.50
TO-247	-C	900	550*140*92	572*308*126	1,800	10.46
BDB	-C	2,000	450*140*84	466*305*295	12,000	14.10
DB-1	-C	2,500	450*140*84	466*305*295	15,000	14.22
DB-S	-C	4,000	450*140*84	466*305*295	24,000	18.44
RS-2M	-C	1,350	540*118*118	560*256*146	2,700	12.80
RS-4M/-10M	-C	900	540*118*118	560*256*146	1,800	14.15
RS-6M/-25M	-C	600	490*135*110	510*290*140	1,200	14.40
RBU4M	-C	1,000	490*135*110	510*290*140	2,000	13.60




Attachment information about RL160XC

1. Internal Circuit



2. Marking on the body



3. Items marked on the inner box and carton

3.1 On the box (for -C)

CUSTOMER
TYPE
LOT NO.
QUANTITY
Q.A.
DATE

3.2 On the carton

CUSTOMER
TYPE
QUANTITY
LOT NO.
REMARK

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.