

DVD-ROM / player single mode 2wavelength laser diode

RLD2WMUV2

This is monolithic type single mode 2wavelength laser diode. With our original technology, realized low threshold current and excellent temperature characteristic. This laser diode is suitable for DVD-ROM and DVD-player.


●Applications

DVD-ROM
DVD player

●Features

- 1) Optimization of a strained multi quantum well realizes the reduction in threshold current, and the good temperature characteristic.
- 2) Low threshold current.
785nm : 18mA (Tc=25°C)
655nm : 20mA (Tc=25°C)
- 3) Low noise is realized by high frequency modulation (BU9369FVM)element.
- 4) Emission point distance : 110μm

●External dimensions (Unit : mm)



●Absolute maximum ratings (Tc=25°C)

785nm

Parameter	Symbol	Limits	Unit	
Output	P _o	7	mW	
Reverse voltage	Laser	V _R	2	V
	PIN photodiode	V _{R(PIN)}	30	V
Operating temperature	T _{opr}	-10 to +70	°C	
Storage temperature	T _{stg}	-40 to +85	°C	

655nm

Parameter	Symbol	Limits	Unit	
Output	P _o	7	mW	
Reverse voltage	Laser	V _R	2	V
	PIN photodiode	V _{R(PIN)}	30	V
Operating temperature	T _{opr}	-10 to +70	°C	
Storage temperature	T _{stg}	-40 to +85	°C	

Laser Diodes

●Electrical and optical characteristics (Tc=25°C)

785nm

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Threshold current	I _{th}	–	18	50	mA	–
Operating current	I _{op}	–	30	60	mA	P _o =5mW
Operating voltage	V _{op}	–	1.9	2.3	V	P _o =5mW
Differential efficiency	η	0.2	0.55	0.8	mW/mA	–
Monitor current	I _m	0.1	0.25	0.5	mA	P _o =5mW
Parallel divergenc angle	θ _{//} *	7	10	15	deg	P _o =5mW
Perpendicular divergenc angle	θ _⊥ *	25	32	39	deg	P _o =5mW
Parallel deviation angle	Δθ _{//}	–2	0	+2	deg	P _o =5mW
Perpendicular deviation angle	Δθ _⊥	–3	0	+3	deg	P _o =5mW
Emission point accuracy	ΔX ΔY ΔZ	–80	0	+80	μm	–
Peak emission wavelength	λ	770	785	810	nm	P _o =5mW
Astigmatism	Δℓ	–	–	10	μm	P _o =5mW



* θ_{//} and θ_⊥ are defined as the angle within which the intensity is 50% of the peak value.

655nm

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Threshold current	I _{th}	–	20	50	mA	–
Operating current	I _{op}	–	28	60	mA	P _o =5mW
Operating voltage	V _{op}	–	2.3	2.7	V	P _o =5mW
Differential efficiency	η	0.4	0.7	1.0	mW/mA	–
Monitor current	I _m	0.1	0.14	0.5	mA	P _o =5mW
Parallel divergenc angle	θ _{//} *	7	8	10	deg	P _o =5mW
Perpendicular divergenc angle	θ _⊥ *	20	27	35	deg	P _o =5mW
Parallel deviation angle	Δθ _{//}	–2	0	+2	deg	P _o =5mW
Perpendicular deviation angle	Δθ _⊥	–3	0	+3	deg	P _o =5mW
Peak emission wavelength	λ	645	655	662	nm	P _o =5mW
Astigmatism	Δℓ	–	–	10	μm	P _o =5mW

* θ_{//} and θ_⊥ are defined as the angle within which the intensity is 50% of the peak value.

●Electrical and optical characteristics curves (Tc=25°C)



Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.