

RLD78NZH1

Laser diodes

AlGaAs laser diodes

RLD78NZH1

The RLD78NZH1 is the laser diode for laser printers that has excellent temperature characteristics and excellent droop characteristics.


●Applications

Laser printers
Optical sensors

●Features

- 1) Absolute max. output power is 5mW.
- 2) High-precision, compact package.($\phi 5.6\text{mm}$)
- 3) Low droop.
- 4) Can be driven by single power supply (N type).

●External dimensions (Unit : mm)



●Absolute maximum ratings ($T_c=25^{\circ}\text{C}$)

Parameter	Symbol	Limits	Unit	
Output	P_o	5	mW	
Reverse voltage	Laser	V_R	2	V
	PIN photodiode	$V_R (PIN)$	30	V
Operating temperature	T_{opr}	-10 to +60	$^{\circ}\text{C}$	
Storage temperature	T_{stg}	-40 to +85	$^{\circ}\text{C}$	

RLD78NZH1

Laser diodes

●Electrical and optical characteristics (Tc=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Threshold current	I _{th}	-	16	45	mA	-
Operating current	I _{op}	-	28	65	mA	P _o =3mW
Operating voltage	V _{op}	-	1.9	2.3	V	P _o =3mW
Differential efficiency	η	0.1	0.25	0.4	mW/mA	$\frac{2mW}{I(3mW) - I(1mW)}$
Monitor current	I _m	0.2	0.45	0.9	mA	P _o =3mW
Parallel divergence angle	θ _∥ *	8	11	15	deg	P _o =3mW
Perpendicular divergence angle	θ _⊥ *	25	30	38	deg	
Parallel deviation angle	Δθ _∥	-	-	±2	deg	
Perpendicular deviation angle	Δθ _⊥	-	-	±3	deg	
Emission point accuracy	$\begin{matrix} \Delta X \\ \Delta Y \\ \Delta Z \end{matrix}$	-100	-	+100	μm	-
Peak emission wavelength	λ	770	785	795	nm	P _o =3mW
Droop	ΔP	-	5	10	%	P _o =3mW

*θ_∥ and θ_⊥ are defined as the angle within which the intensity is 50% of the peak value.

●Electrical and optical characteristic curves




Fig.1 Dependence of I-L on temperature




Fig.2 Dependence of droop on output power and temperature




Fig.3 Parallel far field pattern




Fig.4 Perpendicular far field pattern

Appendix

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.