


ROITHNER LASERTECHNIK

SCHOENBRUNNER STRASSE 7, VIENNA, AUSTRIA

TEL: +43 -1- 586 52 43-0 FAX: +43 -1- 586 52 43-44

office@roithner-laser.com www.roithner-laser.com

RLT1060-100GS TECHNICAL DATA



High Power Infrared Laser Diode

Lasing mode structure: **single mode**

Lasing wavelength: **typ. 1060 nm**

Optical power: **100 mW**


Package: **9 mm (SOT-148)**

NOTE!


LASERDIODE
MUST BE COOLED!



PIN CONNECTION:



- 1) Photodiode cathode
- 2) Laser diode cathode and photodiode anode
- 3) Laser diode anode



Absolute Maximum Ratings (T_c = 25°C)

| CHARACTERISTIC | SYMBOL | RATING | UNIT |
|-----------------------|--------------------|------------|------|
| Optical Output Power | P _o | 120 | mW |
| LD Reverse Voltage | V _{R(LD)} | 1.5 | V |
| PD Reverse Voltage | V _{R(PD)} | 10 | V |
| Operating Temperature | T _C | -20 .. +40 | °C |
| Storage Temperature | T _{STG} | -40 .. +70 | °C |

Optical-Electrical Characteristics (T_c = 25°C)

| CHARACTERISTIC | SYMBOL | TEST CONDITION | MIN | TYP | MAX | UNIT |
|----------------------|-----------------|-------------------------|------|-------|------|-----------------|
| Emitting Aperture | A | cw | | 1 x 5 | | μm ² |
| Optical Output Power | P _o | single mode | | 100 | | mW |
| Threshold Current | I _{th} | cw | 25 | 30 | 35 | mA |
| Operation Current | I _{op} | P _o = 100 mW | 220 | 250 | 280 | mA |
| Forward Voltage | U _f | P _o = 100 mW | | 1.8 | 1.9 | V |
| Lasing Wavelength | λ _p | P _o = 100 mW | 1062 | 1064 | 1067 | nm |
| Spectral Width FWHM | Δλ | P _o = 100 mW | | 0.2 | 0.3 | nm |
| Beam Divergence | θ _{//} | P _o = 100 mW | | 25 | | ° |
| Beam Divergence | θ _⊥ | P _o = 100 mW | | 40 | | ° |
| Monitor Current | I _m | P _o = 100 mW | 0.9 | 1.0 | 1.1 | mA |