

# ROITHNER LASERTECHNIK

A-1040 WIEN, FLEISCHMANNGASSE 9  
 TEL: +43 -1- 586 52 43 FAX: +43 -1- 586 41 43  
 e-mail: rlt@mcb.at <http://www.roithner.mcb.at>

## RLT6505G TECHNICAL DATA

### Visible Wavelength Laserdiode


Structure: **AlGaInP**, index guided, single transverse mode

Lasing wavelength: **650 nm**


Max. optical power: **5 mW**

Package: **9 mm G** or **5.6mm MG**

#### PIN CONNECTION:



- 1) Laser diode cathode
- 2) Laser diode anode and photodiode cathode
- 3) Photodiode anode



#### Maximum Ratings (Tc=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Optical Output Power	$P_o$	5	mW
LD Reverse Voltage	$V_{R(LD)}$	2	V
PD Reverse Voltage	$V_{R(PD)}$	30	V
Operation Case Temperature	$T_C$	-10 .. +40	°C
Storage Temperature	$T_{STG}$	-40 .. +85	°C

#### Optical-Electrical Characteristics (Tc = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Optical Output Power	$P_o$	kink free			5	mW
Threshold Current	$I_{th}$		20	30	40	mA
Operation Current	$I_{op}$	$P_o = 5mW$		45	70	mA
Operating Voltage	$V_{op}$	$P_o = 5mW$		2.2	2.7	V
Lasing Wavelength	$\lambda_p$	$P_o = 5mW$		650	655	nm
Beam Divergence	$q_1$	$P_o = 5mW$	5	8	11	°
Beam Divergence	$q_2$	$P_o = 5mW$	25	31	37	°
Astigmatism	As	$P_o = 5mW, NA=0.4$		11		$\mu m$
Monitor Current	$I_m$	$P_o = 5mW, V_r=5V$		10		$\mu A$